



**Service Attachment
To AT&T Network on Demand Pricing Schedule
For AT&T Inside Wiring**

This AT&T Inside Wiring Service Attachment ("Attachment") is an attachment to the **AT&T NETWORK ON DEMAND PRICING SCHEDULE Provided Pursuant to Custom Terms** entered into by AT&T and Customer (the "Pricing Schedule"), and is incorporated into the Pricing Schedule. In the event of a conflict between the terms of this Attachment and the Pricing Schedule, the terms of the Pricing Schedule shall govern. At such time, if any, that an AT&T Service Publication is published for AT&T Inside Wiring, this Service Attachment will be superseded by such Service Publication.

Service Description

1. AT&T Inside Wiring – Availability

AT&T Inside Wiring is an optional service, available when Customer orders a new AT&T Switched Ethernet Service SDN Port Arrangement at an eligible building location.

2. AT&T Inside Wiring – Specifications

AT&T Inside Wiring consists of the installation of fiber or copper cabling from the AT&T network interface to a patch panel that AT&T will provide and install at the Customer's Site. AT&T will provide cabling, materials and installation, as determined by AT&T based on the AT&T Switched Ethernet Port Interface ordered by the Customer. AT&T may furnish used or refurbished materials that are functionally equivalent to new.

The following technical specifications apply to AT&T Inside Wiring:

Port Interface	Cabling Type	Maximum Distance	Connector Type
100 Mbps Electrical	Copper cable (Cat-6)	Up to 100 meters (328 feet)	RJ-45
1 Gbps Electrical			
1 Gbps Multi-Mode Optical	Multi-mode fiber cable (50/125 micron)	Up to 500 feet	SC
1 Gbps Single-Mode Optical	Single-mode fiber cable (9/125 micron)		

AT&T and Customer will cooperate in good faith to determine the routing and configuration of AT&T Inside Wiring.

3. AT&T Inside Wiring – Site Requirements

Customer must comply with the requirements below with respect to the Site and work areas. AT&T will determine Customer's compliance with those requirements, in its sole discretion.

- AT&T must be allowed to place facilities in the building and must have sufficient space to perform the work.
- The pathway must be open and free of insulation or other obstructions, and must have easily accessible drop-in panels or crawl space.
- Walls must be open, and free of insulation or other obstructions, and must be easily fishable with a clear path.

**Service Attachment
To AT&T Network on Demand Pricing Schedule
For AT&T Inside Wiring**

- Any necessary conduits and inner ducts that are to be used must be free and clear with pull strings, adequate pull boxes, and sufficient capacity for cabling installation as required. Conduit with a pull string is preferred, but is not a requirement as long as AT&T has a clear path for cabling.
- Additional charges may apply if Inside Wiring installation requires as solely determined by AT&T, special equipment or construction activity (such as scissor lifts, extension ladder, hammer drill, concrete saw, jackhammer, etc.).
- Any existing wiring to be used must be owned or controlled by Customer.

4. AT&T Inside Wiring – Additional Customer Responsibilities

- Customer must obtain all necessary permissions or approvals from the landlord or building owner for installation of AT&T Inside Wiring.
- Customer must give or obtain from the landlord or building owner, as appropriate, permission to AT&T to use any existing wiring owned or controlled by Customer, the landlord or the building owner, and to remove any existing equipment or accessories from such wiring, if such wiring is to be used in the provision of AT&T Inside Wiring.
- Customer must provide or arrange for reasonable access to the site and work areas during AT&T's normal business hours.
- Customer must provide a safe worksite for AT&T employees, including, but not limited to: (1) promptly notifying AT&T of any worksite hazards such as presence of asbestos or other hazardous substances; (2) removing worksite hazards, when the removal of such hazards is necessary to allow AT&T to safely install inside wiring; and (3) paying the cost of removing such hazards or taking other appropriate safety measures. AT&T reserves the right to refuse to perform work on any premises it deems unsafe.
- Customer must provide sufficient space in any computer room, telephone closet, equipment room, or electrical room to install cables.
- Customer must provide copper cable (RJ-45 connectors) or duplex fiber connectorized cable (SC connectors) to connect the Customer's network equipment to the patch panel at the Customer's Site.
- Customer must comply with all other Site preparation requirements, if any, provided by AT&T, in writing, if AT&T reasonably deems such requirements necessary for the completion of its installation of AT&T Inside Wiring.
- Customer or landlord, as appropriate, assumes full ownership and responsibility for the inside wiring upon completion of installation.
- Customer must indemnify and hold AT&T harmless from and against all damages and claims by any owner, landlord, building manager, and other third parties in connection with installation, maintenance, repair, or provision of AT&T Inside Wiring.
- Customer must satisfy the obligations set forth above in a timely manner.

5. AT&T Inside Wiring – Exclusions

AT&T Inside Wiring does not include the following:

- Conduits or inter-building pathways or cabling;
- Removal and/or replacement of interlocking ceiling tiles;
- Removal of existing inside wiring; or
- Signal repeaters/extenders, media convertors, enclosures or "fiber bulk heads."

**Service Attachment
To AT&T Network on Demand Pricing Schedule
For AT&T Inside Wiring**

6. AT&T Inside Wiring – Warranty

THE FOLLOWING LIMITED 30-DAY WARRANTY APPLIES:

AT&T will install AT&T Inside Wiring in a workmanlike manner. If installation is not performed in a workmanlike manner, or if AT&T Inside Wiring does not adequately perform as required, and if Customer provides notice of such inadequacy within thirty (30) days after installation, AT&T will correct the inadequacy in a commercially reasonable manner at no additional charge. This limited warranty is Customer's sole remedy for AT&T Inside Wiring and for its installation or repair.

AT&T MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, TO CUSTOMER OR ANY OTHER PARTY FOR ANY WORK OR MATERIALS CONSTITUTING OR ASSOCIATED WITH AT&T INSIDE WIRING. IN ADDITION TO OTHER DISCLAIMERS IN THE AGREEMENT, AT&T EXPRESSLY DISCLAIMS ANY RESPONSIBILITY TO MAINTAIN, UPDATE, REPAIR, REPLACE, OR REMOVE ANY INSTALLED AT&T INSIDE WIRING.

Pricing

7. AT&T Inside Wiring – Pricing

If AT&T determines that AT&T Inside Wiring can be provided as described in this Service Attachment, the following flat rate non-recurring charges will apply:

- AT&T Inside Wiring Charge: \$600.00 on a per port basis.

Cancellation Charge: If Customer cancels an order (other than as permitted because of default by AT&T), or AT&T cancels an order for AT&T Inside Wiring for cause prior to installation, Customer will reimburse AT&T for time, materials and expenses incurred prior to the effective date of such cancellation, plus any third party charges resulting from the cancellation.

End of Document