B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

CONTENTS

B103.1.1 General 1 B103.1.2 Application 1.0.1 B103.1.3 Rate Categories 1.0.1 B103.1.4 Service Configurations 1.0.2 B103.1.5 Special Routing Of IntraLATA Channels 1.0.2 B103.2 Service Descriptions 1.1 B103.2.1 Sub Voice Grade Services - Series 1000 1.1 B103.2.2 Voice Grade Service - Series 2000 3	(T)
B103.1.3 Rate Categories 1.0.1 B103.1.4 Service Configurations 1.0.2 B103.1.5 Special Routing Of IntraLATA Channels 1.0.2 B103.2 Service Descriptions 1.1 B103.2.1 Sub Voice Grade Services - Series 1000 1.1 B103.2.2 Voice Grade Service - Series 2000 3	(T)
B103.1.4 Service Configurations 1.0.2 B103.1.5 Special Routing Of IntraLATA Channels 1.0.2 B103.2 Service Descriptions 1.1 B103.2.1 Sub Voice Grade Services - Series 1000 1.1 B103.2.2 Voice Grade Service - Series 2000 3	(N)
B103.1.5 Special Routing Of IntraLATA Channels 1.0.2 B103.2 Service Descriptions 1.1 B103.2.1 Sub Voice Grade Services - Series 1000 1.1 B103.2.2 Voice Grade Service - Series 2000 3	(N)
B103.2 Service Descriptions 1.1 B103.2.1 Sub Voice Grade Services - Series 1000 1.1 B103.2.2 Voice Grade Service - Series 2000 3	(N)
B103.2.1 Sub Voice Grade Services - Series 1000 1.1 B103.2.2 Voice Grade Service - Series 2000 3	(N)
B103.2.2 Voice Grade Service - Series 2000	(T)
	(T)
D102.2.2 W' 1.M ' G ' G ' C000	(T)
B103.2.3 Wired Music Service - Series 6000 3.1.2	(T)
B103.3 Rate Terms and Conditions 3.2	(T)
B103.3.1 Types of Rates and Charges 3.2	(T)
B103.3.2 Moves 3.2.1	(T)
B103.3.3 Mileage Measurements 3.2.1	(T)
(DELETED)	(D)
B103.4 Rates and Charges 3.3	(T)
B103.4.1 Sub Voice Grade Service – Series 1000 3.3	(N)
B103.4.2 Voice Grade Service – Series 2000 5	(N)
B103.4.3 Series 7000 Channels 5	(N)
B103.4.4 Local Channels 6	(N)
B103.4.5 Interoffice Channels 6.1	(N)
B103.4.6 Optional Feature and Functions 6.2	(N)
B103.5 Non-Wire Center Connected Channels 7.1	(T)
B103.6 Series 10000 Channels (Entrance Facilities) 8	
B103.6.1 Types And Description 8	
B103.6.2 Terms and Conditions 8	
B103.6.3 Rates - Monthly Service 8	
B103.7 (DELETED) 8	(T)
B103.8 Local Area Data Channels 8.1	(T)
B103.9 Reserved For Future Use 8.1	(T)
B103.10 Description Of Service And Rates - Customer Operating	
Center Service (COCS)	

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

(T)

(N)

(T)

(M)

(O)

(O)

(O)

(T)

(T)

(T)

(T)

(T)

B103.1 Provision of Service Effective June 30, 2021 Channel Services will no longer be available for purchase by new or existing customers. In addition, requests

Effective June 30, 2021, Channel Services will no longer be available for purchase by new or existing customers. In addition, requests to move, add, change, or renew existing service arrangements will not be accepted. Following the expiration of a customer's existing term agreement, service will be provided on a month-to-month basis at the applicable Monthly rates until the service is discontinued. The Company currently plans to discontinue these services on or after June 30, 2024 (December 1, 2021 for Wired Music Service).

Effective October 11, 1985, Sub Voice Grade Service - Series 1000 is obsoleted, Type A.

Effective December 1, 2020, Obsoleted, Type D; *Wired Music Service – Series 6000 is* not available for new installations, moves or transfers. The Company intends to discontinue this service on or after December 1, 2021.

B103.1.1 *General* (T)

- **A.** Channel Services provided under the provisions of this Guidebook are offered for IntraLATA Services only. Services consisting of Local Channels, Interoffice Channels, and Optional Features and Functions are classified by series. The various series are sub-divided into different types and are described in terms of circuit characteristics and use.
- **B.** Customers may order local channels which are designed to meet specific communications requirements. The customer is responsible for determining that his terminal equipment is compatible with the service provided by the Company.
- responsible for determining that his terminal equipment is compatible with the service provided by the Company.

 C. Where multipoint service is furnished, the local channels are bridged in the wire center.
- D. Dedicated circuits between the customer's interLATA Digital Electronic Tandem Switching (DETS) or Tandem Switching Features (TSF) functions and the customer's other location(s) within the same LATA will be provided from this Guidebook. Where this service is provided by the Company as a feature of ESSX service, Digital ESSX service, MultiServ Service, MultiServ PLUS service, or BellSouth Centrex service, the transport of traffic between the DETS or TSF function and the basic ESSX service, Digital ESSX service, MultiServ Service, MultiServ PLUS service or BellSouth Centrex service functions may be performed by the Company's network switching facilities.
- E. Methods Of Applying Rates
 - Additional Point Of Termination Of A Local Channel In Different Buildings On The Same Premises
 (Obsoleted 01-01-87, Type B)
 A charge, as provided in B103.1.1 E.1.b. following, for extending a Local Channel and terminating the charge.
 - a. A charge, as provided in B103.1.1.E.1.b. following, for extending a Local Channel and terminating the channel at a station location in a different building on the same premises shall apply in lieu of an additional Local Channel Charge when conditions and facilities permit, otherwise the local channel charge applies.
 - b. When additional points of termination of a single private line service are located in different buildings on the same premises, the charge for the channel shall be based on the airline distance between each pair of buildings. The rates are specified in *B103.4* (*Intraexchange and Interexchange*) following.
 - 2. Additional Point of Termination of a Local Channel in the Same Building (Obsoleted 01-01-87, Type B)
 - A charge as provided in *B103.4 (Intraexchange and Interexchange)* following for extending a Local Channel and terminating the channel at a station location in the same building applies in lieu of an additional local channel charge.
 - Same Building
 - (Obsoleted 01-01-87, Type D; customers may add channels only to the extent that they are available within facilities in place as of the date of this obsolescence)
 - When all station locations of a private line service are in the same building, the charge for same building channel specified in *B103.4 (Intraexchange)* following applies.
 - 4. Channels Between Buildings on the Same Premises
 - (Obsoleted 01-01-87, Type D; customers may add channels only to the extent that they are available within facilities in place as of the date of this obsolescence)
 - When station locations of a private line service are located in different buildings on the same premises the charge for the channel shall be based on the airline distance between each pair of buildings when conditions and facilities permit. The charges are as specified in *B103.4* (*Intraexchange*) following.
 - Where a supporting structure is necessary for the purpose of furnishing these channels on the subscriber's premises, such supporting structure will be furnished by the subscriber as provided for in "Construction on Private Property" in Section A5. of the General Exchange Guidebook.

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.1 Provision of Service (continued)

B103.1.2	Application	(T)(O)			
The	e rates and charges specified herein apply for all IntraLATA Private Line services provided by the Company.	(O)			
B103.1.3	Rate Categories	(T)(O)			
A. Following are the basic rate categories which apply to Private Line service.					
1.	Local Channels	(O)			
	a. A local channel provides for a communications path between the demarcation point at a customer premises and the serving wire center of that premises. One local channel charge applies per channel termination.	(O)			
	b. When service is provided by non-wire center connected channels, a non-wire center connected channel charge applies in lieu of local channel charges. (See Section B103.4 for channel charges).	(O)			
2.	Interoffice Channels	(O)			
	This rate category provides for the transmission facilities between serving wire centers associated with two customer premises, between serving wire centers associated with a customer premises and a Company hub, or between two Company hubs.	(O)			
	Interoffice mileage is portrayed in mileage bands. A flat rate and a rate per mile applies to each band. For method of determining mileage, see <i>B103.3.3.A</i> .	(T)(O)			
3.	Non-Wire Center Connected Channels	(O)			
	Served Direct channels are provided on a direct basis and are limited to one airline mile in length. These channels will be provided only at the option of the Company.	(O)			
	Obsoleted, See Section B103.4 for charges for channels.	(O)			
4.	Optional Features and Functions	(O)			
	This rate category provides for features and functions which may be added to a service to improve its quality or utility to meet specific communications requirements. These are not necessarily identifiable with specific equipment, but rather represent the end result in terms of the performance characteristics which may be obtained. This category includes a. and b. following:	(O)			
	a. Hub Functions	(O)			
	A hub is a Company designated wire center where bridging or multiplexing functions are performed i.e., connecting three or more customer premises in a multipoint arrangement or channelizing analog or digital services requiring a lower capacity or bandwidth.	(O)			
	b. Provides for such things as signaling, conditioning, transfer arrangements, protection switching, etc.	(O)			

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.1 Provision of Service (continued)

B103	.1.4	Serv	ice Configurations	(T)(O)			
A.	The	There are two types of service configurations which can be provided. These are described as follows:					
	1.	Τv	vo-Point Service	(O)			
			two-point service connects two customer premises either directly through a serving wire center(s) or through a mpany hub where additional functions are performed.	(O)			
	2.	M	altipoint Service	(O)			
		a.	Multipoint service connects three or more customer premises through a Company hub.	(O)			
		b.	There is no limitation on the number of mid-links available with multipoint service. However, when more than three mid-links are provided in tandem, the quality of the service may be degraded. A mid-link is a channel between hubs (i.e., bridging locations).	(O)			
		c.	Voice Grade (Series 2000) Multipoint Channel services for data use have a limit of six two-wire facility type local channels or 20 four-wire facility type local channels when used with customer-provided station equipment.	(O)			
		d.	Only certain types of service are available for multipoint applications. These are so designated in the service descriptions set forth in <i>B103.2</i> following.	(T)(O)			
B103	.1.5	Spec	cial Routing Of IntraLATA Channels	(T)(O)			
A.	The	priv	rate line services furnished in this Guidebook are provided over such routes as the Company may elect.	(O)			
В.			routing is involved where, in order to comply with requirements specified by the customer, the Company furnishes the ine service in a manner which includes one or both of the following conditions:	(O)			
	1.	W	here two or more private lines must be furnished over different physical routes.	(O)			
	2.	W	here a private line must be furnished on a route which avoids specified geographical locations.	(O)			
C.	Wh	en sj	pecial routing of services is furnished a customer, the rates will be determined on an individual case basis.	(O)			

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.2 Service Descriptions

(T)

B103.2.1 Sub Voice Grade Service - Series 1000

(T)

A. The following types of Sub Voice Grade Services are designed for transmission of low speed data at speeds up to 75 and up to 150 baud within certain technical specifications. These channels are furnished for half duplex and duplex operation for use with two-point or multi-point Private Line Services. The service is not suitable for the transmission of alternating current tones.

(M1) (O)

These channels are furnished for operation on a two point or multipoint basis subject to the number of point limitations indicated for each type and are provided for use with customer-provided power and signaling equipment. It is expressly declared that metallic facilities are in continually decreasing supply and that the Company does not hold itself in a position to make such facilities available. In addition, if modernization programs dictate the replacement of existing metallic facilities with non-metallic facilities such as fiber optics, the Company will not be required to continue this service over metallic facilities. In consideration of the decreasing supply of metallic facilities, the Company will convert a customer's service requiring such facilities to a Voice Grade Service and waive the nonrecurring charges associated with the change. This applies to customers where metallic facilities are being replaced with non-metallic facilities, or a customer may elect to make this change at any time prior to a modernization program that would eliminate the availability of metallic facilities.

The various types of services furnished within this Series are as follows.

. The types of local channel and the transmission characteristics offered for termination at a premises are as follows:

1. Type 1050 (Interexchange)

(T)(M) (M)

A four wire interface engineered for binary signals at rates up to 75 baud, 20 or 62.5 milliamperes dc neutral signals. The terminal equipment with a transmitted output of no more than 8 percent telegraph distortion local and capable of processing received data signals with up to 35 percent telegraph distortion.

The Company has the option of providing 20 or 62.5 milliamperes and will notify the customer of the current level to be supplied. The Company will supply the line voltage and provide for the current adjustment. The maximum open circuit voltage across the send data leads at the interface will not exceed 270 volts.

(111)

2. Type 1051 (Interexchange)

(T)(M)
(M)

EIA Standard RS232B type interface engineered for binary signals at rates up to 150 baud and the terminal equipment with a transmitted output of not more than 5 percent telegraph distortion and capable of processing received data signals with up to 40 percent telegraph distortion.

(T)

3. Type 1150 (Intraexchange)

(T)

A four-wire interface engineered for binary signals at rates up to 75 baud, 20 or 62.5 milliamperes dc neutral signals. The terminal equipment with a transmitted output of no more than 8 percent telegraph distortion local and capable of processing received data signals with up to 35 percent telegraph distortion.

The Company has the option of providing 20 or 62.5 milliamperes and will notify the customer of the current level to be supplied. The Company will supply the line voltage and provide for the current adjustment. The maximum open circuit voltage across the send data leads at the interface will not exceed 270 volts.

(T)

4. Type 1151 (Intraexchange)

(T)(O)

EIA Standard RS232B type interface engineered for binary signals at rates up to 150 baud and the terminal equipment with a transmitted output of not more than 5 percent telegraph distortion and capable of processing received data signals with up to 40 percent telegraph distortion.

Type 1204

σ (O)

A two-wire interface with two-wire facilities suitable for use with direct current continuity type of equipment. Signaling must be within the criteria as described in Technical Reference, "Transmission Specifications for Private Line Metallic Circuits" and limited to three station locations. This type channel may also be used to furnish auxiliary features (such as lights, hold, signaling, etc.)

(O)

Current applied by CPE - ac & dc components per conductor, not to exceed 0.150 amperes rms

Magnitude of the peak of the voltage between any conductor and ground - not to exceed 70.7 volts (50 volts rms) except continuous dc voltage not to exceed 135 volts.

(O) (T)(O)

6. Type 1205

(1)(O) (O)

A two-wire interface with two-wire facilities suitable for low speed, uni-directional series-operated signaling. Transmission specifications as described in Technical Reference, "Transmission Specification for Low Speed Signaling System Channels". Service is limited to three serving wire centers and 26 stations.

(M2)

B103.	2 <i>S</i>	ervi	ce Descriptions (Cont'd)	(T)
B103	3.2.1	Sub	Voice Grade Service - Series 1000 (Cont'd)	(T)
C.			ers and Specifications for Sub Voice Grade Local Channels used with Customer Provided Station Equipment (CPE) is d in <i>B103.2.1.B</i> (1. through 4.). The following type specifications apply.	(T)(M)
	1.	Ba	sic Parameters With Specification Or Limit	(M)
		a.	Channel Signals	(M)
			Local Channels used with CPE - as specified in <i>B103.2.1.B</i> (1. through 4.). Note that the specifications of channel signals refer to the requirement of the total service offering and not the individual local channel.	(T)(M)
		b.	Channel Distortion	(M)
			Local Channels used with CPE - as specified in <i>B103.2.1.B</i> (1. through 4.) Note that the specifications for channel distortion refer to the requirement of the total service offering and not the individual local channel.	(T)(M)
		c.	Power Requirement	(M)
			For up to 75 Baud Type - Where the Company provides transmission equipment at the interface. The customer must provide a source of continuous 117 volt, 60 Hz ac power by means of a nonswitched outlet.	(M)
			For up to 150 Baud - Customer must in all cases provide a source of continuous 117 volt, 60 Hz ac power, nonswitched outlet.	(M)
			The Company will in all cases supply all voltage and current adjustments.	(M)
			These channels are not suitable for the transmission of alternating current tones.	(M)
D.	(DE	ELET	TED)	(D)(M)
				(M1)

		B103. OBSOLETE S	SERVICE OFFERING	GS - CHANNELS	(M)	
					(1VI)	
		ervice Descriptions (Cont'd)			(T)(O)	
B103	.2.2	Voice Grade Service - Series 2000			(T)(O)	
A.	day: cha whi	s per week, 24 hours per day, for a minimum nnel) basis when connected to services such a	period of one month. These ones FlexServ service, LightGate and to connect a flat rate system	s on a two-point or multipoint basis for service 7 channels may also be furnished on a link (partial service or MegaLink channel service. Channels m with a message rate system. The transmission scribed in B. and C. following.	(O)	
В.				scribed for the end to end operation as follows:	(O)	
		Basic Parameters	For Speech Application For Data Application			
		Net Loss		ninal equipment: Limit as specified in the following osses or gains present in CPE have not been	(O)	
		DC Resistance	Local Channel limit as specifie Does not imply or guarantee er	ed in the following Local Channel descriptions.	(O)	
		Frequency Error	Plus or Minus 5 Hz	Plus or Minus 5 Hz	(O)	
		Frequency Response	(Referenced to 1000 Hz Loss)		(O)	
		300 - 3000 Hz	-3dB to + 12dB	-3dB to +12dB		
		500 - 2500 Hz	-2dB to $+8dB$	-2dB to $+8dB$		
		Envelope Delay Distortion			(O)	
		800 - 2600 Hz	Not Controlled	Less than 1750 Microseconds	(O)	
		C-Notched Noise (with a -13dBm0 1000 Hz Test Signal)	Not Controlled	Noise level 24dB below signal level	(O)	
		Impulse Noise	Not Controlled	15 Counts in 15 minutes at a threshold of 6dB below a -13dBm0 rms 1000 Hz Signal	(O)	
		Phase Jitter Non-Linear Distortion	Not Controlled	10 degrees peak to peak	(O) (O)	
		2nd Order Distortion 3rd Order Distortion	Not Controlled Not Controlled	25dB below signal level 30dB below signal level	(O) (O)	
C.	Trai	nsmission parameters for voice grade service		Soud below signal level	(O)	
	1. Type 2230 - A two-wire interface with effective two-wire facilities engineered for a 1004 Hz net loss of 0 to 10dB. Generally furnished for voice transmission - Private Line Telephone, Mobile Radio Telephone, or Supervisory Control Use. Multipoint service may be provided at charges specified in <i>B103.4.6.A.</i> following.					
	2.			neered for a 1004 Hz net loss of 0dB to 4.5dB. extension station services. Signaling is required	(O)	
	3.	Type 2432 - A two or four-wire interface PBX's or customer-provided communication		ities engineered for tie line service use between red for this service.	(O)	
	4.			rire center where loop facilities are not required. en ESSX-1 Systems and may be connected with	(O)	
	5.			ngineered for a 1004 Hz net loss of 0 to 16db. e provided at charges specified in <i>B103.4.6.A</i> .	(T)(O)	
	6. Type 2261 - A two-wire interface with effective two-wire facilities engineered for use in Tele Service (TABS).		agineered for use in Telemetry/Alarm Bridging	(O)		
	7.	Type 2462 - A four-wire interface with e Service (TABS).	ffective four-wire facilities er	ngineered for use in Telemetry/Alarm Bridging	(O)	
	8.			or a 1004 Hz net loss of 16dB. Generally used in d at charges specified in <i>B103.4.6.A.</i> following.	(T)(O)	
	9.	Type 2464 - A two-wire interface with fou	r-wire facilities engineered fo	r a 1004 Hz net loss of 16dB. Generally used in at charges specified in <i>B103.4.6.A.</i> following.	(T)(O)	

				(M)
B103.	2 Se	ervi	ce Descriptions (Cont'd)	(T)(O)
B103	.2.2	Voic	e Grade Service - Series 2000 (Cont'd)	(T)(O)
D.	Sig	nalin	g Arrangements	(O)
	1.	Of	f Premises Stations	(O)
		a.	For use with PBX (or similar system) off-premises channels for terminal equipment. Signaling arrangements are furnished for grandfathered and registered PBX (or similar) systems in accordance with Part 68 of the FCC Rules and Regulations or for customer-provided communications systems not subject to Part 68 of the FCC Rules and Regulations.	(O)
			Type A - Furnished for use with Class A PBX (or similar) system station ports capable of operation over loops with resistance in the range of 0-199 ohms.	(O)
			Type B - Furnished for use with Class B PBX (or similar) system station ports capable of operations over loops with resistance in the range of 200-899 ohms.	(O)
			Type C - Furnished for use with Class C PBX (or similar) system station ports capable of operation over loops with resistance in the range of 900 ohms or more.	(O)
		b.	For connections to registered or grandfathered PBX (or similar) system equipment, the customer must specify the equipment capability for use with Type A, B, or C Signaling Arrangements.	(O)
	2.	Tie	e Lines	(O)
		a.	E&M signaling is provided for use with tie line channels with E&M signaling interfaces. Signaling Arrangements are furnished for grandfathered and registered PBX's in accordance with Part 68 of the FCC Rules and Regulations or for customer-provided communications systems not subject to Part 68 of the FCC Rules and Regulations.	(O)
			- An E&M Signaling Arrangement is required for each tie line termination, operating in a Dial Repeating mode, at a customer's premises with a registered PBX.	(O)
			- An E&M Signaling Arrangement is required for each tie line termination at a customer's premises with grandfathered PBX's when the tie line is arranged with an E&M signaling interface.	(O)
			- An E&M Signaling Arrangement is not required with Types 2432 and 2434 channels for additions to or for new installations of grandfathered PBX equipment when not arranged with an E&M signaling interface.	(O)
			- An E&M Signaling Arrangement is required for each Type 2432 or 2434 channel termination at a customer's premises with a customer-provided communications system not subject to Part 68 of the FCC Rules and Regulations when arranged with an E&M signaling interface.	(O)

				(M)
B103	<i>.2</i> S	erv	ice Descriptions (Cont'd)	(T)(O)
B103	3.2.2	Voic	e Grade Service - Series 2000 (Cont'd)	(T)(O)
Е.			ry/Alarm Bridging Service (TABS)	(T)(O)
	1.		ms and Conditions	(O)
		a.	This section contains the terms and conditions applicable for Telemetry/Alarm Bridging Service (TABS)	(O)
		b.	Except as otherwise specified following, the terms and conditions contained herein are in addition to the terms and conditions found in other sections of this Guidebook.	(O)
		c.	TABS requires the use of equipment as specified in <i>B103.2.2.E.</i> and Type 2261 or 2462 voice grade local channels described in <i>B103.2.2.C.</i>	(T)(O)
		d.	Terminal equipment provided by the customer for use with TABS must meet specifications for such customer-provided equipment found in other sections of this Guidebook.	(O)
		e.	No more than 128 remote stations may be connected to a master station over an individual Split Band Active Bridge.	(O)
		f.	In Split Band Active Bridging arrangements, secondary bridges must be directly connected to the primary bridge via mid-link channels. Secondary bridges cannot be connected through other secondary bridges to allow additional layers of tandeming.	(O)
		g.	Secondary bridges, utilized in Split Band, Active Bridging arrangements, reduce the two-wire remote station capacity of the primary bridge. The initial secondary bridge reduces the primary bridge capacity by twelve two-wire remote station connections. Each subsequent secondary bridge reduces the primary bridge capacity by four additional two-wire remote station connections. At the customer's option external bridging may be provided for connecting secondary bridges at the rate applicable in <i>B103.4.6.A.1.a.</i> without reducing the two-wire capacity of the primary bridge.	(T)(O)
		h.	Standard multipoint bridging charges as provided in other sections of this Guidebook are not applicable to TABS, except as provided in g. preceding.	(O)
		i.	Access over four-wire master station channels for Split Band Active Bridging is provided using a Type 2462 local channel.	(O)
		j.	Access over remote station channels is provided through a Type 2261 local channel and through the appropriate channel connection as contained in <i>B103.4.6.A.1.c.</i> following. Interconnection of remote stations located outside the serving wire center where the bridge to which they are to be connected is located will require interoffice channels at charges contained in <i>B103.4.5</i> .	(T)(O)
		k.	Access over each four-wire mid-link channel for Split Band Active Bridging is through voice grade interoffice channels at charges contained in <i>B103.4.5</i> . Additionally, mid-link channel connections are required as described in <i>B103.4.6.A.1.c.</i> following.	(T)(O)
	2.	Se	ervice Description	(O)
		a.	Telemetry/Alarm Bridging Service is a multi-station, voice frequency, private line service designed to provide connections between a master station and a number of remote stations simultaneously. Direct transmission between remote stations is not intended. This service is intended for application in multipoint, voice frequency, data or tone signaling arrangements with transmission at rates up to 400 baud.	(O)
		b.	TABS is provided in the following arrangement:	(O)
			Split Band, Active Bridging - A bridging arrangement providing for a four-wire (master station or mid-link channel) frequency split common port and multiple two-wire (remote station) ports intended for application in multipoint, voice frequency, data or tone signaling arrangements. Two-way (polling) communication between the master station and each remote station is intended.	(O)

				(M)
B103.	2 S	erv	ice Descriptions (Cont'd)	(T)(O
B103.	2.3 V	Vire	ed Music Service - Series 6000	(M1)
Α.	rec hou	ordir ırs p	6000 private line service provides for one way audio transmission for use in connection with loudspeaker and sound ag equipment. Channels are furnished for operation on a two-point or multipoint basis for service 7 days per week, 24 er day, for a minimum period of one month. These channels are arranged for use with customer-provided station ent only.	(M1)
В.	Cha	anne npar	Is for audio and wired music are furnished only directly to the customer originating the program material. The my does not allocate charges between, nor collect charges from the patrons of the customer. The customer is responsible payment of all charges for channels furnished to him by the Company.	(M1)
С.	Au	dio C	Channels	(M1)
	1.		adio private line channels are specially equipped channels provided for the closed circuit (non-broadcast) transmission voice and music signals in one direction only for operation on a two-point basis.	(M1
		Ar	ny of the following arrangements may be provided as a two-point audio private line service:	(M1
		a.	Two local channels in the same wire center area connected together at the serving central office.	(M1
		b.	Two local channels not in the same wire center area connected by an interoffice channel.	(M1
		c.	One local channel feeding a music distribution amplifier when the music source is in the same wire center area as the distribution amplifier.	(M1
		e.	One local channel and an interoffice channel feeding a music distribution amplifier when the music source is not in the same wire center area as the distribution amplifier.	(M1
		f.	One interoffice channel connecting music distribution amplifiers in different wire center areas.	(M1
	2.	Th	ne various types of services furnished as audio channels are described as follows:	(M1
		a.	Type 6211 - A two-wire interface with effective two-wire facilities engineered for a 1000 Hz maximum loss of 12dB without equalization.	(M1
		b.	Type 6212 - A two-wire interface engineered for a 1000 Hz maximum loss of $12dB$ and equalized to + or - $1dB$ of the 1000 Hz loss from 100 to 5000 Hz.	(M1
		c.	Type 6213 - A two-wire interface engineered for a 1000 Hz maximum loss of $12dB$ and equalized to + or - $1dB$ of the 1000 Hz loss from 50 Hz to 8000 Hz.	(M1
D.	Wi	red N	Music Multipoint Distribution Channels	(M1
	1.		ired music multipoint distribution private line channels are specially equipped channels provided for the closed circuit on-broadcast) transmission of voice and music signals in one direction only for operation on a multipoint basis.	(M1
	2.	so	wired music multipoint distribution service consists of one or more distribution amplifiers feeding multiple wired usic local channels within a wire center area. Local channels and interoffice channels required to connect the music urce to the wired music multipoint distribution system or to connect distribution amplifiers in separate wire centers are ovided as two point audio channels.	(M1
		a.	Distribution amplifiers provided by the Company are required to receive signals from a source provided by the customer and to transmit the appropriate signal level to the multiple wired music local channels which the amplifiers may feed. Distribution amplifiers are provided at the serving wire center.	(M1
		b.	Wired music local channels are furnished within a wire center area between the premises of the patrons of the wired music service and the distribution amplifier located in the serving wire center.	(M1
	3.	Th	ne various types of services furnished as wired music channels are described as follows:	(M1
		a.	Type 6215 - A two-wire interface with effective two-wire facilities engineered for a 1000 Hz maximum loss of 14dB without equalization.	(M1
		b.	Type 6216 - A two-wire interface engineered for a 1000 Hz maximum loss of $14dB$ and equalized to + or - $4dB$ of the 1000 Hz loss from 100 to 5000 Hz.	(M1
		c.	Type 6217 - A two-wire interface engineered for a 1000 Hz maximum loss of 14dB and equalized to + or - 4dB of the 1000 Hz loss from 50 Hz to 8000 Hz.	(M1)

				(M
B103.	<i>3</i> Ra	ate	Terms and Conditions	(T)(O
B103	.3.1	Гурс	s of Rates and Charges	(T)(O
A.	The	two	types of rates and charges are monthly rates and nonrecurring charges and are described as follows:	(O
	1.	Mo	nthly Rates	(O
			nthly rates are recurring charges that apply each month or fraction thereof that a service is provided. For billing boses, each month is considered to have 30 days.	(O
		Ra	es applicable to a month-to-month payment option are subject to Company initiated changes.	(O
	2.	No	nrecurring Charges	(O
			are are installation of service, installation of features and functions and service rearrangements.	(O
		a.	Installation of Service	(O
			Nonrecurring charges apply for each service terminated at the customer's premises. For the installation of local channels when more than one of the same type of service, between the same locations, for the same customer is ordered and installed at the same time, one at each location is billed at the First Service Installed rate and the others are billed at the Additional Service Installed rate.	(O
			The nonrecurring charges for the Installation of Services are set forth in <i>B103.4</i> following as Nonrecurring Charges for the Local Channel and Interoffice Channel rate elements.	(T)(O
		b.	Nonrecurring charges apply for the installation of features and functions available with the various services. For some features and functions there is a lower charge if installed coincident with the service and a higher charge if installed subsequent to the service.	(O
		c.	Service Rearrangements	(O
			(1) Service rearrangements are changes to existing (installed) services which do not result in either a change in the minimum period requirements or a change in the physical location of the point of termination at a customer premises. Changes which result in the establishment of new minimum period obligations are treated as disconnects and starts. Changes in the physical location of the point of termination are treated as moves and are described and charged for as set forth in <i>B103.3.2</i> .	(T)(O
			The charge to the customer for the service rearrangement is dependent on whether the change is administrative only in nature or involves actual physical change to the service.	(O
			Administrative changes will be made without charge(s) to the customer. Such changes require the continued provision and billing of the Private Line Service to the same entity (i.e., customer remains responsible for all outstanding indebtedness for the service). Administrative changes are as follows:	(O
			- Change of customer name (i.e., the customer of record does not change but rather the customer of record changes name),	(O
			- Change of customer or customer's premises address when the change of address is not a result of a physical relocation of equipment.	(O
			- Change in billing data (name, address or contact name or telephone number).	(O
			(2) All other service rearrangements will be charged for as follows:	(O
			- If the change involves the addition of other customer designated premises to an existing multipoint service, the nonrecurring charge for the local channel rate element will apply. The charges will apply only for the location(s) that is being added.	(O
			- If the change involves the addition of an optional feature or function which has a separate nonrecurring charge, that nonrecurring charge will apply.	(O
			- If the change involves changing the type of signaling on a voice grade service the subsequent, nonrecurring charge will apply for the new type signaling. The charge will apply per service termination affected.	(O
			 For all other changes, including a change of the customer of record involving no physical changes to the service provided or the addition of optional features without separate nonrecurring charges, a charge equal to a local channel rate element nonrecurring charge will apply. Only one such charge will apply per service, per change. 	(O

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

(M)

B102	2 D	ate Terms and Conditions	(141)			
			(T)(O)			
		Moves	(T)(O)			
Α.		nove involves a change in the physical location of one of the following:	(O)			
	1.	The point of interface at the customer premises.	(0)			
В.	2. The	The customer's premises. charges for the move are dependent on whether the move is to a new location within the same building or to a different	(O) (O)			
ъ.		ding.	(0)			
	1.	Moves Within the Same Building	(O)			
		When the move is to a new location within the same building, the charge for the move will be an amount equal to one-half the nonrecurring (i.e., installation) charge for the affected service termination at the customer's premises. There will be no change in the minimum period requirements. If a move is made at the same time a service rearrangement is made, the total charge will never exceed a full nonrecurring charge for the basic service.	(O)			
	2.	To a Different Building	(O)			
		Moves to a different building will be treated as a discontinuance and start of service and all associated nonrecurring charges will apply. New minimum period requirements will be established at the new location. The customer will also remain responsible for satisfying all outstanding minimum period charges for the discontinued service.	(O)			
B103	.3.3 I	Mileage Measurements	(T)(O)			
Α.	When station locations of a private line service are located in different wire center serving areas, interoffice channel charges apply. Charges are based on the direct airline distance measured between the serving wire centers. Mileage is determined in accordance with the following:					
	 Obtain the "V" and "H" coordinates for each wire center, as listed in the National Exchange Carrier Association F.C.C. No. 4. 		(O)			
	2. Obtain the difference between the "V" coordinates of the two wire centers. Obtain the difference between the "F coordinates. (The difference is always obtained by subtracting the smaller coordinate from the larger coordinate.)					
	3.	Square each difference obtained in 2. preceding.	(O)			
	4.	Add the squares of the "V" difference and the "H" difference obtained in 3. preceding.	(O)			
	5.	Divide the sum of the squares obtained in 4. preceding by 10.	(O)			
	6.	Obtain the square root of the result obtained in 5. This is the rate distance in miles. (Fractional miles being considered as full miles.)	(O)			
		EXAMPLE: The rate distance is required between City One and City Two.	(O)			
		V H				
		City One 7260 2083	(O)			
		City Two 7364 1865	(O) (O)			
		Difference 104 218 Squared $10,816 + 47,524 = 58,340$	(O)			
		10,010 1 17,321 - 30,510	(-)			
		58,340 divided by $10 = 5834$	(O)			
		Square root of $5834 = 76.38 = 77$ Airline miles	(O)			
В.	а се	en a private line is furnished over facilities which the Company elects to provide on a direct basis and is not routed through entral office, one two-point channel charge from B103.5 will apply. The arrangement is limited to channels not more than airline mile in length.	(T)(O)			
C.	airli	the purpose of applying multipoint charges, the bridging or hubbing locations are determined by that combination of ne distances connecting the serving wire center which will produce the lowest interoffice mileage charges. Bridging rges apply when three or more channels connect at the same location.	(O)			
D.	con	Series 1000, 2000 and 6000 channels the customer may specify the sequence in which the service points are to be nected in which case the rate mileage is the shortest airline mileage determined in accordance with C., which will connect wire centers of the service points in the specified sequence.	(O)			

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

(M)

B103.3 Rate Terms and Conditions (Cont'd)

(T)

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

(M)

B103.3 Rate Terms and Conditions (Cont'd)

(T)

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

			(M1)
B103.4 Rates and Charges			(N)
B103.4.1 Sub Voice Grade Service - Series 1000			(T)(M)
A. Intraexchange - Type 1150 and 1151			(T)(M)
(Obsoleted Type A)			(M)
1. Half Duplex			(T)(M)
	Monthly Rate	USOC	
(a) Local Channel, each	442.02		(T)(M)
(1) Type 1150 (2) Type 1151	\$43.82 52.61	25W++ 25W++	(T)(M) (T)(M)
(b) Interoffice Channel including the Channel terminals for use with the local channels listed in B103.4.1.A.1.(a) per channel	5 2. 01	25	(T)(M)
(1) 1st 1/4 mile	33.42	1L3A+	(T)(M)
(2) Each additional 1/4 mile or fraction thereof	1.09	1L6B+	(T)(M)
(c) Each additional point of termination of a local channel in a different building on the same premises			(T)(M)
(I) Type 1150 and 1151 - 1st mile	3.95	1L3A+	(T)(M)
(2) Type 1150 and 1151 for each 1/4 mile or fraction thereof	3.95	1L6B+	(T)(M)
(d) Two-point service, different building, same premises			(T)(M)
(1) Type 1150 - 1/4 mile or fraction thereof route measurement	3.95 3.95	1L3A+ 1L6B+	(T)(M) (T)(M)
(2) Type 1151 - For each 1/4 mile or fraction thereof(e) Two-point service, same building	3.73	1L0D+	(T)(M)
(I) Type 1151	3.95	1L6BB	(Tt)(M)
(f) Each additional point of termination in same building for two-point service in B103.4.1.A.1.(d) and (e)			(T)(M)
(1) Type 1150	1.97	1L3AA	(T)(M)
2. Full Duplex			(T)(M)
(a) Local Channel, each	43.82	257	(T)(M)
(1) Type 1150(b) Interoffice Channel including the Channel terminals for use with	43.02	25Z++	(T)(M) (T)(M)
the local channels listed in B103.4.1.A.2.(a) per channel.			. , , ,
(I) 1st 1/4 mile	33.42	1L3C+	(T)(M)
(2) Each additional 1/4 mile or fraction thereof	1.09	1L6D+	(T)(M)
(c) Each additional point of termination of a local channel in a different building on the same premises			(T)(M)
(1) Type 1150 and 1151, 1st mile	7.89	1L3C+	(T)(M)
(2) Type 1150 and 1151, for each 1/4 mile or fraction thereof	7.89	1L6D+	(T)(M)
(d) Two-point service, different building, same premises			(T)(M)
 (1) Type 1150 - For each 1/4 mile or fraction thereof (2) Type 1151 - For each 1/4 mile or fraction thereof 	7.89 7.89	1L3C+ 1L6D+	(T)(M) (T)(M)
(2) Type 1151 - For each 1/4 mile or fraction thereof(e) Two-point service, same building	1.07	ШОДТ	(T)(M)
(1) Type 1151	7.89	1L6DB	(T)(M)

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

								(M1)
B103.4	1 Rates	s ar	nd C	harges (Cont'd)				(T)(M)
				de Service - Series 1000 (Cont'd)				(T)(M)
				1204 and 1205 (Same Continuous Property Different ar	nd Same Building Channel	(s)		(T)(M)
			-31		Installation Charge ¹	Monthly Rate	USOC	
	1.	Eac	h addit	tional point of termination of a local channel (Obsoleted		Kate	CBGC	(T)(M)
		(a)	In th	e same building				(T)(M)
			(1)	Type 1204	\$-	\$1.54	267++	(T)(M)
	2.	Two	(2) point	Type 1205 service different buildings	-	1.54	267++	(T)(M) (T)(M)
				d 01-01-87, Type D; customers may add channels only t s of the date of this obsolescence)	to the extent that they are a	available within fa	acilities	(M)
		(a)	Samo	e premises				(T)(M)
			(1)	First mile ¹	17.83	7.89	1L3++	(T)(M)
	2	Т	(2)	Each additional 1/4 mile or fraction thereof	-	1.97	1L3++	(T)(M)
	3.		-	service	o the extent that they are	wailahla within fe	ailitias	(T)(M) (M)
				d 01-01-87, Type D; customers may add channels only to of the date of this obsolescence)	o the extent that they are a	avanable within ia	aciities	(1V1)
		(a)	Samo	e building				(T)(M)
			(1)	First mile ¹	17.83	7.89	1L3++	(T)(M)
		г.	(2)	Each additional 1/4 mile or fraction thereof	-	1.97	1L3++	(T)(M)
	4.			tional point of termination (Obsoleted 01-01-87, Type B)			(T)(M)
		(a)		e same building for two point service 103.4.1.B.2. or 3.				(T)(M)
			(1)	Type 1204	-	1.54	1L3++	(T)(M)
C	T4		(2) T	Type 1205	-	1.54	1L3++	(T)(M) (T)(M)
С.		-		1050 and 1051 (Obsoleted Type A)				(T)(M)
	1.		f Duple		*a1			
		(a)		office Channel including the Channel terminal for use with interexchange channels listed in <i>B103.4.1.C</i> per channel.				(T)(M)
			(1)	1st 1/4 mile		6.16	1L3A+	(T)(M)
		(h)	(2)	Each additional 1/4 mile or fraction thereof additional point of termination of a local channel,		2.28	1L6A+	(T)(M) (T)(M)
		(b)		rent building on the same premises, per 1/4 mile or fract	tion thereof			(1)(W1)
			(1)	Type 1050		3.57	NA	(T)(M)
т.	T . 1		<i>(2)</i>	Type 1051	01.07 = D)	3.57	NA	(T)(M)
D.		_		1205 (Additional Points of Termination) (Obsoleted 01- l point of termination	-01-87, Type B)			(T)(M)
	1.			•				(T)(M)
		(<i>a</i>)		e same building		1.40	2671J	(T)(M)
			(1)	Each		1.40	∠ 0/1J	(T)(M)

The Installation Charge is per channel.

(M)

Note 1:

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

					(M1)
103.4 Rate	s and Charges (Cont'd)				(T)(M
B103.4.2 Void	ce Grade Service – Series 2000				(T)(M
A. Intraexch	nange - Same Continuous Property Different and Same Building Ch	annels			(T)(N
1.	Each additional point of termination of a local channel in a different building on the same premises				(T)(N
	(Obsoleted 01-01-87, Type B)				(N
	(a) Per 1/4 mile or fraction thereof				(T)(N
	(1) Half Duplex (2) Duplex	Installation Charge \$- -	Monthly Rate \$3.95 4.92	USOC 1LM+G 1L6+G	(T)(N (T)(N
2	A Minimum Charge of 2/4 miles applies				(N
2.	Each additional point of termination of a local channel				(T)(N
	(Obsoleted 01-01-87, Type B)				(I) (T)(I)
	(a) In the same building		1.97	MUX++	
3.	(1) Full Duplex Two-point service	•	1,97	WICATT	(T)(I (T)(I
	(Obsoleted 01-01-87, Type D)				(N
	(a) Same building				(T)(I
	(1) Half Duplex(2) Duplex	48.19 48.19	3.18 3.95	1LM+B 1L6+B	(T)(N (T)(N
	nange - Additional Point of Termination				(T)(I
•	Obsoleted 01-01-87, Type B)				(1
1.	Each additional point of termination of a local channel in a different building on the same premises				(T)(N
	(a) Per 1/4 mile or fraction thereof				(T)(N
2.	(1) Half Duplex Each additional point of termination of a local channel		4.26	1LPJG	(T)(N (T)(N
	(a) In the same building				(T)(N
<i>B103.4.3</i> Seri	(1) Full Duplex ses 7000 Channels		5.37	MUX++	(T)(N (T)(N
A. General					(N
1. Sp	pecial Terms and Conditions Regarding Provision of Service				(N
a.	New systems will be provided in accordance with B5.1.H of the	Private Line Guideboo	k. until the develop	nent of a	(T)(N

new offering, at which time said systems will be converted to the new offering.

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS B103.4 Rates and Charges (Cont'd)

B103.4.4 Local Channels

					ecurring	
			Monthly		narge	
			Rate	First	Additional	USOC
A.	Sub Voice Grade					
	 Per point of te 	rmination				
	(a)	Type 1204	\$2,481.00(I)	\$498.00	\$210.00	P1JAX
	(b)	Type 1205	2,262.00(I)	378.00	150.00	P1JHX
В.	Voice Grade					
	Per point of termina	ation				
	1. Voice					
	(a)	Type 2230	6,829.00(I)	354.00	138.00	P2JUX
	(b)	Type 2231	6,829.00(I)	360.00	138.00	P2JHX
	(c)	Type 2432	10,255.00(I)	414.00	174.00	P2JQX
	(d)	Type 2434	2,122.00(I)	168.00	93.60	P2JGX
	(e)	Type 2435	10,255.00(I)	378.00	156.00	P2JWX
	(f)	Type 2261	7,943.00(I)	588.00	276.00	P2JLX
	(g)	Type 2462	9,458.00(I)	582.00	270.00	P2JRX
	2. Data					
	(a)	Type 2463	10,832.00(I)	432.00	192.00	P2JMX
	(b)	Type 2464	10,832.00(I)	432.00	192.00	P2JNX
C.	Wired Music					
	1. Per point of te	ermination				
	(a)	Type 6211	4,116.00(I)	552.00	246.00	P6JAX
	(b)	Type 6212	5,139.00(I)	642.00	324.00	P6JBX
	(c)	Type 6213	5,775.00(I)	654.00	342.00	P6JCX
	(d)	Type 6215	4,025.00(I)	552.00	246.00	P6JEX
	(e)	Type 6216	5,139.00(I)	642.00	324.00	P6JNX
	(f)	Type 6217	5,775.00(I)	654.00	342.00	P6JGX

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS B103.4 Rates and Charges (Cont'd)

B103.4.5 Interoffice Channels¹

			Fixed Monthly Charge	Monthly Charge Per Mile	Nonrecurring Charge Per Channel	USOC
A.	Fixe	ed and Mileage Charges applicable	5			
	1.	Sub Voice Grade - Series 1000 ²				
		(a) 1 thru 8 Miles	\$3,110.00(I)	\$278.00(I)	-	3LBAS
		(b) 9 thru 25 Miles	3,110.00(I)	278.00(I)	-	3LBAS
		(c) Over 25 Miles	3,110.00(I)	278.00(I)	-	3LBAS
	2.	Voice Grade Service - Series 2000				
		(a) 1 thru 8 Miles	9,863.00(I)	739.00(I)	\$115.20	3LBBS
		(b) 9 thru 25 Miles	9,863.00(I)	739.00(I)	115.20	3LBBS
		(c) Over 25 Miles	9,863.00(I)	739.00(I)	115.20	3LBBS
	3.	Wired Music - Series 6000 3.0 kHz Types 6211 and 6215				
		(a) 1 thru 8 Miles	5,697.00(I)	195.00(I)	92.40	3LBCS
		(b) 9 thru 25 Miles	5,697.00(I)	195.00(I)	92.40	3LBCS
		(c) Over 25 Miles	5,697.00(I)	195.00(I)	92.40	3LBCS
	4.	Wired Music - Series 6000 5 kHz				
		Types 6212 and 6216				
		(a) 1 thru 8 Miles	5,904.00(I)	383.00(I)	81.60	3LBDS
		(b) 9 thru 25 Miles	5,904.00(I)	383.00(I)	81.60	3LBDS
		(c) Over 25 Miles	5,904.00(I)	383.00(I)	81.60	3LBDS
	5.	Wired Music - Series 6000 8 kHz Types 6213 and 6217				
		(a) 1 thru 8 Miles	7,954.00(I)	646.00(I)	81.60	3LBES
		(b) 9 thru 25 Miles	7,954.00(I)	646.00(I)	81.60	3LBES
		(c) Over 25 Miles	7,954.00(I)	646.00(I)	81.60	3LBES

Note 1: For method of determining mileage, see B103.3.3.A.

Note 2: Metallic interoffice channels are no longer available for new installations, moves or transfers. Metallic interoffice facilities are in continually decreasing supply due to modernization programs that replace existing metallic interoffice with non-metallic facilities such as fiber optics.

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.4 Rates and Charges (Cont'd)

B103.4.6 Optional Features And Functions

A. Bridging

Bridging charges are applicable where more than two Local Channels, or one or more Local Channels and more than one Interoffice Channel, or more than one Local Channel and one Interoffice Channel are bridged or hubbed at the same wire center. No additional bridging charges are applicable for Series 1000, Types 1204 and 1205.

1. Voice Grade Bridges (Series 2000)

				Monthly	Nonrecurring	
				Rate	Charge	USOC
a.	Voi	ce Bri	dging			
	(1)	Per I	Port			
		(a)	Two-Wire (Type 2230)	\$2,598.00(I)	\$38.40	BQ9
		(b)	Four-Wire (Type 2435)	3,395.00(I)	38.40	BQ9
b.	Dat	a Bridg	ging			
	(1)	Per I	Port			
		(a)	Four-Wire (Types 2463 and 2464)	4,903.00(I)	40.80	BQ9
c.	Tele	emetry	and Alarm Bridging - Split Band, Active Bridging			
	(1)	Com	mon Equipment, per central office			
		(a)	First bridging shelf, capacity of 48 two-wire	9,798.00(I)	385.00	XW1
		. ,	connections			
		(b)	Additional bridging shelf, capacity of 56 two-wire	9,798.00(I)	350.00	XW2
			connections installed subsequent to the first bridging			
			shelf	4.050.00(T)	215.00	*/**/0
		(c)	Additional bridging shelf, capacity of 56 two-wire connections installed at the same time as the first	4,958.00(I)	215.00	XW8
			bridging shelf			
	(2)	Chai	nnel connections, per channel connected			
	(-)	(a)	Remote station channel connection	383.00(I)	33.00	XW3
		(a) (b)	Mid-link channel connection, first channel	972.00(I)	43.00	XW4
		(c)	Mid-link channel connection, subsequent channels	972.00(I)	43.00	XW5
Wi	red N	(-)	Bridges (Series 6000)	`,		
a.	Dist	tributio	on Amplifiers			
	(1)	Per I	Port			
	(-)	(a)	Each	2.40	32.40	6LE
		(u)	Lucii	2.10		V

B. Signaling Arrangements

2.

Signaling arrangements are provided at the customer's option to arrange channels for suitable signaling. Signaling is required on all off-premises extension channels and tie line channels associated with PBX (or similar) systems.

		Nonrecurring			
		Monthly	Charge		
		Rate	Initial	Subsequent	USOC
Per local chan	nel				
(a)	Ringdown-Manual	\$1,580.00(I)	\$40.80	\$216.00	SL3
(b)	Ringdown-Automatic	1,448.00(I)	18.00	68.40	SL5
(c)	E & M Type	1,448.00(I)	52.80	198.00	SLM
(d)	Type A (0-199 ohms)	854.00(I)	48.00	138.00	SAL
(e)	Type B (200-899 ohms)	854.00(I)	44.40	138.00	SAU
(f)	Type C (900 or more ohms)	383.00(I)	14.40	138.00	SAY
	(a) (b) (c) (d) (e)	 (b) Ringdown-Automatic (c) E & M Type (d) Type A (0-199 ohms) (e) Type B (200-899 ohms) 	Monthly Rate Rate Per local channel	Monthly Rate Initial Per local channel	Monthly Charge Rate Initial Subsequent

B3. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.4 Rates And Charges (Cont'd)

B103.4.6 Optional Features And Functions (Cont'd)

- C. Conditioning (Voice Grade Services)
 - 1. Conditioning provides more specific transmission characteristics for data services. There are two types of C-conditioning and one type of D-conditioning, each with different technical specifications. C-Type conditioning controls attenuation distortion and envelope delay distortion. D-Type conditioning controls the signal to C-notched noise ratio and intermodulation distortion.

Conditioning is charged for on a per Local Channel basis for two-point and multipoint service. For two-point services the parameters apply to each service. For multipoint services the parameters apply to any path between any two service points.

2. The types and description of the available conditioning options are as follows:

Type Conditioning	Frequency Response Specification	Envelope Delay Specification	Distortion
C1 (two-point or multipoint)	300-2700 Hz,	1000-2400 Hz, le	ss
	-2dB to $+6dB$.	than 1000 micros	econds
	1000-2400 Hz,		
	-1dB to $+3$ dB.		
	300-3000 Hz,		
	-3dB to $+12dB$.		
C2 (two-point or multipoint)	300-3000 Hz,	1000-2600 Hz, le	SS
	-2dB to $+6dB$.	than 500 microse	econds
	500-2800 Hz,	600-2600 Hz, less	S
	-1dB to $+3$ dB.	than 1500 micros	econds
		500-2800 Hz, less	S
		than 3000 micros	econds
		Non-Linear l	Distortion
	C-Notched Noise	2nd Order	3rd Order
		Distortion	Distortion
D1 (two-point)	Noise level 28dB	35dB below	40dB below
	below signal level	signal level	signal level

3. When a channel is equipped with Type D1 conditioning and is utilized for voice communications, the Company does not undertake to represent that the channel will be suitable for such voice transmission.

			Nonrecurring		
		Monthly	Cha	ırge	
		Rate	Initial	Subsequent	USOC
4.	C-Type Conditioning				
	a. C-Type Conditioning is available for Types 2463 and 24	164			
	(1) C-Types of Conditioning per local channel				
	(a) C1-Type	\$383.00(I)	\$12.00	\$78.00	P2W
	(b) C2-Type	383.00(I)	26.40	88.80	P3W
5.	D-Type Conditioning				
	a. D-Type Conditioning is available for Types 2463 and 24	464			
	(1) D-Type Conditioning per local channel				
	(a) D1-Type	383.00(I)	19.20	82.80	QHA

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.5 Non-Wire Center Connected Channels

(Obsoleted 9/15/03, Type B; Not available for new installations, additions or transfers of service to new location)

- A. Served Direct
 - 1. Not routed via the central office, limited to one airline mile or less

			Non	recurring	
		Monthly	(Charge	
		Rate	First	Additional	USOC
(a)	Series 1000	\$12.00	\$498.00	\$210.00	SDD1X
(b)	Series 2000	15.00	498.00	210.00	SDD2X

Note 1: For method of determining mileage, see *B103.3.3.A*.

(T)

(T)

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.6 Series 10000 Channels (Entrance Facilities)

(Obsoleted 11/15/89, Type D; not available for new installations, moves or transfers. Existing customers may add channels only to the extent that they are available.)

B103.6.1 Types And Description

- **A.** Series 10000 channels are furnished to the customer by the Company for the purpose of extending customer-provided communications systems to a premises of the customer or authorized user, or to Centrex Type Services Switching Equipment serving the premises of the customer or authorized user for use at such premises. Channels are furnished for half-duplex or duplex operation on a two-point basis for service 7 days per week, 24 hours per day, for a minimum period of one month.
 - Type 10001 Approximate bandwidth of 300 3000 cycles per second. Furnished, to the extent permitted by the normal transmission characteristics of this grade of channel, for types of transmission similar to those set forth for Series 1000 and 2000 channels.

B103.6.2 Terms and Conditions

- **A.** In addition to the terms and conditions set forth in Section B2., the following terms and conditions apply to Series 10000 channels as specified following:
 - 1. Type 10001 The customer's or authorized user's premises must be located 25 airline miles or less from the point at which the customer-provided communication channel is connected to the Company entrance facility.

B103.6.3 Rates - Monthly Service

- A. Type 10001
 - 1. (Rates for entrance facilities will be based on the costs incurred on a case-by-case basis.)

B103.7 (DELETED)

(M)

B103	.8 Local Area Data C	hannels					(T)(M1)
(O	bsoleted 4-8-91, Type B)						(M)
In cor cha fac	consideration of the decreasing nvert a customer's service requir arges associated with the changilities, or a customer may elect ailability of metallic facilities.	ing such facilities to a ge. This applies to cu	Voice Grade Service or Syn stomers where metallic fac	nchroNet ⁴ service ar ilities are being re	nd waive the nonreplaced with non-	ecurring metallic	(C)(M)
	cal Area Data Channels are intentween two different premises with					nises or	(M)
a.	Provision of these channels is this service.	subject to the availabili	ty of facilities and does not e	nvision construction	n of facilities expre	essly for	(M)
b.	Transmission specifications for the service as follows:	or local area data channo	els are dependent upon the re	oute length of the fa	acilities utilized to	provide	(M)
	Maximum End-To-End Fac In Route Mile	ility Length	Maximum Insertion Loss At 1000 Hz, In dB ¹				(M)
	1		9.0				(M)
	2		13.5				(M)
	3		17.0				(M)
	4		20.0				(M)
	5		23.0 25.5				(M) (M)
c.	Type 1180 is provided as a 2-v	vire interface with effec					(M)
d.	Type 1182 is provided as a 4-v						(M)
е.	Rates - Intraexchange	who interface with effec	dive i wife identifies.				
C.	(1) Local Channel, Each						(M) (M)
	(1) Boom Chamier, Buch			Installation	Monthly		(2.2)
				Charge	Rate	USOC	
	(a) Type 1180			\$44.40	\$23.01	1L6GJ	(M)
	(b) Type 1182			44.40	46.04	1L6GJ	(M)
	(2) Two point service different non-wire center connected		emises,				(T)(M)
	(a) First mile ³			17.83	7.89	1L6G+	(T)(M)
	· /	mile or fraction thereo		-	1.54	1L6++	(M)
f.	Rates - Type 1180 and 1182 (S	-		-			(M)
	(Obsoleted 01-01-87, Type D only to the extent that they are		installations, moves or trai	nsfers. Existing cus	tomers may add c	hannels	(M)
	(1) Two point service, differen	ent buildings same prem	nises				(M)
	(a) First mile ³			17.83	7.89	1L6GQ	(T)(M)
	(b) Each additional 1/4	mile or fraction thereo	f	-	1.97	1L6GB	(M)
	(2) Two point service same b	uilding					(M)
	(a) Charge			17.83	1.54	1L6GB	(M)
B103	3.9 Reserved For Fut	ture Use					(M1)
	Note 1:	Insertion loss is refer	enced to 135 ohm resistive to	erminations at each	end.		(M)
	Note 2:	Offered only where f	acilities permit.				(M)
	Note 3:	The Installation Char	-				(M)
	Note 4:		21, SynchroNet Service is of	osoleted See R107	2 for service avail	ability	(N)
	11016 4.	Effective June 30, 20	21, Syncinorica Service is of	booleted. See B107.	.2 101 Set vice avail	aciity.	(11)

AL-14-0086 EFFECTIVE: December 18, 2014

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.10 Description Of Service And Rates - Customer Operating Center Service (COCS)

(Obsoleted 11/15/89, Type D; customers may continue to activate channels within their existing size of service cable).

(M)

(T)

B103.10.1 General

- A. Customer Operating Center Service (COCS) is designed for use by customers who utilize large quantities of local channels of the types specified in B103.10.1.K.2. following between their location and the serving wire center.
- Customer Operating Center Service is provided to customers at their option. The rates for COCS service are billed directly by the Company to the customer of COCS service.
- For the purposes of this *Guidebook*, a Customer Operating Center is defined as a customer location:
 - owned or leased by the customer over which the customer has control and provides security.
 - from which the customer furnishes and administers services to multiple clients in a geographical area. The term "Client" denotes a subscriber to the services offered by the owner or leasee of a Customer Operating Center.
 - 3. at which a system, or a group of systems, owned or leased by the customer whose operation is to receive signals and messages which are recorded, maintained, and supervised by the customer.
 - at which the customer has regularly scheduled observers and operators and/or equipment in attendance at all times whose duties include, upon receipt of a signal or message from a client, to take such action as shall be required under the rules established by the customer for their guidance.
- COCS service is provided by using a complement of cable pairs in the size and length specified in B103.10.1.K.1. following.
- A monthly rate applies for each complement of cable pairs of a specific size and length.
- The customer will provide in advance a forecast of the complement of cable pairs he wishes to have planned to his use and agrees to payment of the charges for the complement of cable pairs whose airline distance is greater than 1/4 mile whether circuits are activated or not.
- The monthly rate for each complement of cable pairs is based on the airline distance between the customer's operating center and its normal serving wire center. The maximum distance for COCS service is one and a quarter mile.
- H. In addition to the monthly rate for the complement of cable pairs, a monthly rate applies for each local channel activated within the complement of cable pairs.
- **Basic Termination Liability**

A basic termination liability will apply for any facility placed new specifically for a customer for which no reuse is foreseen if the initial use is discontinued.

The termination liability period is 5 years.

The amount of the termination liability is equal to the estimated amount for:

- Cost of the installed facilities provided including costs incurred for rearrangements of existing facilities and/or construction of new facilities as appropriate, less net salvage. Installed cost includes the cost of:
 - a. equipment and materials provided or used,
 - b. engineering, labor and supervision,
 - c. transportation,
 - d. rights of way.

AL-12-0080 EFFECTIVE: October 26, 2012

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.10 Description Of Service And Rates - Customer Operating Center Service (COCS) (Cont'd)

B103.10.1 General (Cont'd)

- I. Basic Termination Liability (Cont'd)
 - 2. Any other costs associated with the particular situation.
 - 3. The maximum termination liability defined preceding is reduced by 1/60th for each month of a 5 year period that the complement of cable pairs is in service from the date it is placed in service for a specific customer.
- J. A service charge applies for a connection move or change of each local channel activated within the complement of cable pairs. The service charges are as specified in B103.10.1.L.1.e. following.
- K. Monthly Rates
 - 1. Per complement of cable pairs
 - a. Distance in 1/4 Mile or Fraction Thereof
 - (1) Service Cable Size 50 Pairs

			Monthly		
			Rate ¹	USOC	
	(a)	1/4 mile	\$-	1LZ5A	
	(b)	(DELETED)			(D)
	(c)	(DELETED)			(D)
	(d)	(DELETED)			(D)
	(e)	(DELETED)			(D)
(2)		ice Cable Size - 100 Pairs			(-)
(2)					
	(a)	1/4 mile	-	1LZ1A	
	(b)	(DELETED)			(D)
	(c)	(DELETED)			(D)
	(d)	(DELETED)			(D)
	(e)	(DELETED)			(D)
(3)	Serv	ice Cable Size - 200 Pairs			
	(a)	1/4 mile	-	1LZ2A	
	(b)	(DELETED)			(D)
	(c)	(DELETED)			(D)
	(d)	(DELETED)			(D)
	(e)	(DELETED)			(D)
(4)		ice Cable Size - 300 Pairs			` '
	(a)	1/4 mile	-	1LZ3A	
	(b)	(DELETED)			(D)
	(c)	(DELETED)			(D)
	(d)	(DELETED)			(D)
	(e)	(DELETED)			(D)
	(0)	(DEDETED)			(2)

Note 1: Rates are effective with normal billing cycles beginning on or after March 22, 2003.

AL-18-0063 EFFECTIVE: November 1, 2018

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.10 Description Of Service And Rates - Customer Operating Center Service (COCS) (Cont'd)

B103.10.1 General (Cont'd)

- **K.** Monthly Rates (Cont'd)
 - 1. Per complement of cable pairs (Cont'd)
 - a. Distance in 1/4 Mile or Fraction Thereof (Cont'd)
 - (5) Service Cable Size 400 Pairs

	(a) 1/4 mile (b) 1/2 mile (6) Service Cable Size - 600 Pairs	Monthly Rate \$- 591.65	USOC 1LZ4A 1LZ4B	(T)
	(a) 1/4 mile (7) (DELETED)	-	1LZ6A	(D)
2.	 (8) Service Cable Size - 1200 Pairs (a) 1/4 mile Per Local Channel Activated a. Local Channel Provided Within A Cable Whose Airline Distance Is 1/4, 1/2, 3/4, 4/4 Or 5/4 Mile 	-	1LZCA	
	(1) Type Of Local Channel Activated - 1204 (a) 1/4 mile (b) 1/2 mile (c) 3/4 mile (d) 4/4 mile	\$6.67 6.67 6.67 6.67	1LZ++ 1LZ++ 1LZ++ 1LZ++	

AL-14-0086 EFFECTIVE: December 18, 2014

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.10 Description Of Service And Rates - Customer Operating Center Service (COCS) (Cont'd)

B103.10.1 General (Cont'd)

- **K.** Monthly Rates (Cont'd)
 - 2. Per Local Channel Activated (Cont'd)
 - a. (Cont'd)
 - (1) Type Of Local Channel Activated 1204 (Cont'd)

		Monthly	
		Rate	USOC
	(e) 5/4 mile	\$6.67	1LZ++
(2)	Type Of Local Channel Activated - 1205		
	(a) 1/4 mile	6.67	1LZ++
	(b) 1/2 mile	6.67	1LZ++
	(c) 3/4 mile	6.67	1LZ++
	(d) 4/4 mile	6.67	1LZ++
	(e) 5/4 mile	6.67	1LZ++
(3)	Type Of Local Channel Activated - 2230		
	(a) 1/4 mile	12.02	1LZ++
	(b) 1/2 mile	12.02	1LZ++
	(c) 3/4 mile	12.02	1LZ++
	(d) 4/4 mile	12.02	1LZ++
	(e) 5/4 mile	12.02	1LZ++
(4)	Types of Local Channel Activated - 2106 ¹		
(5)	Type of Local Channel Activated - 2107 ¹		
(6)	Type Of Local Channel Activated - 2463 ²		
	(a) 1/4 mile	22.46	1LZ++
	(b) 1/2 mile	24.11	1LZ++
	(c) 3/4 mile	25.20	1LZ++
	(d) 4/4 mile	29.58	1LZ++
	(e) 5/4 mile	32.31	1LZ++
(7)	Type Of Local Channel Activated - 2464 ²		
	(a) 1/4 mile	47.12	1LZ++
	(b) 1/2 mile	48.76	1LZ++
	(c) 3/4 mile	50.39	1LZ++

Note 1: See General *Exchange Guidebook*, Section A108. for Rates.

Note 2: These local channels are provided with a four-wire facility (2 pairs). The total number of all types of local channels that may be activated within a complement of cable pairs is limited by the number of these types of local channels.

(T)

(C)

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.10 Description Of Service And Rates - Customer Operating Center Service (COCS) (Cont'd)

B103.10.1 General (Cont'd)

- **K.** Monthly Rates (Cont'd)
 - 2. Per Local Channel Activated (Cont'd)
 - a. (Cont'd)
 - (7) Type Of Local Channel Activated 2464¹ (Cont'd)

			Monthly		
			Rate ²	USOC	(T)
	(d)	4/4 mile	\$51.49	1LZ++	(T)(I)
	(e)	5/4 mile	52.60	1LZ++	(T)(I)
(8)	Туре	Of Local Channel Activated - 2230			
	(a)	1/4 mile	6.47	1LZ++	(T)(I)
	(b)	1/2 mile	6.47	1LZ++	(T)(I)
	(c)	3/4 mile	6.47	1LZ++	(T)(I)
	(d)	4/4 mile	11.16	1LZ++	(T)(I)
	(e)	5/4 mile	14.92	1LZ++	(T)(I)
(9)	Туре	Of Local Channel Activated - 2261			
	(a)	1/4 mile	6.47	1LZ++	(T)(I)
	(b)	1/2 mile	6.47	1LZ++	(T)(I)
	(c)	3/4 mile	6.47	1LZ++	(T)(I)
	(d)	4/4 mile	11.16	1LZ++	(T)(I)
	(e)	5/4 mile	14.92	1LZ++	(T)(I)
(10) Type Of Local Channel Activated – 2462 ¹					
	(a)	1/4 mile	22.46	1LZ++	(T)(I)
	(b)	1/2 mile	24.11	1LZ++	(T)(I)
	(c)	3/4 mile	25.20	1LZ++	(T)(I)
	(d)	4/4 mile	29.58	1LZ++	(T)(I)
	(e)	5/4 mile	32.31	1LZ++	(T)(I)

- L. Nonrecurring Charges
 - 1. Service Charge Per Local Channel Activated

The service charge for the connection or change of each local channel activated within a complement of cable pairs is as follows:

- a. The term Service Charge as specified herein is defined as the nonrecurring charge or charges applying to the ordering, installing, rearranging and furnishing of local channels. Service charges are categorized as
 - **Note 1:** These local channels are provided with a four-wire facility (2 pairs). The total number of all types of local channels that may be activated within a complement of cable pairs is limited by the number of these types of local channels.
 - Note 2: Rates are effective with normal billing cycles beginning on or after March 22, 2003.

C1. 1

TICOC

(N)

B103. OBSOLETE SERVICE OFFERINGS - CHANNELS

B103.10 Description Of Service And Rates - Customer Operating Center Service (COCS) (Cont'd)

B103.10.1 General (Cont'd)

- L. Nonrecurring Charges (Cont'd)
 - 1. Service Charge Per Local Channel Activated (Cont'd)
 - a. (Cont'd)
 - (1) Service Ordering Charge
 - (2) Visit Charge
 - (3) Channel Connecting Charge
 - b. Service Ordering Charge
 - (1) The Service Ordering Charge applies per customer request for work performed by the Company in connection with the receiving, recording and processing the customer's request for local channels to be installed at the same time.
 - (2) The term "per customer request" as specified preceding means all work or service ordered by the customer to be performed or provided at the same time. Only one service ordering charge applies when more than one local channel or types of local channels is ordered at the same time. When two or more types of local channels are ordered on the same customer request the higher charge applies.
 - c. Visit Charge

A Visit Charge applies for connecting or changing Types 2463, 2464, 2230, 2261 and 2462 local channels only. Only one Visit Charge applies when more than one Type Local Channel is ordered to be provided at the same time.

d. Channel Connecting Charge

The Channel Connecting Charge covers work associated with activating a local channel in a complement of cable pairs. The charge applies for each channel activated.

- e. Schedule of Charges
 - (1) Service Ordering Charge, per customer request

			Charge ²	USOC	(1)
	(a)	Type 1204 and 1205	\$49.00	NA	(I)
	(b)	Type 2463, 2464 and 2462	262.20	NA	(I)
	(c)	Type 2230 and 2261	165.60	NA	(I)
	(d)	Type 2230 (Interexchange)	289.80	NA	(I)
(2)) Visit Charge				
	(a)	Type 2230, 2463 and 2464	18.97	NA	(I)
(3)	Char	nnel Connecting Charge			
	(a)	Type 2463 and 2464	136.62	NA	(I)
	(b)	Type 2230	84.18	NA	(I)
	(c)	Type 1204, 1205	21.73	NA	(I)
	(d)	Type 2230 (Interexchange)	317.40	NA	(I)

Note 1: Rates are effective with normal billing cycles beginning on or after March 22, 2003.