

TARIFF DISTRIBUTION

FILE PACKAGE NO.: FL-14-0072

DATE: September 1, 2014

STATE: FLORIDA

EFFECTIVE DATE: 09/01/2014

TYPE OF DISTRIBUTION: Approved

PURPOSE: Increase Private Line Channels (APL) monthly charges

<u>TARIFF SECTION</u>	<u>PAGE NUMBER</u>	<u>PAGE REVISION</u>
H003	14	0005
H003	15	0005
H003	16	0005
H003	17	0005

B3. CHANNELS

B3.4 Rates and Charges (Cont'd)

B3.4.3 Interoffice Channels^{1,2}

A. Fixed and Mileage Charges applicable

1. Sub Voice Grade - Series 1000 (Obsoleted, See B103.)
2. Voice Grade Service - Series 2000

	Fixed Monthly Charge	Monthly Charge Per Mile	Nonrecurring Charge Per Channel	USOC	
(a) 1 thru 8 Miles	\$378.00	\$24.00	\$117.48	3LBBS	(1)
(b) 9 thru 25 Miles	378.00	24.00	117.48	3LBBS	(1)
(c) Over 25 Miles	378.00	24.00	117.48	3LBBS	(1)
3. (Obsoleted, See B103)					

Note 1: Nonrecurring charges are described in B3.3.1.A.

Note 2: For method of determining mileage, see B.3.3.3.A.

B3. CHANNELS

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions¹

A. Bridging

Bridging charges are applicable where more than two Local Channels, or one or more Local Channels and more than one Interoffice Channel, or more than one Local Channel and one Interoffice Channel are bridged or hubbed at the same wire center. No additional bridging charges are applicable for Series 1000, Types 1204 and 1205.

1. Voice Grade Bridges (Series 2000)

	Monthly Rate	Nonrecurring Charge	USOC	
a. Voice Bridging				
(1) Per Port				
(a) Two-Wire (Type 2230)	<i>\$ 94.00</i>	<i>\$ 40.92</i>	BQ9	(1)
(b) Four-Wire (Type 2435)	<i>94.00</i>	<i>40.92</i>	BQ9	(1)
b. Data Bridging				
(1) Per Port				
(a) Four-Wire (Types 2463 and 2464)	<i>134.00</i>	<i>44.88</i>	BQ9	(1)
c. (Obsoleted, See B103.)				
d. (Obsoleted, See B103.)				
e. Telemetry and Alarm Bridging - Split Band, Active Bridging				
(1) Common Equipment, per central office				
(a) First bridging shelf, capacity of 48 two-wire connections	<i>376.00</i>	<i>375.00</i>	XW1	(1)
(b) Additional bridging shelf, capacity of 56 two-wire connections installed subsequent to the first bridging shelf	<i>376.00</i>	<i>340.00</i>	XW2	(1)
(c) Additional bridging shelf, capacity of 56 two-wire connections installed at the same time as the first bridging shelf	<i>164.00</i>	<i>210.00</i>	XW8	(1)
(2) Channel connections, per channel connected				
(a) Remote station channel connection	<i>8.00</i>	<i>33.00</i>	XW3	(1)
(b) Mid-link channel connection, first channel	<i>39.00</i>	<i>46.00</i>	XW4	(1)
(c) Mid-link channel connection, subsequent channels	<i>34.00</i>	<i>46.00</i>	XW5	(1)

Note 1: Nonrecurring charges are described in B3.3.1.A.

B3. CHANNELS

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions¹ (Cont'd)

B. Signaling Arrangements

Signaling arrangements are provided at the customer's option to arrange channels for suitable signaling. Signaling is required on all off-premises extension channels and tie line channels associated with PBX (or similar) systems.

1. Per local channel

	Monthly Rate	Nonrecurring Charge		USOC
		Initial	Subsequent	
(a) Ringdown-Manual ²	\$62.00	\$55.44	\$277.20	SL3
(b) Ringdown-Automatic ²	58.00	21.12	91.08	SL5
(c) E & M Type ³	57.00	60.72	250.80	SLM
(d) Type A (0-199 ohms) ⁴	34.00	58.08	184.80	SAL
(e) Type B (200-899 ohms) ⁴	34.00	56.76	184.80	SAU
(f) Type C (900 or more ohms) ⁴	8.00	14.52	184.80	SAY

(1)

C. Conditioning (Voice Grade Services)

1. Conditioning provides more specific transmission characteristics for data services. There are two types of C-conditioning and one type of D-conditioning, each with different technical specifications. C-Type conditioning controls attenuation distortion and envelope delay distortion. D-Type conditioning controls the signal to C-notched noise ratio and inter-modulation distortion.

Conditioning is charged for on a per Local Channel basis for two-point and multi-point service. For two-point services the parameters apply to each service. For multipoint services the parameters apply to any path between any two service points.

2. The types and description of the available conditioning options are as follows:

Type Conditioning	Frequency Response Specifications	Envelope Delay Distortion Specification
C1 (two-point or multipoint)	300-2700 Hz, -2dB to +6dB. 1000-2400 Hz, -1dB to +3dB. 300-3000 Hz, -3dB to +12dB.	1000-2400 Hz, less than 1000 microseconds

Note 1: Nonrecurring charges are described in B3.3.1.A.

Note 2: For use with Type 2230 and 2435 services.

Note 3: For use with Type 2432 and 2434 services.

Note 4: For use with Type 2231 service.

B3. CHANNELS

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions¹ (Cont'd)

C. Conditioning (Voice Grade Services) (Cont'd)

2. The types and description of the available conditioning options are as follows: (Cont'd)

Type Conditioning	Frequency Response Specifications	Envelope Delay Distortion Specification
C2 (two-point or multipoint)	300-3000 Hz, -2dB to +6dB. 500-2800 Hz, -1dB to +3dB.	1000-2600 Hz, less than 500 microseconds 600-2600 Hz, less than 1500 microseconds 500-2800 Hz, less than 3000 microseconds
	C-Notched Noise	Non-Linear Distortion
D1 (two-point)	Noise level 28dB below signal level	2nd Order Distortion 3rd Order Distortion
		35dB below signal level 40dB below signal level

3. When a channel is equipped with Type D1 conditioning and is utilized for voice communications, the Company does not undertake to represent that the channel will be suitable for such voice transmission.

	Monthly Rate	Nonrecurring Charge		USOC	
		Initial	Subsequent		
4. C-Type Conditioning					
a. C-Type Conditioning is available for Types 2463 and 2464.					
(1) C-Types of Conditioning per local channel					
(a) C1-Type	\$8.00	\$13.20	\$113.52	P2W	(1)
(b) C2-Type	8.00	29.04	125.40	P3W	(1)
5. D-Type Conditioning					
a. D-Type Conditioning is available for Types 2463 and 2464.					
(1) D-Type Conditioning per local channel					
(a) D1-Type	2.00	21.12	118.80	QHA	(1)

Note 1: Nonrecurring charges are described in B3.3.1.A.