

**TARIFF DISTRIBUTION**

FILE PACKAGE NO.: FL-17-0078

DATE: December 6, 2017

STATE: FLORIDA

EFFECTIVE DATE: 12/02/2017

TYPE OF DISTRIBUTION: Approved

PURPOSE: Increase residence Privacy Manager Monthly Rate.

**TARIFF SECTION**

G013

**PAGE NUMBER**

71

**PAGE REVISION**

0008

**A13. MISCELLANEOUS SERVICE ARRANGEMENTS**

**A13.70 Privacy Manager Service (Cont'd)**

**A13.70.2 Terms, Conditions and Limitations of Service**

- A. The following terms, conditions and limitations apply:
  1. Privacy Manager service is provided subject to availability of facilities.
  2. Privacy Manager service is available to single and multi-line residence customers.
  3. Privacy Manager service is not compatible with Calling Number Delivery Blocking-Permanent, FX, FCO, ISDN or ADSL. Privacy Manager service may not be compatible with RingMaster service in all switch types.
  4. Caller ID and Touch-Tone service are required in order to subscribe to Privacy Manager service.

**A13.70.3 Rates and Charges**

- A. The following rates are for Privacy Manager service only and are in addition to the applicable service charges and monthly rates for exchange access lines and other services with which this service is associated.
  1. Residence

	<b>Monthly Rate</b>	<b>USOC</b>	
(a) Per line except Complete Choice plan lines	<b>\$10.99</b>	<b>PMX1R</b>	(1)
(b) Per Complete Choice plan line	<b>10.99</b>	<b>PMX1R</b>	(1)

**A13.71 Reserved for Future Use**

**A13.72 Inter-Switch Simplified Message Desk Interface**

**A13.72.1 General**

- A. Inter-Switch Simplified Message Desk Interface (ISMDI) service provides subscribers with the capability of receiving call information over a data link interface for use with voice messaging system (VMS) equipment. Only call information routed over the Public Switched Telephone Network using the Common Channel Signaling/Signaling System 7 (CCS/SS7) network is available for ISMDI. The ISMDI data link must be associated with a voice level hunt group assigned to the VMS subscriber. Incoming call data available from the CCS/SS7 network includes the number called, the type of incoming call (direct or forwarding due to busy or no answer), the forwarding number, and the calling number. The numbers are provided as ten digit Directory Numbers.
- B. ISMDI provides the capability for the VMS provider to transmit data messages over the data link to the ISMDI host switch for use in delivering message waiting notification to VMS client users. These data messages will enable the VMS subscriber to activate or deactivate message waiting indicators (MWI) on VMS client station lines served by ISMDI compatible central offices.
- C. The subscriber had the option of specifying an SS7 Point Code to which MWI messages are to be routed.