# **TARIFF DISTRIBUTION**

FILE PACKAGE NO.: FL-18-0024

DATE: March 2, 2018

STATE: FLORIDA

EFFECTIVE DATE: 03/01/2018

TYPE OF DISTRIBUTION: Approved

PURPOSE: Increase Private Line Channels (APL) monthly charges.

<b>TARIFF SECTION</b>	PAGE NUMBER	PAGE REVISION
H003	12	0007
H003	13	0006
H003	14	0009
H003	15	0010
H003	16	0010
H003	17	0010

### **B3. CHANNELS**

## **B3.3 Rate Terms and Conditions (Cont'd)**

### **B3.3.3** Mileage Measurements (Cont'd)

A. (Cont'd)

6. Obtain the square root of the result obtained in 5. This is the rate distance in miles (Fractional miles being considered as full miles.) (Cont'd)

Difference 104 218 Squared 10,816 + 47,524 = 58,340

58,340 divided by 10 = 5834

Square root of 5834 = 76.38 = 77 Airline miles

- **B.** When a private line is furnished over facilities which the Company elects to provide on a direct basis and is not routed through a central office, one two-point channel charge will apply. The arrangement is limited to channels not more than one airline mile in length.
- C. On a multipoint circuit, each channel connecting a hubbing wire center with a serving wire center or a hubbing wire center with another hubbing wire center or a serving wire center with another serving wire center is considered a separate channel for which a mileage charge is independently computed. The total charge for a multipoint channel is the combination of individual legs that connect all points and results in the lowest charge. Bridging charges apply when three or more channels connect at the same location.
- **D.** For Series 1000 and 2000 channels the customer may specify the sequence in which the service points are to be connected in which case the rate mileage is the shortest airline mileage determined in accordance with paragraph C., which will connect the wire centers of the service points in the specified sequence.

## **B3.4 Rates and Charges**

#### **B3.4.1 Local Channels**

- A. Sub Voice Grade (Obsoleted, See B103.)
- **B.** Voice Grade

C.

Per point of termination

1. Voice

		Nonrecurring				
		Monthly	Monthly Charge			
		Rate	First	Additional	USOC	
(a)	Type 2230	\$331.00	\$448.80	\$145.20	P2JUX	(I)
(b)	Type 2231	331.00	448.80	145.20	P2JHX	(I)
(c)	Type 2432	496.00	521.40	184.80	P2JQX	(I)
(d)	Type 2434	104.00	204.60	99.00	P2JGX	(I)
(e)	Type 2435	496.00	481.80	165.00	P2JWX	(I)
(f)	Type 2261	385.00	745.80	303.60	P2JLX	(I)
(g)	Type 2462	458.00	732.60	290.40	P2JRX	(I)
2. Data						
(a)	Type 2260	385.00	534.60	198.00	P2JKX	(M)(I)
(b)	Type 2463	524.00	534.60	198.00	P2JMX	(M)(I)
(c)	Type 2464	524.00	534.60	198.00	P2JNX	(M)(I)
(Obsoleted, See B1	03)					(M)

### **B3. CHANNELS**

# **B3.4 Rates and Charges (Cont'd)**

(M)

### **B3.4.2** Non-Wire Center Connected Channels<sup>1</sup>

- A. Served Direct
  - 1. Not routed via the central office, limited to one airline mile or less

		Monthly	Nonrecurring Charge			
		Rate	First	Additional	USOC	
(a)	Series 1000 (Obsoleted, See B103.)	-	-	-	SDD1X	
(b)	Series 2000	\$78.00	\$627.00	\$217.80	SDD2X	(I)

**Note 1:** Nonrecurring charges are described in B3.3.1.A.

### **B3. CHANNELS**

# **B3.4 Rates and Charges (Cont'd)**

### **B3.4.3** Interoffice Channels<sup>1,2</sup>

- A. Fixed and Mileage Charges applicable
  - 1. Sub Voice Grade Series 1000 (Obsoleted, See B103.)
  - 2. Voice Grade Service Series 2000

		Fixed	Monthly	Nonrecurring		
		Monthly	Charge	Charge		
		Charge	Per Mile	Per Channel	USOC	
(a)	1 thru 8 Miles	\$477.00	\$37.00	\$117.48	3LBBS	(I)
(b)	9 thru 25 Miles	477.00	37.00	117.48	3LBBS	(I)
(c)	Over 25 Miles	477.00	37.00	117.48	3LBBS	(I)

3. (Obsoleted, See B103)

**Note 1:** Nonrecurring charges are described in B3.3.1.A.

**Note 2:** For method of determining mileage, see B.3.3.3.A.

### **B3. CHANNELS**

## **B3.4 Rates and Charges (Cont'd)**

## **B3.4.4** Optional Features and Functions<sup>1</sup>

### A. Bridging

Bridging charges are applicable where more than two Local Channels, or one or more Local Channels and more than one Interoffice Channel, or more than one Local Channel and one Interoffice Channel are bridged or hubbed at the same wire center. No additional bridging charges are applicable for Series 1000, Types 1204 and 1205.

1. Voice Grade Bridges (Series 2000)

		Monthly Rate	Nonrecurring	USOC	
a.	Voice Bridging	Kate	Charge	USUC	
ч.	1) Per Port				
b.	<ul> <li>(a) Two-Wire (Type 2230)</li> <li>(b) Four-Wire (Type 2435)</li> <li>Data Bridging</li> <li>(1) Per Port</li> </ul>	\$ 127.00 165.00	\$ 40.92 40.92	BQ9 BQ9	(I) (I)
c.	(1) Per Port  (a) Four-Wire (Types 2463 and 2464) (Obsoleted, See B103.)	238.00	44.88	BQ9	(I)
d.	(Obsoleted, See B103.)				
e.	Telemetry and Alarm Bridging - Split Band, Active Bridging				
	(1) Common Equipment, per central office				
	(a) First bridging shelf, capacity of 48 two-wire connections	474.00	375.00	XW1	(I)
	(b) Additional bridging shelf, capacity of 56 two-wire connections installed subsequent to the first bridging shelf	474.00	340.00	XW2	(I)
	<ul> <li>(c) Additional bridging shelf, capacity of 56 two-wire connections installed at the same time as the first bridging shelf</li> <li>(2) Channel connections, per channel connected</li> </ul>	240.00	210.00	XW8	(I)
	(a) Remote station channel connection	20.00	33.00	XW3	(I)
	(b) Mid-link channel connection, first channel	48.00	46.00	XW4	(I)
	(c) Mid-link channel connection, subsequent channels	48.00	46.00	XW5	(I)

**Note 1:** Nonrecurring charges are described in B3.3.1.A.

### **B3. CHANNELS**

### **B3.4 Rates and Charges (Cont'd)**

### **B3.4.4** Optional Features and Functions<sup>1</sup> (Cont'd)

#### **B.** Signaling Arrangements

Signaling arrangements are provided at the customer's option to arrange channels for suitable signaling. Signaling is required on all off-premises extension channels and tie line channels associated with PBX (or similar) systems.

Per local channel

			Nonro	ecurring		
		Monthly	Ch	Charge		
		Rate	Initial	Subsequent	USOC	
(a)	Ringdown-Manual <sup>2</sup>	\$78.00	\$55.44	\$277.20	SL3	(I)
(b)	Ringdown-Automatic <sup>2</sup>	72.00	21.12	91.08	SL5	(I)
(c)	E & M Type <sup>3</sup>	72.00	60.72	250.80	SLM	(I)
(d)	Type A (0-199 ohms) <sup>4</sup>	42.00	58.08	184.80	SAL	(I)
(e)	Type B (200-899 ohms) <sup>4</sup>	42.00	56.76	184.80	SAU	(I)
(f)	Type C (900 or more ohms) <sup>4</sup>	20.00	14.52	184.80	SAY	(I)

#### C. Conditioning (Voice Grade Services)

 Conditioning provides more specific transmission characteristics for data services. There are two types of C-conditioning and one type of D-conditioning, each with different technical specifications. C-Type conditioning controls attenuation distortion and envelope delay distortion. D-Type conditioning controls the signal to C-notched noise ratio and inter-modulation distortion.

Conditioning is charged for on a per Local Channel basis for two-point and multi-point service. For two-point services the parameters apply to each service. For multipoint services the parameters apply to any path between any two service points.

2. The types and description of the available conditioning options are as follows:

Type Conditioning	Frequency Response Specifications	Envelope Delay Distortion Specification
C1 (two-point or multipoint)	300-2700 Hz,	1000-2400 Hz, less
	-2dB to $+6dB$ .	than 1000 microseconds
	1000-2400 Hz,	
	-1dB to $+3$ dB.	
	300-3000 Hz,	
	-3dB to $+12dB$ .	

**Note 1:** Nonrecurring charges are described in B3.3.1.A.

Note 2: For use with Type 2230 and 2435 services. Note 3: For use with Type 2432 and 2434 services.

**Note 4:** For use with Type 2231 service.

### **B3. CHANNELS**

# **B3.4 Rates and Charges (Cont'd)**

## **B3.4.4** Optional Features and Functions<sup>1</sup> (Cont'd)

- C. Conditioning (Voice Grade Services) (Cont'd)
  - 2. The types and description of the available conditioning options are as follows: (Cont'd)

Type Conditioning	Frequency Response Specifications	Envelope Dela Specification	y Distortion	
C2 (two-point or multipoint)	300-3000 Hz,	1000-2600 Hz, le	ess	
	-2dB to $+6dB$ .	than 500 micros	than 500 microseconds	
	500-2800 Hz,	600-2600 Hz, les	SS	
	-1dB to $+3$ dB.	than 1500 micros	seconds	
		500-2800 Hz, les	SS	
		than 3000 micros	seconds	
		Non-Linea	r Distortion	
		2nd Order	3rd Order	
	C-Notched Noise	Distortion	Distortion	
D1 (two-point)	Noise level 28dB	35dB below	40dB below	
- '	below signal level	signal level	signal level	
D1 (two-point)	500-2800 Hz, -1dB to +3dB.  C-Notched Noise Noise level 28dB	600-2600 Hz, les than 1500 micros 500-2800 Hz, les than 3000 micros <b>Non-Linea</b> <b>2nd Order</b> <b>Distortion</b> 35dB below	ss seconds seconds ar Distortion 3rd Ord Distortion 40dB belo	

3. When a channel is equipped with Type D1 conditioning and is utilized for voice communications, the Company does not undertake to represent that the channel will be suitable for such voice transmission.

		Nonrecurring				
		Monthly	Cha	arge		
		Rate	Initial	Subsequent	USOC	
4.	C-Type Conditioning					
	a. C-Type Conditioning is available for Types 2463 and 2464.					
	(1) C-Types of Conditioning per local channel					
	(a) C1-Type	\$20.00	\$13.20	\$113.52	P2W	(I)
	(b) C2-Type	20.00	29.04	125.40	P3W	(I)
5.	D-Type Conditioning					
	a. D-Type Conditioning is available for Types 2463 and 2464.					
	(1) D-Type Conditioning per local channel					
	(a) D1-Type	20.00	21.12	118.80	QHA	(I)

**Note 1:** Nonrecurring charges are described in B3.3.1.A.