

**TARIFF DISTRIBUTION**

FILE PACKAGE NO.: KY-16-0040

DATE: May 17, 2016

STATE: KENTUCKY

EFFECTIVE DATE: 05/15/2016

TYPE OF DISTRIBUTION: Approved

PURPOSE: KY GB Cleanup A140, A142

| <b><u>TARIFF SECTION</u></b> | <b><u>PAGE NUMBER</u></b> | <b><u>PAGE REVISION</u></b> |
|------------------------------|---------------------------|-----------------------------|
| G140                         | 1                         | 0002                        |
| G140                         | 1.1                       | 0001                        |
| G140                         | 1.2                       | 0001                        |
| G140                         | 1.3                       | 0001                        |
| G140                         | 1.4                       | 0001                        |
| G140                         | 1.5                       | 0001                        |
| G140                         | 1.6                       | 0001                        |
| G140                         | 1.7                       | 0001                        |
| G140                         | 1.8                       | 0001                        |
| G140                         | 1.9                       | 0001                        |
| G140                         | 1.10                      | 0001                        |
| G140                         | 1.11                      | 0002                        |
| G140                         | 1.12                      | 0002                        |
| G140                         | 1.19                      | 0001                        |
| G140                         | 2                         | 0001                        |
| G140                         | 3                         | 0001                        |
| G140                         | 4                         | 0001                        |
| G140                         | 7                         | 0002                        |
| G140                         | 7.1                       | 0001                        |
| G140                         | 7.2                       | 0001                        |
| G140                         | 7.3                       | 0001                        |
| G140                         | 7.4                       | 0001                        |
| G140                         | 7.5                       | 0001                        |
| G140                         | 7.6                       | 0001                        |
| G140                         | 7.7                       | 0001                        |
| G140                         | 7.8                       | 0001                        |
| G140                         | 7.9                       | 0001                        |
| G140                         | 7.10                      | 0001                        |
| G140                         | 7.11                      | 0002                        |
| G140                         | 7.12                      | 0001                        |
| G140                         | 7.13                      | 0001                        |

|                 |      |      |
|-----------------|------|------|
| G140            | 7.14 | 0001 |
| G140            | 7.15 | 0002 |
| G140            | 7.16 | 0001 |
| G140            | 7.17 | 0002 |
| G140            | 7.22 | 0001 |
| G140            | 8    | 0001 |
| G140            | 9    | 0002 |
| G140            | 10   | 0001 |
| G140            | 11   | 0001 |
| G140            | 12   | 0001 |
| G140            | 13   | 0001 |
| G140            | 14   | 0002 |
| G140            | 14.1 | 0001 |
| G140            | 14.2 | 0001 |
| G140            | 14.3 | 0001 |
| G140            | 14.4 | 0001 |
| G142            | 1    | 0002 |
| G142            | 2    | 0002 |
| G142            | 3    | 0002 |
| G142            | 4    | 0004 |
| G142            | 4.1  | 0001 |
| G142            | 5    | 0003 |
| G142            | 6    | 0003 |
| G142            | 6.1  | 0003 |
| G142            | 6.2  | 0001 |
| G142            | 6.3  | 0001 |
| G142            | 7    | 0002 |
| G140 Cont. (pg) | 1    | 0004 |
| G142 Cont. (pg) | 1    | 0004 |

---

**A140. OBSOLETE SERVICE OFFERINGS- FAST PACKET TRANSPORT SERVICES**

## CONTENTS

|                |   |             |     |
|----------------|---|-------------|-----|
| <b>A140.1</b>  | <b>Frame Relay Service</b>                            | 1           |     |
| A140.1.1       | General   | 1           |     |
| A140.1.2       | <i>Terms and Conditions</i>                           | 1           | (T) |
| A140.1.3       | Rates and Charges                                     | 1.12        |     |
| <b>A140.2</b>  | <b>Reserved For Future Use</b>                        | 1.19        |     |
| <b>A140.3</b>  | <b>Native Mode LAN Interconnection (NMLI) Service</b> | 1.19        |     |
| A140.3.1       | General   | 1.19        |     |
| A140.3.2       | <i>Terms and Conditions</i>                           | 1.19        | (T) |
| A140.3.3       | Rates and Charges                                     | 4           | (T) |
| <b>A140.4</b>  | <b>Reserved For Future Use</b>                        | 4           | (T) |
| <b>A140.5</b>  | <b>Broadband Line Service</b>                         | 7           |     |
| A140.5.1       | General   | 7           |     |
| A140.5.2       | <i>Terms and Conditions</i>                           | 7           | (T) |
| A140.5.3       | Rates and Charges                                     | 7           |     |
| <b>A140.6</b>  | <b>Reserved For Future Use</b>                        | 7           |     |
| <b>A140.7</b>  | <b>Reserved For Future Use</b>                        | 7           |     |
| <b>A140.8</b>  | <b>Asynchronous Transfer Mode (ATM) Service</b>       | 7.1         |     |
| A140.8.1       | General   | 7.1         |     |
| A140.8.2       | <i>Terms and Conditions</i>                           | 7.2         | (T) |
| A140.8.3       | Rates and Charges                                     | 7.18        |     |
| <b>A140.9</b>  | <b>Reserved For Future Use</b>                        | 8           | (T) |
| <b>A140.10</b> | <b>Reserved For Future Use</b>                        | 8           | (T) |
| <b>A140.11</b> | <b>BellSouth Video Conferencing Service</b>           | 8           | (T) |
| A140.11.1      | General   | 8           | (T) |
| A140.11.2      | <i>Terms and Conditions</i>                           | 8           | (T) |
| A140.11.3      | Rates and Charges                                     | 12          |     |
| <b>A140.12</b> | <b>Customer Network Management</b>                    | 14          |     |
| A140.12.1      | General   | 14          |     |
| A140.12.2      | <i>Terms and Conditions</i>                           | 14.2        | (T) |
| A140.12.3      | Rates and Charges                                     | 14.4        |     |
| <b>A140.13</b> | <b>(DELETED)</b>                                      | <b>14.4</b> | (T) |

## A140. OBSOLETE SERVICE OFFERING-FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service

(Obsoleted 9/19/2011, Type B - Not available for new installations, additions or on transfers of service to new location.)

#### A140.1.1 General

- A. Frame Relay Service is a connection oriented data transport service based on packet switching technology.
- B. Frame Relay Service provides flexible connectivity using Permanent Virtual Circuits (PVCs) implemented over digital facilities operating at transmission speeds of 56 Kbps, 64 Kbps, 128 Kbps, 1.536 Mbps or 44.210 Mbps.
- C. Network interface specifications for Frame Relay Service are contained in the following documents:
  - ANSI T1.617-1991, "Integrated Services Digital Network (ISDN) - Digital Subscriber Signaling System No. 1 (DSS1) Signaling Specification for Frame Relay Service", American National Standards Institute, April 1991 and ANSI T1.618-1991, "Integrated Services Digital Network (ISDN) - Core Aspects of Frame Relay Protocol for use with Frame Relay Bearer Service", American National Standards Institute, April 1991. Both of these documents may be ordered from:  
American National Standards Institute  
Customer Service  
11 West 42nd Street  
New York, New York 10036
  - Document No. 001-208966, "Frame Relay Specification with Extension Based on Proposed T1S1 Standards", Revision 1.0, Digital Equipment Corporation, Northern Telcom, Inc., and StrataCom, Inc., September 1990. This document may be ordered from:  
Frame Relay Forum  
39355 California Street  
Suite 307  
Freemont, CA 94538-1447
  - TR-73587 Frame Relay Service Interface and Performance Specifications. This document may be ordered from:  
**AT&T** Telecommunications, Inc. (T)  
Regional Documentation Coordinator  
20th Floor  
600 North 19th Street  
Birmingham, AL 35203
- D. Frame Relay Service, as provided for in this Section, is offered for intraLATA use only.
- E. The **Terms, Conditions** and rates specified herein are in addition to the applicable **Terms, Conditions** and rates specified in other sections of this and other Guidebooks of the Company. (T)
- F. The rates and charges set forth for Frame Relay Service provide for the furnishing of service where suitable facilities are available.
- G. Frame Relay Service is only available when provided in conjunction with Broadband Line Service. Specifications for Broadband Line Service are contained in A40.5. (T)

#### A140.1.2 Terms and Conditions (T)

- A. Explanation of Terms
  - 1. Customer Connection to Frame Relay Service  
The Customer Connection provides the customer with the standard interface to the Frame Relay Service network. This interface receives the data frame from the customer's network or device and verifies that the DLCI is valid before relaying the frame to the destination. Included in the Customer Connection are the customer's termination on the Frame Relay Service switching equipment, the transport from the Serving Area Point to the switching equipment, and the first DLCI. These interfaces connect the Frame Relay Service network with digital facilities operating at transmission speeds of 56 Kbps, 64 Kbps, 128 Kbps, 1.536 Mbps, or 44.210 Mbps.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service (Cont'd)

#### A140.1.2 Terms and Conditions (Cont'd)

##### A. Explanation of Terms (Cont'd)

##### 2. Frame Relay Service Network Serving Area

Certain Company Central Offices are designated by the Company as Serving Area Points for the Frame Relay Service Network Serving Area. A customer accessing the Frame Relay Service network, whose Serving Wire Center is designated a Serving Area Point, requires a Broadband Line-Fast Packet Option (FPO) as described in A40.5. A Frame Relay Service customer, whose Serving Wire Center is not designated a Serving Area Point, will use a Broadband Line-FPO to the Wire Center, as well as, the Broadband Line Extension-FPO (also described in A40.5) to gain access to the closest designated Serving Area Point.

##### 3. Permanent Virtual Circuit (PVC)

A PVC is a software defined data path transporting data within the Frame Relay Service network between two Customer Connections. This data path, once defined in the network software, does not have to be established again. PVCs are end-to-end, bi-directional channels that are established via the service provisioning process. A Standard PVC is created via the mapping of two Standard DLCIs; on an optional basis features are available to allow the creation of Priority Voice and Priority Data, Intelligent and MultiCast PVCs.

##### a. Priority PVC

Priority PVC capability allows a customer to differentiate specific PVCs with regard to the importance of the data within those PVCs as compared to other PVCs. In the case of contention or network congestion, the Frame Relay Service network will give precedence to the frames of a Priority PVC over frames of a Standard PVC. Frame Relay Service allows the creation of Priority Voice PVCs and Priority Data PVCs. Such a Priority PVC is formed by the mapping of Priority Voice or Priority Data DLCIs<sup>1</sup> (as set forth in A140.1.3.C.1.b or c) to Priority Voice and Priority Data DLCIs; these Priority DLCIs must have an associated CIR value of greater than zero.

##### b. Intelligent PVC

Intelligent PVC capability allows automatic rerouting on a per PVC basis within the Frame Relay Service network. The Intelligent PVC feature is associated with a customer-specified three DLCI PVC. With the Intelligent PVC feature, a PVC is established between an originating DLCI (referred to as the pivot endpoint) and a primary terminating DLCI (referred to as the primary endpoint). Frames from the originating DLCI (pivot endpoint) will automatically be rerouted to a secondary terminating DLCI (referred to as the secondary endpoint) if the Frame Relay switch detects trouble associated with the primary terminating DLCI (primary endpoint). After such rerouting, the Frame Relay switch will continue to monitor the signals from the primary endpoint and when the trouble is cleared, will automatically reroute the frames going to the secondary endpoint back to the primary endpoint. The document TR-73587 provides more detailed technical information on how Intelligent PVC capability is provided.

##### c. MultiCast PVC

MultiCast PVC capability allows a customer to establish a one-to-many broadcasting PVC that distributes data simultaneously from a host site to a group of predetermined remote sites (called a MultiCast PVC Group). Transmission on a MultiCast PVC is unidirectional (from the host to the remotes in each MultiCast PVC Group). All sites in a MultiCast PVC Group will be able to simultaneously receive a single packet transmission transmitted from the host; upon transmission from the host, the Frame Relay network replicates and distributes the packets to the various remote sites identified as members of the MultiCast PVC Group. A MultiCast PVC may be established as a Standard MultiCast PVC or as a Priority MultiCast PVC (refer to description of Priority PVC capability discussed in A140.1.2.A.3.a).

##### 4. Data Link Connection Identifier

The Frame Relay standard specifies an address field called the Data Link Connection Identifier (DLCI). The DLCI specifies a connection. When any two DLCIs are mapped together, a PVC can be created. When three DLCIs are associated together, an Intelligent PVC can be formed. A DLCI which is not a Priority DLCI (as specified in A140.1.2.A.3.a.) is referred to as a Standard DLCI.

**Note 1:** PVCs are bi-directional unless specified otherwise (e.g., a MultiCast PVC is uni-directional).

(T)

(T)

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service (Cont'd)

#### A140.1.2 Terms and Conditions (Cont'd)

(T)

##### A. Explanation of Terms (Cont'd)

##### 5. Committed Information Rate (CIR)

Committed Information Rate is a feature that enables the customer to select a sustained throughput under normal conditions. A CIR must be selected for each DLCI. A CIR selected with a value greater than zero has a separate charge from any DLCI charges. Frames submitted at a rate above the subscribed CIR will be marked "discard eligible" (DE) and, should network congestion occur, are subject to being dropped by the network. If CIR is set equal to zero, then all frames will be marked DE. However, in the absence of network congestion, DE marked frames will be transported with the same reliability as frames not marked DE within a single, Company Frame Relay Switch. The CIR value selected cannot exceed the minimum transmission speed of the link at either end of the PVC.

The CIR value of Priority Voice DLCIs and Priority Data DLCIs must be greater than zero.

##### 6. Feature Change Charge

In addition to any specific optional feature charges, a Feature Change Charge applies whenever a change is made (at the customer's request) to a single optional feature for a single customer within a single network configuration on a single switch within a single jurisdiction. Only one Feature Change Charge will apply per service order required to perform the work.

A Feature Change Charge is applicable if the "first" DLCI, the one included with the Customer Connection, is modified.

##### 7. Serving Area Point (SAP)

A Company Central Office that is designated as a member of the Frame Relay Service Network Serving Area (See the definition of Frame Relay Service Network Serving Area).

##### 8. Backup Capability

Backup Capability is available on an optional basis and provides the customer with the ability to have a backup logical port configured to his service needs in the event that the customer's primary connection is disabled. A Backup Customer Connection utilizes a Broadband Line (with Broadband Line Extension Service, as appropriate). Both the Backup Customer Connection and its associated Broadband Line Service are specifically dedicated to providing backup service and remain idle except when being utilized for backup purposes.

The customer must prearrange with the Company which primary Customer Connection(s) may be directed to a specific Backup Customer Connection so that the necessary work is done by the Company which is required prior to backup capability being possible. A Customer Connection so identified which may be redirected in the event of a failure is referred to as a backup enabled primary Customer Connection, or referred to herein as simply the primary Customer Connection. A Frame Relay primary Customer Connection may only utilize a Frame Relay Backup Customer Connection and both must be the same type of interface (i.e., both configured as either NNI or UNI interfaces). A primary Customer connection must be in the same Frame Relay Network Serving Area as its identified Backup Customer Connection. A primary Customer Connection may have only one Backup Customer Connection identified. A Backup Customer Connection may serve as the backup for more than one primary Customer Connection; however, a Backup Customer Connection may only be actively in use with one primary Customer Connection at a given time.

The Backup Customer Connection is manually activated by the Company when the customer requests service from a primary Customer Connection to be redirected to its pre-identified Backup Customer Connection. All DLCIs associated with the primary Customer Connection are rerouted to the Backup Customer Connection<sup>1</sup>. It is strongly recommended that the size of the Backup Customer Connection be the same size as the customer's largest primary Customer Connection.

In the event that the customer chooses to utilize a Backup Customer Connection which is of a lower speed than the primary Customer Connection, the Company cannot guarantee the sufficiency of the Backup Customer Connection to protect the customer's primary data. There exists the realistic possibility that due to the lower amount of physical bandwidth on the Backup Customer Connection in such cases, that not all of the customer's DLCIs will be provisioned to the Backup Customer Connection. Network congestion may be encountered, which may result in packets of data being discarded or entire locations without access to Backup Capability.

A Backup Customer Connection is not eligible for Network Service Level Agreements (SLAs) specified in B.6.

**Note 1:** To appropriately provision new DLCIs ordered subsequent to a primary Customer Connection being enabled for Backup Capability, subsequent orders for DLCIs should specify that the DLCIs are being requested in association with a primary Customer Connection.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.1 Frame Relay Service (Cont'd)****A140.1.2 Terms and Conditions (Cont'd)**

(T)

**A.** Explanation of Terms (Cont'd)

## 9. Oversubscription

A customer may establish multiple PVCs on a Frame Relay Service Customer Connection with a total CIR greater than the Frame Relay Service Customer Connection speed. This is called oversubscription. This allows the customer to take advantage of the fact that not all of these PVCs will be active simultaneously. However, the network's apparent performance will be degraded if the customer attempts to make use of this overbooked commitment (or oversubscription) beyond the capacity of the Frame Relay Service Customer Connection. In the worst case, attempts to fully utilize such overbooked commitment may appear to the customer as network unavailability.

The amount of oversubscription (expressed as a percentage) will be determined by the following formula:

$$\frac{\text{Sum of the CIR/PVC on a single Frame Relay Customer Connection}}{\text{Frame Relay Service Customer Connection speed}} \times 100$$

In order to qualify for Network SLAs (as specified in B.6.), a Frame Relay Service Customer Connection may only oversubscribe up to 200%. In the event the customer exceeds this oversubscription limit, Network SLA credits will not be issued. The customer then must either upgrade their Frame Relay Service Customer Connection speed or subscribe to an additional Customer Connection(s) to remain less than or equal to the 200% oversubscription limit to qualify for future Network SLA crediting.

**B.** Basis of Offering

1. Detailed monthly billing is not provided.

2. Suspension of service is not allowed.

3. Obligations of Customer and Company

a. The Company is not responsible for the installation, operation, or maintenance of any equipment provided by the customer.

b. The customer is responsible for the provision and maintenance of all Customer Provided Equipment (CPE) and to ensure that the operating characteristics of this equipment are compatible with and do not interfere with the service offered by the Company.

c. The maximum number of DLCIs per Customer Connection is subject to the characteristics of the customer's data traffic. Thus, the number of DLCIs per Customer Connection must be negotiated between the customer and the Company at the establishment of the Customer Connection and subsequent to the establishment should the traffic characteristics change.

## **A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

### **A140.1 Frame Relay Service (Cont'd)**

#### **A140.1.2 Terms and Conditions (Cont'd)**

(T)

##### **B. Basis of Offering (Cont'd)**

4. In order to maintain the quality of Frame Relay Service, the Company reserves the right to perform preventive maintenance and software updates to the network. This could result in Frame Relay Service being unavailable during the time period between 2:00 A.M. and 4:00 A.M. Eastern Time on any given Monday or Sunday morning. However, the Company only expects to utilize this maintenance window for any given switch on the average of once a quarter. In addition, the Company will make every reasonable effort to provide advance notice to those customers likely to be severely affected by such maintenance work. This maintenance window may be adjusted by the Company upon written notice to the customer.
5. The minimum service period is one month.
6. Service Level Agreement

Frame Relay Service includes Service Level Agreements (SLAs) which specify the Company's provisioning, repair and performance commitments for Frame Relay Service in specific areas. Provisioning and repair commitments are measured on a per occurrence basis. Network service level commitments are monthly performance measurements. The following service measurements will outline the service levels that the Company will deliver to its Frame Relay customers.

##### Provisioning and Repair:

- Frame Relay Installation Interval
- Frame Relay Time-To-Repair

##### Network Service Levels:

- Frame Relay Network Availability
- Frame Relay Network Transit Delay
- Frame Relay Frame Delivery Rate

Service Level Commitments will define Frame Relay service measurements that the Company agrees to provide every customer. If the Company fails to meet a Service Level Commitment, the customer is eligible for a SLA credit. Credits for missed Network Service Level Commitments will only be available to customers subscribing to the Gold Package in Customer Network Management from A140.12. Billing credits which may apply if the Company does not meet the objectives associated with these stated SLAs (specifically covering rates for Frame Relay Service and associated Broadband Line Service from Section A40.) are provided as set forth in c. Credits only apply for portions of service supplied by the Company.

##### a. SLA Service Level Commitments

The Company's Service Level Commitments for Frame Relay Service are as follows:

- Frame Relay Installation Interval - Standard Interval
- Frame Relay Time-To-Repair on customer sites within the Frame Relay Network Serving Area - 4 hours
- Frame Relay Network Availability on a customer's network within the Frame Relay Network Serving Area - 99.9%
- Frame Relay Network Transit Delay/One Way - 60 milliseconds
- Frame Relay Delivery Rate of all frames transmitted with CIR greater than 32 Kbps - 99.9%



## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service (Cont'd)

#### A140.1.2 Terms and Conditions (Cont'd)

##### B. Basis of Offering (Cont'd)

##### 6. Service Level Agreement (Cont'd)

##### b. SLA Restrictions

The Company will implement SLA provisioning restrictions that will define customer network design requirements and limitations to the Company's commitment to meet Service Levels for Frame Relay Service. Customer network design requirements are intended to limit or negate the Company's obligation to provide SLA credits when the customer has under-engineered their AT&T Frame Relay network. The customer network design requirements are as follows:

- The customer's network must have a minimum of 10 customer connections for the Company to provide SLA credits.
- The total CIR on all PVCs carried by any of the customer's Frame Relay Customer Connections may not be greater than 200% of the Customer Connection port speed (oversubscription).
- A customer must be subscribing to the Gold Package in Customer Network Management (CNM) from A140.12 to receive credits for missed Network Service Level Commitments. Customer Connections at both ends of a PVC must have the CNM Gold Package or equivalent. In the event only one end of a PVC is ordered from this Guidebook, credits will only be issued for the rate elements ordered from this Guidebook.

SLA credits do not apply when any stated objective is not met because the Company does not have control over the circumstances causing the objective to be missed. Situations over which the Company does not have control can be defined as, but not limited to, the following:

- any act, any omission or negligence on the part of the customer, any other customer or any third party, or of any other entity providing a portion of the service,
- labor difficulties, governmental orders, civil commotions, declared National Emergencies, criminal actions against the Company, acts of God, war, or other circumstances beyond the Company's control,
- the customer's premises equipment,
- unavailability of the customer's facilities and/or equipment, and
- customer oversubscription of Frame Relay Service Customer Connections.

SLA commitments only apply for service wholly within Company territory. SLA commitments will not apply for circuits which are part of a jointly provided service. SLA commitments do not apply for service provided by other telephone companies concurring in the rates, *terms and conditions* of the Company. (T)

The customer must request a credit within one calendar month of the Company missing a Frame Relay Service Level Commitment. The Company will investigate customer requests for any SLA credits to determine the cause of any performance failures reported by the customer. The Company will investigate the customer's request over a period of up to 45 calendar days. The 45-day period will begin when the customer makes the request for credit with their *Company* Sales Representative. SLA credits will be provided to the customer if the Company determines that the Company had control over the circumstances causing the failure. If the Company determines that these failures are the result of oversubscription of Frame Relay Service Customer Connections, the Company will provide the customer with the reports documenting the oversubscription and Network SLA credits will not be issued. The customer will be required to upgrade their Frame Relay Service Customer Connections or no future SLA credits will be allowed on that Frame Relay Service Customer Connection(s). (T)

When a customer requests a SLA credit for Frame Relay Network Availability, all requests for a calendar month must be submitted at the same time. For example, the customer receives a SLA report on May 1, providing a report on April performance. Any requests for Network Availability SLA credits on Customer Connections for the month of April must all be submitted together.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service (Cont'd)

#### A140.1.2 Terms and Conditions (Cont'd)

##### B. Basis of Offering (Cont'd)

##### 6. Service Level Agreements (Cont'd)

##### c. SLA Credits for Frame Relay Service Level Commitments

The following credits will apply when the Company misses a Service Level Commitment (each credit is described in (1) thru (5)):

- Frame Relay Installation Interval – Credit non-recurring installation charge paid by the customer
- Frame Relay Time-To-Repair – Credit one day of Monthly Recurring Charge (MRC)
- Frame Relay Network Availability – Credit one day of MRC
- Frame Relay Network Transit Delay – Credit MRC
- Frame Relay Frame Delivery Rate – Credit MRC

The SLA credit amount will be determined by applying the credits outlined above to the rate elements or total billed revenues specified following.

(1) Frame Relay Installation Interval Credit - this credit will only apply to the installation or upgrade of a Frame Relay Customer Connection. The credit will be equal to the nonrecurring installation charge for the Customer Connection, Broadband Line and Broadband Line Extension. The credit will not apply to expedited installations or to installations where no facility and/or switch exist. If on the due date the customer is not ready or in a case where another of the customer's service providers (including the customer's provider of customer premises equipment, interexchange service, or other local service provider) is not ready, the Company is not liable for missing the due date and SLA credits do not apply.

(2) Frame Relay Time-To-Repair Credit - this credit will require that the customer report the problem to the **Company's** Repair Center. The repair interval will start with the time entered on the trouble ticket. The Service Level Commitment measurement will be based on each individual trouble ticket for a Customer Connection. Multiple trouble tickets on the same day for the same Customer Connection will only be eligible for one time-to-repair credit. The credit will be one day of the MRC for the Customer Connection and Broadband Line. Credits on any individual Customer Connection for a calendar month cannot exceed the MRC for the Customer Connection and Broadband Line.

(3) Frame Relay Network Availability – this credit will apply in the event that the measurement for the customer's network is missed. The credit will then be for each Frame Relay Customer Connection which does not meet the 99.9% availability commitment. The credit will be one day of the MRC of the Frame Relay Customer Connection and the Broadband Line. The unavailability of a Customer Connection will be calculated from the trouble tickets submitted for the Customer Connection. The unavailability of a customer's network will be calculated from the trouble tickets submitted for each Customer Connection within the customer's network. The Service Level Commitment will be calculated by first subtracting the unavailable time from the total available time for a particular calendar month and then dividing it by the total available time. Included in available time are scheduled maintenance windows and time the network was unavailable due to circumstances outside the Company's control.

(4) Frame Relay Network Transit Delay – measurement will be on each Frame Relay PVC (network port to network port). The credit will be equal to the MRC for the DLCI pair making up the PVC.

(5) Frame Relay Frame Delivery Rate – measurement will be on each Frame Relay PVC. The credit will be equal to the MRC for the DLCI pair and 15 days of the MRC for each CIR making up the PVC.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.1 Frame Relay Service (Cont'd)****A140.1.2 Terms and Conditions (Cont'd)****C. Provision of Service****1. Rates and charges contained in this Section consist of the following elements:****a. Customer Connection to Frame Relay Service**

Frame Relay Service Customer Connections are available at the following transmission speeds: 56 Kbps, 64 Kbps, Fractional T1, Subrate T1, 1.536 Mbps, MultiLink, Subrate T3 and 44.210 Mbps.

- (1) Fractional T1 Customer Connections are provided at the following specific transmission speeds: 112 Kbps, 128 Kbps, 192 Kbps, 256 Kbps, 320 Kbps, 384 Kbps, 448 Kbps, 512 Kbps, 576 Kbps, 640 Kbps, 704 Kbps, 768 Kbps, 1024 Kbps and 1152 Kbps. A Fractional T1 Customer Connection is provisioned in association with a channelized 1.536 Mbps transport facility and requires the dedication of only a quantity of the DS0 channels equivalent to the Fractional T1 Customer Connection transmission speed.
- (2) Subrate T1 Customer Connections are provided at the following specific transmission speeds: 128 Kbps, 256 Kbps, 384 Kbps, 512 Kbps, 768 Kbps and 1152 Kbps. A Subrate T1 Customer Connection is also provisioned in association with a 1.536 Mbps transport facility but requires the dedication of the full 1.536 Mbps transport facility's bandwidth.
- (3) MultiLink Customer Connections are provided at the following specific transmission speeds: 3 Mbps, 6 Mbps, 9 Mbps and 12 Mbps. A MultiLink Customer Connection is provisioned in association with multiple 1.536 Mbps Broadband Line facilities whose combined bandwidth is equivalent to the transmission speed of the MultiLink Customer Connection. MultiLink Customer Connections will not be available to operate with Customer Network Management or Frame Relay Back-Up Capability until such time as technical limitations are resolved.
- (4) Subrate T3 Customer Connections are provided at the following specific transmission speeds: 3 Mbps, 6 Mbps, 9 Mbps, 12 Mbps, 15 Mbps, 18 Mbps, 21 Mbps, 24 Mbps, 27 Mbps, 30 Mbps and 33 Mbps. A Subrate T3 Customer Connection is provisioned in association with a 44.210 Mbps transport facility and requires the dedication of the full 44.210 Mbps transport facility's bandwidth.

**b. Back-Up Capability****c. Frame Relay Service Features**

(T)

(T)

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.1 Frame Relay Service (Cont'd)****A140.1.2 Terms and Conditions (Cont'd)**

(T)

**C. Provision of Service (Cont'd)**

2. Certain Company Central Offices are designated by the Company as Serving Area Points (SAPs) for the Frame Relay Service Network Serving Area. A customer accessing the Frame Relay Service network, whose Serving Wire Center is designated a SAP, will only require a Broadband Line-FPO as described in A40.5. A Frame Relay Service customer, whose Serving Wire Center is not designated a SAP, will require a Broadband Line-FPO to the Serving Wire Center, as well as, a Broadband Line Extension-FPO (also described in A40.5) to gain access to the closest designated SAP.
3. The Customer Connection rate element includes the customer's transport from a Serving Area Point to the Frame Relay Service switching equipment and the customer's termination on the Frame Relay Service switching equipment. One Initial DLCI is applicable when DLCIs are ordered at the same time as the installation of the Customer Connection. Only one "Initial" DLCI (either one Initial Standard DLCI or one Initial Priority DLCI) is allowed per Customer Connection. Additional DLCIs (beyond this initial DLCI) ordered with the installation of the Customer Connection and any DLCIs ordered subsequent to the installation of the Customer Connection are considered Additional DLCIs.
4. Service Charges for installing Frame Relay Service are included in the respective nonrecurring charges specified herein. Service Charges from Section A4 are not applicable for installing such services. Charges applicable for customer requested change of service installation due date and cancellation of service installation are as specified in A40.9.
5. Should a customer, having locations in more than one Frame Relay Network Serving Area within a LATA, desire to send data traffic between these locations, the customer can interconnect these locations through the following two options:
  - a. Dedicated Connection:

The customer subscribes to additional Customer Connections (in each Network Serving Area) which are enabled to support inter-serving area connectivity and Broadband Line Extension-FPOs to connect them. These additional rate elements will be used solely to transport this customer's data traffic between affected Frame Relay Network Serving Areas. In addition to the normal DLCI and CIR charges associated with each PVC, additional DLCI and CIR charges apply per PVC between the additional Customer Connections except when these connections have been specifically requested by the customer to be provisioned as customer specific trunks.
  - b. Shared Connection:

The Company may establish facilities between Frame Relay Service switching equipment in different Network Serving Areas in the same LATA and may allow customers to share bandwidth on these facilities; where these shared facilities are available to customers, a shared connection is an option. The customer must establish one or more Inter-Network Serving Area Links that extend between Frame Relay switches. Each of these links has an associated CIR. One PVC exists between both customer premises through each link. All CIRs on this PVC must have the same value. Charges for the Inter-Network Serving Area Link are applied as follow:

    - the Inter-Network Serving Area Link Establishment is charged at each end of the link,
    - the Inter-Network Serving Area Link CIR is charged at each end of the link, and
    - no additional DLCI charges apply for the link (however, normal DLCI and CIR charges apply for the PVC).
6. In some cases, the Company and another Incumbent Local Exchange Company that offers Frame Relay technology will jointly connect Frame Relay switching equipment within a LATA to provide customers the ability to interconnect their locations served by the different companies. In order to utilize the Company's portion of this jointly provided shared connection, the customer must subscribe to one end of an Inter-Network Serving Area Link and the associated CIR.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service (Cont'd)

#### A140.1.2 Terms and Conditions (Cont'd)

##### C. Provision of Service (Cont'd)

7. Based upon Frame Relay Forum Implementation Agreement 5 (FRF.5), a Frame Relay end user may send data from a premises location with a Frame Relay User Network Interface (UNI) or a Network to Network Interface (NNI) to another premises with an Asynchronous Transfer Mode (ATM) Service UNI. The Frame Relay data is essentially encapsulated in the ATM Service bit stream and must be retrieved by the end-user's CPE as Frame Relay. To enable this feature, the customer must establish one or more Frame Relay/ATM interworking links that extend between the Frame Relay and ATM switches. Each of these links has an associated CIR. One PVC exists between these switches through this link. All CIRs on this PVC must have the same value. The following charges apply for this Frame Relay/ATM Network Interworking feature:

- the Inter-Network Serving Area Link Establishment is charged at each end of this link, and
- the Inter-Network Serving Area Link CIR is charged at each end of this link, and
- no additional DLCI charges apply for the interworking link (however, normal DLCI and CIR charges apply for the PVC).

8. To have Back-Up Capability as an option, the customer is required to have a Back-Up Customer Connection and a separate Broadband Line (with Broadband Line Extension Service, as appropriate) which are designated specifically for back-up purposes. Monthly rates and nonrecurring charges applicable for a Back-Up Customer Connection are provided in A140.1.3.B.1. Monthly rates and nonrecurring charges for Broadband Line Service are found in A40.5.

The activation of a Back-Up Customer Connection via the rerouting of traffic from a primary Customer Connection to the Back-Up Customer Connection is a manual operation performed by the Company at the direction of the customer. At the direction of the customer, the Company will subsequently then redirect traffic from the Back-Up Customer Connection to the primary Customer Connection.

A Primary Customer Connection Back-Up Enablement/Change Charge provided in A140.1.3.B.2 is applicable per existing primary Customer Connection which is requested by the customer to be back-up enabled. A Primary Customer Connection Back-Up Enablement/Change Charge is also applicable for each existing back-up enabled primary Customer Connection when the customer requests a reassignment of that primary Customer Connection to a different Back-Up Customer Connection.

9. To create a Priority PVC, the customer requests the mapping of Priority Voice or Priority Data DLCIs. Feature Change Charges apply for requests to convert existing Standard PVCs to Priority PVCs (or vice versa).<sup>1</sup> A Feature Change Charge applies per service order required to perform the work.

At the customer's request, a Priority PVC may be formed between a Frame Relay Service Priority Voice or Priority Data DLCI and an ATM Service non-UBR PVC Segment (which would additionally require Frame Relay to ATM Interworking capability).<sup>2</sup> A Feature Change Charge shall apply for a request involving an existing Frame Relay to ATM Interworking PVC where the associated Standard DLCI is converted to a Priority DLCI (or vice versa); a Frame Relay Service Feature Change Charge applies per service order required to perform the Frame Relay Service work.

10. To create a Frame Relay Service Intelligent PVC, the customer requests the mapping of three DLCIs. A Frame Relay Service Intelligent PVC may be comprised of three Standard DLCIs, three Priority Voice DLCIs or three Priority Data DLCIs. One Intelligent PVC Charge (a recurring rate) applies per customer-specified arrangement of 3 DLCIs and applies in addition to the appropriate nonrecurring and recurring charges for each of the three DLCIs. The Intelligent PVC Charge shall be billed to the Customer Connection associated with the DLCI which is the pivot endpoint (as explained in A140.1.2.A.3.b.) of this PVC.

A request to convert an existing two DLCI PVC into a three DLCI Intelligent PVC (or vice versa) shall be considered as a request to disconnect the existing PVC and as a request for the connection of new DLCIs to form the new PVC. At the customer's direction, the DLCI numbers associated with the PVC being disconnected may be reused for the DLCIs associated with the new PVC.

The pivot endpoint of an Intelligent PVC must be provisioned out of a Company-provided Frame Relay Service switch. The primary endpoint and secondary endpoint of an Intelligent PVC may be associated with premises located outside of Company territory. If only Company provided switches are utilized in the total service configuration, no service limitations should occur; however, when a non-Company switch is involved in an Intelligent PVC configuration, service limitations may be encountered. BellSouth document TR-73587, which contains technical information on Intelligent PVC rerouting, provides details relating to such limitations.

Both the primary and secondary endpoints of an Intelligent PVC must be of the same service type; therefore, both endpoints must be Frame Relay Service because the use of any method of Frame Relay to ATM interworking within an Intelligent PVC configuration is not currently technically feasible.

**Note 1:** Applicable for such requests on Standard PVCs, Intelligent PVCs or MultiCast PVCs.

**Note 2:** Not applicable to Priority MultiCast PVCs where Frame Relay to ATM Interworking is not technically possible.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.1 Frame Relay Service (Cont'd)

#### A140.1.2 Terms and Conditions (Cont'd)

##### C. Provision of Service (Cont'd)

11. To create a MultiCast PVC, the customer must have established individual PVCs between the Customer Connection of the host site and each Customer Connection of each remote site that is to be a member of that specific MultiCast PVC Group. Standard charges apply for the establishment of the DLCIs, CIR, etc. associated with these member PVCs. While these standard PVCs will be identified as members of a MultiCast PVC Group (and as such receive the unidirectional broadcast transmission from the host site), each individual PVC is still a bi-directional PVC capable of being used by the host site and remote site to communicate independently of the MultiCast PVC Group.

The customer shall provide a unique DLCI number to be used to identify each MultiCast PVC Group associated with a host site; this unique DLCI number will be used in establishing the MultiCast PVC and shall be utilized on an ongoing basis to refer to that specific MultiCast PVC when requesting any subsequent change activity to the associated MultiCast PVC Group. A host site can have more than one MultiCast PVC. A remote site can be a part of multiple MultiCast PVC Groups associated with the same or multiple other host site(s).

Each MultiCast PVC Group shall be established as a Standard MultiCast PVC Group or a Priority MultiCast PVC Group. A Standard MultiCast PVC Group shall be comprised of member PVCs established utilizing all Standard DLCIs; while not specifically required, it is strongly recommended that each member PVC in a Standard MultiCast PVC have DLCIs with an associated CIR value of greater than zero. A Priority MultiCast PVC Group shall be comprised of member PVCs established utilizing all Priority (Voice or Data) DLCIs; each member PVC in a Priority MultiCast PVC is required to have Priority (Voice or Data) DLCIs with an associated CIR value of greater than zero.

One MultiCast PVC Group Charge shall apply and be billed to the host site in association with each MultiCast PVC established. The appropriate MultiCast PVC Group Charge varies based *upon*; 1) whether the MultiCast PVC is to be a Standard MultiCast PVC or a Priority MultiCast PVC, and 2) the transmission speed of the host site Frame Relay Customer Connection (e.g., the Priority 1.536 Mbps MultiCast PVC Group Charge would be applicable for a Priority MultiCast PVC established on a 1.536 Mbps Frame Relay Customer Connection).

A MultiCast PVC Group Modification Charge applies per member PVC that is requested to be modified, added to or deleted from an existing MultiCast PVC Group, subsequent to the initial establishment of the MultiCast PVC. The MultiCast PVC Group Modification Charges are billed to the host Customer Connection.

If a Standard MultiCast PVC is requested to be changed to a Priority MultiCast PVC (or vice versa), Feature Change Charges apply as set forth in A140.1.2.C.9 to change each DLCI in each member PVC from Standard to Priority (or vice versa). In addition to the nonrecurring charge associated with the MultiCast PVC Group Charge billed to the host for this change request, a MultiCast PVC Group Modification Charge shall also apply per member PVC so modified in the MultiCast PVC Group.

The Frame Relay Customer Connection associated with the host site must be of a transmission speed equal to or greater than 1.536 Mbps and may not be a MultiLink Customer Connection.

A service inquiry will be required in order to determine the availability of MultiCast PVC Capability to meet each customer request for a MultiCast PVC as a result of the following limitations. MultiCast PVC Capability is possible only where Frame Relay switch facilities are available (that serve the host site) that are currently technically capable of provisioning this feature. There is an additional limitation on the total number of MultiCast Groups which can be established per Frame Relay switch; consequently, capacity may not exist to fulfill a customer's request. Additionally, there is a per MultiCast PVC Group limit on the number of members possible which varies based upon the packet size transmitted by the host site; as the standard packet size increases, the number of members that may be in the MultiCast PVC Group decreases.

M1 - Material previously appearing on this page now appears on page(s) 1.9 of this section.

M2 - Material appearing on this page previously appeared on page(s) 1.11 of this section.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.1 Frame Relay Service (Cont'd)****A140.1.2 Terms and Conditions (Cont'd)**

(T)

(M)

**D. Contract Plans**

1. Contract plans *as* specified in the Fast Packet Services Payment Plan in A40.10 with contract periods are described as follows:
  - a. Term Payment Plan A - payment periods may be selected from 12 to 36 months.<sup>1</sup>
  - b. Term Payment Plan B - payment periods may be selected from 37 to 60 months<sup>2</sup>
2. (DELETED)
3. (DELETED)
4. A Termination Liability Charge will not apply to Frame Relay Service terminated on or after the date Frame Relay Service became an obsolete service offering.

**Note 1:** As of January 20, 2011, Term Payment Plan A payment periods greater than 24 months are no longer available for new or renewing subscribers.

**Note 2:** As of January 20, 2011, Term Payment Plan B payment periods are no longer available for new or renewing subscribers.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

**A140.1 Frame Relay Service (Cont'd)**

**A140.1.3 Rates and Charges**

**A. Customer Connection to Frame Relay Service**

1. A minimum of one Customer Connection is required per customer to subscribe to Frame Relay Service.

|                             | Nonrecurring Charge | Month To Month | A <sup>4</sup> 12 to 36 Months | B <sup>5</sup> 37 to 60 Months | USOC  |
|-----------------------------|---------------------|----------------|--------------------------------|--------------------------------|-------|
| (a) at 56 Kbps <sup>1</sup> | \$425.00            | \$177.00       | \$153.00                       | \$ 74.00                       | FRH56 |
| (b) at 64 Kbps <sup>1</sup> | 425.00              | 177.00         | 153.00                         | 74.00                          | FRH64 |
| (c) at Fractional T1        |                     |                |                                |                                |       |
| - 112 Kbps <sup>2</sup>     | 475.00              | 249.00         | 216.00                         | 102.00                         | FRH11 |
| - 128 Kbps <sup>2</sup>     | 475.00              | 249.00         | 216.00                         | 102.00                         | FRH12 |
| - 192 Kbps <sup>2</sup>     | 475.00              | 496.50         | 445.50                         | 235.00                         | FRH19 |
| - 256 Kbps <sup>2</sup>     | 475.00              | 636.00         | 552.00                         | 286.00                         | FRH25 |
| - 320 Kbps <sup>2</sup>     | 475.00              | 714.00         | 630.00                         | 337.00                         | FRH32 |
| - 384 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH38 |
| - 448 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH44 |
| - 512 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH51 |
| - 576 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH57 |
| - 640 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH40 |
| - 704 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH70 |
| - 768 Kbps <sup>2</sup>     | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH76 |
| - 1024 Kbps <sup>2</sup>    | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH24 |
| - 1152 Kbps <sup>2</sup>    | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH52 |
| (d) at Subrate T1           |                     |                |                                |                                |       |
| - 128 Kbps <sup>3</sup>     | 550.00              | 352.50         | 321.00                         | 166.00                         | FRHS1 |
| - 256 Kbps <sup>3</sup>     | 550.00              | 414.00         | 384.00                         | 208.00                         | FRHS2 |
| - 384 Kbps <sup>3</sup>     | 550.00              | 532.50         | 508.50                         | 282.00                         | FRHS3 |
| - 512 Kbps <sup>3</sup>     | 550.00              | 621.00         | 579.00                         | 323.00                         | FRHS5 |
| - 768 Kbps <sup>3</sup>     | 550.00              | 693.00         | 651.00                         | 365.00                         | FRHS7 |
| - 1152 Kbps <sup>3</sup>    | 550.00              | 840.00         | 786.00                         | 448.00                         | FRHSE |
| (e) at 1.536 Mbps           | 550.00              | 900.00         | 837.00                         | 475.00                         | FRH15 |

**Note 1:** The Customer Connections at 56 Kbps and 64 Kbps are primarily utilized respectively with 56 Kbps and 64 Kbps transport facilities. They may alternately be utilized with a 1.536 Mbps transport facility and provisioned as a Fractional T1 service (as discussed in Note 2).

**Note 2:** Fractional T1 Customer Connection: This Customer Connection is provisioned in association with channelized 1.536 Mbps transport facilities. If requested with a 1.536 Mbps Broadband Line Service, only other Fast Packet Transport Services may utilize the remaining bandwidth of the transport; if provided in association with spare capacity on a channelized Private Line Service (e.g., channelized MegaLink Service), any other services may utilize the remaining bandwidth as allowed by the *Terms and Conditions* governing the transport service.

**Note 3:** Subrate T1 Customer Connection: This Customer Connection is provisioned as Subrate T1 service and may be referred to for marketing purposes as Flexible T1 Frame Relay Service. Each such Customer Connection requires the dedication to it of a full 1.536 Mbps of transport bandwidth (e.g., a full 1.536 Mbps Broadband Line Service); no other service(s) may utilize the remaining bandwidth.

**Note 4:** As of January 20, 2011, Term Payment Plan A payment periods greater than 24 months are no longer available for new or renewing subscribers.

**Note 5:** As of January 20, 2011, Term Payment Plan B payment periods are no longer available for new or renewing subscribers.

(T)



## A140. OBSOLETE SERVICE OFFERING-FAST PACKET TRANSPORT SERVICES

### A140.2 Reserved For Future Use

### A140.3 Native Mode LAN Interconnection (NMLI) Service

(Obsoleted 3/30/2004, Type B. Installation of new service is not allowed on or after obsolescence date.)

#### A140.3.1 General

- A. Native Mode LAN Interconnection (NMLI) service is a high-speed (10, 100 or 1000 Mbps) shared fiber optic transport service for the interconnection of customer-owned Local Area Networks (LANs) and other high-speed data devices.
- B. NMLI service provides a means of basic LAN extension for customer-owned Ethernet (IEEE Standard 802.3, 802.3u and 802.3z) LANs. A customer with multiple LANs in an area served by NMLI service may interconnect these LANs through NMLI service.
- C. The signals at the NMLI Port meet IEEE 802.3, 802.3u or 802.3z standards. Technical requirements for interfaces with customer premises equipment (CPE) are contained in ANSI/IEEE 802.3-1992, "Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications". These technical documents may be ordered from:  
American National Standards Institute  
11 West 42nd Street  
New York, New York 10036
- D. NMLI service is suitable for data transmission only.
- E. NMLI service, as provided under the provisions of this section, is offered for intraLATA use only.
- F. The **Terms, Conditions** and rates specified herein are in addition to the applicable **Terms, Conditions** and rates specified in other sections of this and other Guidebooks of the Company. (T)
- G. The rates and charges set forth for NMLI service provide for the furnishing of service where suitable facilities are available. Where special construction of facilities is necessary, special construction charges may apply as set forth in Section A5. (T)

#### A140.3.2 Terms and Conditions

- A. Explanation of Terms
  - 1. Customer End Bridge Management  
Customer End Bridge Management provides NMLI customers the ability to manage their Ethernet LANs by allowing them access to their end bridge devices in order to monitor and receive status reports of their network. Customer End Bridge Management is based on the Simple Network Management Protocol (SNMP), an Internet network management protocol, which is a widely accepted, message based protocol for the exchange of management information between a management station and managed devices.
  - 2. Ethernet LAN  
A type of Local Area Network (LAN). Ethernet is based on technology where a workstation on the LAN sends a message to another workstation on the LAN and "listens" to determine if any other station is sending. If another station begins sending at the same time, all stations back off and wait a pre-set delay before attempting to send again. Ethernet meets IEEE Standard 802.3. Ethernet LANs operate at 10 Mbps.
  - 3. Fast Ethernet LAN  
A type of Local Area Network (LAN). The same service functionality parameters for an Ethernet LAN apply for a Fast Ethernet LAN except it utilizes IEEE Standard 802.3u, 100 Base-FX, full duplex technology and it operates at 100 Mbps..
  - 4. Local Area Network (LAN)  
A data communications network spanning a limited geographical area, usually a few miles at most. A LAN connects computers and other peripheral equipment for data communications purposes within a building or campus.
  - 5. Native Mode of a Local Area Network (LAN)  
The operating speed of the communication on the originating LAN which is not changed through interworking with NMLI service or after interconnecting with the terminating LAN.

## **A140. OBSOLETE SERVICE OFFERINGS-FAST PACKET TRANSPORT SERVICES**

### **A140.3 Native Mode LAN Interconnection (NMLI) Service (Cont'd)**

#### **A140.3.2 Terms and Conditions (Cont'd)**

(T)

##### **A. Explanation of Terms (Cont'd)**

###### **6. NMLI Data Channel**

The customer's fiber optic transport. The Data Channel is charged in 1/2 mile increments and is measured from the customer premises to their Serving Wire Center and through all intermediate Wire Centers required to reach the NMLI Wire Center in airline miles. The NMLI Wire Center is the wire center containing the NMLI equipment that provides the NMLI service functionality for the premises associated with the Data Channel. The NMLI Data Channel is for use with either the Shared or Dedicated NMLI Service Arrangement as described herein.

###### **7. NMLI Port**

The equipment that interconnects the customer's LAN with NMLI service. There are two categories of NMLI Ports offered; (1) for interconnection of Shared NMLI Service arrangements, and (2) for interconnection of Dedicated NMLI Service arrangements. Within the Shared NMLI Service category, there are three types of Ports offered; (1) for interconnection of Ethernet LANs operating at 10 Mbps, (2) for interconnection of Fast Ethernet LANs operating at 100 Mbps, and (3) for interconnection of Gigabit Ethernet LANs operating at 1 Gbps. Within the Dedicated NMLI Service category, there are two types of Ports offered; (1) for interconnection of 100 Mbps Fast Ethernet LAN's or data devices operating at 100 Mbps, and (2) for interconnection of Gigabit Ethernet LAN's or data devices operating at 1 Gbps. The Port, whether associated with a Shared or Dedicated NMLI Service arrangement, is specific customer for addressing and security reasons.

###### **8. Shared NMLI Service Arrangement**

This service arrangement is where a NMLI Port is associated with a network capable of interconnecting with one or more other NMLI Port(s). This service arrangement is available for all NMLI transmission speeds.

###### **9. Dedicated NMLI Service Arrangement**

This service arrangement is where a NMLI Port is associated with a network capable of interconnecting with only one other NMLI Port. Both NMLI Ports and their associated Data Channels are served from the same NMLI Wire Center. This service arrangement is only available for 100 Mbps Fast Ethernet service and Gigabit Ethernet service.

###### **10. Gigabit Ethernet**

A LAN interconnection service being offered under the family on NMLI products for interconnection of LANs or other high-speed devices. This service uses the 802.3 specification procedures to operate a LAN at 1 Gbps. This is 100 times the 10 Mbps Ethernet clocking speed with the existing physical medium, producing a LAN at 1 Gbps.

##### **B. Basis of Offering**

###### **1. Suspension of service is not allowed.**

###### **2. NMLI service is available 24 hours per day, 7 days per week, except for preventive maintenance.**

###### **3. Due to the nature of NMLI service it will be necessary to perform preventive maintenance and software updates. This will mean that NMLI service will be unavailable during the period of time when preventive maintenance is being performed. This maintenance will be scheduled between 1:00AM and 5:00AM Eastern Time on any given Monday or Sunday morning.**

###### **4. Obligations of customer and Company**

a. The Company is not responsible for the installation, operation, or maintenance of any equipment provided by the customer.

b. The customer is responsible for the provision and maintenance of all customer provided equipment and to insure that the operating characteristics of this equipment is comparable with and does not interfere with the service offered by the Company.

c. At the Port the customer's signals must conform to IEEE Standards 802.3 or 802.3u. To meet end-to-end delay requirements contained in these aforementioned standards, the customer may be required to provide additional equipment.

d. Company provided shared network equipment, for use in NMLI service, is not accessible by the customer.

###### **5. The minimum service period for all NMLI service components is twelve months.**

(T)

###### **6. Customer End Bridge Management is available only to NMLI customers with Ethernet LANs. For addressing and security reasons, this option can only be used between ports within the same domain/security screen. This option provides customers access to their end bridge device in order to:**

(M)

a. Perform visibility tests on the end bridge to show connectivity between the main location and remote sites

(M)

b. Receive traps from the end bridge when error conditions occur

(M)

c. Obtain statistical information about the bridge and their LAN segments

(M)

## A140. OBSOLETE SERVICE OFFERINGS-FAST PACKET TRANSPORT SERVICES

### A140.3 Native Mode LAN Interconnection (NMLI) Service (Cont'd)

#### A140.3.2 Terms and Conditions (Cont'd)

- (T)  
(M1)
- C. Provision of Service
1. Rates and charges contained in this *Guidebook* consist of the following elements: (T)
    - a. NMLI Data Channel
    - b. NMLI Port
    - c. Address Reconfiguration
    - d. Customer End Bridge Management
  2. The Data Channel is available in 1/2 mile increments and is measured from the customer's location to the customer's Serving Wire Center and through all intermediate Wire Centers required to reach the NMLI Wire Center in airline miles. A minimum of one 1/2 mile increment is required.
  3. A minimum of two NMLI Ports are required per customer for full use of NMLI service.
  4. The Address Reconfiguration charge applies whenever a customer requests software modifications to a specific NMLI Port subsequent to the establishment of the Port.
  5. All service connection charges for NMLI service are included in the respective nonrecurring charges specified herein. Service Charges from Section A4 are not applicable. (T)
  6. Customer End Bridge Management is available as an optional feature at the following rates and charges for customers with Ethernet LANs:
    - a. A Nonrecurring and monthly rate will apply for the first one to four ports managed under this option. For each subsequent one to four ports, a separate monthly rate will apply only when the subsequent ports are established at the same time as the first ports. The first ports and the subsequent ports must be in the same domain/security screen.
- D. Contract Plans
1. Contract plans are available under conditions specified in the Fast Packet Services Payment Plan in A40.10 with contract periods described as follows. (T)
    - a. Term Payment Plan A - payment periods may be selected from 24 to 42 months.
    - b. Term Payment Plan B - payment periods may be selected from 43 to 60 months.
  2. Provided the applicable conditions set forth in A40.10.2 and A40.10.4.B are satisfied, a Termination Liability Charge will not be applicable at the date of termination if prior to fulfilling the period of the contract plan the customer requests a change to either Frame Relay Service, CDS, or ATM Service under a contract plan. Full nonrecurring charges will apply for the installation of the new service requested, except as specified in 3. (T)
  3. The nonrecurring charge for the installation of a NMLI Service Connection and all associated ports is not applicable for the customer requested change to convert an existing Connectionless Data Service (CDS) Customer Connection to a NMLI Service Connection.
- E. Moves
1. A move involves a change in the physical location of one of the following:
    - a. The point of interface at the customer premises.
    - b. The customer's premises.
  2. The charges for the move are dependent on whether the move is to a new location within the same building or to a different building. (M2)
    - a. Moves Within the Same Building (M2)
 

When the move is to a new location within the same building, the charge for the move will be an amount equal to one half the nonrecurring (i.e., installation) charge for the affected service termination at the customer's premises. There will be no change in the minimum period requirements. (M2)
    - b. To a Different Building (M2)
 

Moves to a different building, other than addressed in 3. will be treated as a disconnect at the existing location and all associated nonrecurring charges will apply at the new location. The customer will remain responsible for satisfying the remainder of the existing contract. (T)(M2)
  3. Moves of Service(s) under Fast Packet SPP (M2)
 

Customer requests for moves of service under Fast Packet SPP, other than inside moves, will be subject to the conditions stated in A40.10.11. (T)(M2)

M1 - Material previously appearing on this page now appears on page(s) 2 of this section.

M2 - Material appearing on this page previously appeared on page(s) 4 of this section.

**A140. OBSOLETE SERVICE OFFERINGS-FAST PACKET TRANSPORT SERVICES**  
**A140.3 Native Mode LAN Interconnection (NMLI) Service (Cont'd)**

(M1)

**A140.3.3 Rates and Charges**

**A. NMLI**

- 1. NMLI Data Channel  
 One Data Channel is required per NMLI Port. A minimum of 1/2 mile is required
  - (a) First 1/2 mile
  - (b) each additional 1/2 mile

| Nonrecurring Charge | Monthly Rate |  |  | USOC  |
|---------------------|--------------|--|--|-------|
| -                   | \$80.00      |  |  | NOMAX |
| -                   | 65.00        |  |  | NOMBX |

**B. NMLI Port – Shared NMLI Service Arrangement**

- 1. Ethernet at 10 Mbps
  - (a) per port
- 2. Fast Ethernet at 100 Mbps
  - (a) per port
- 3. Gigabit Ethernet at 1 Gbps
  - (a) per port

| Nonrecurring Charge | Month to Month | 24 to 42 Months | 43 to 60 Months |  |  | USOC  |
|---------------------|----------------|-----------------|-----------------|--|--|-------|
| \$1,000.00          | \$750.00       | \$725.00        | \$704.00        |  |  | NPPBX |
| 1,500.00            | 1,500.00       | 1,450.00        | 1,408.00        |  |  | NPP1X |
| 2,000.00            | 4,000.00       | 3,500.00        | 3,150.00        |  |  | NPPGP |

**C. NMLI Port – Dedicated NMLI Service Arrangement**

- 1. Fast Ethernet at 100 Mbps
  - (a) per port
- 2. Gigabit Ethernet at 1 Gbps
  - (a) per port

|          |          |          |          |  |  |       |
|----------|----------|----------|----------|--|--|-------|
| 1,725.00 | 2,000.00 | 1,950.00 | 1,900.00 |  |  | NPPP1 |
| 2,300.00 | 4,600.00 | 4,000.00 | 3,600.00 |  |  | NPPPG |

**D. Address Reconfiguration**

- 1. Subsequent to Port establishment
  - (a) per Software Modification per Port

|       |   |   |   |  |  |       |
|-------|---|---|---|--|--|-------|
| 75.00 | - | - | - |  |  | ARRAC |
|-------|---|---|---|--|--|-------|

**E. Customer End Bridge Management**

- 1. Ethernet Ports Managed -Service Establishment
  - (a) First 1-4 Ports
  - (b) Subsequent 1-4 Ports (coincident with first 1-4 Ports)<sup>1</sup>

|        |       |       |       |       |      |
|--------|-------|-------|-------|-------|------|
| 490.00 | 50.00 | 45.00 | 40.00 | NBE11 | (M2) |
| 370.00 | 50.00 | 45.00 | 40.00 | NBE1A | (M2) |

(T)(M2)

(M2)

(M2)

(M2)

**A140.4 Reserved for Future Use**

(M2)

**Note 1:** These rates apply only when the subsequent 1 - 4 ports are established at the same time as the first 1 - 4 ports.

(M2)

**Pages 5 and 6 are hereby deleted in their entirety and removed from this Guidebook.**

(N)

M1 - Material previously appearing on this page now appears on page(s) 3 of this section.  
 M2 - Material appearing on this page previously appeared on page(s) 5 of this section.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

**A140.5 Broadband Line Service**

**A140.5.1 General**

Except as specified in A140.5.2 and A140.5.3, terms and conditions located in A40.5 are applicable.

(T)

**A140.5.2 Terms and Conditions**

(Obsoleted 11/4/2002, Type D) Not available for new installations, moves or changes. Upon expiration of an existing contract, a 128 Kbps (2B1Q) Broadband Line Service can only be retained on a month-to-month payment plan basis.

(T)

An existing customer with a 128 Kbps (2B1Q) Broadband Line from A140.5 may request to convert to a 1.536 Mbps Broadband Line from A40.5 for use with their 128 Kbps Fractional T1 Frame Relay Service Customer Connection; the nonrecurring charges specified in A40.5 shall not apply for such conversions. Customers requesting to concurrently convert their 128 Kbps Fractional T1 Customer Connection to a 128 Kbps Subrate T1 Customer Connection shall not incur the Fractional T1 to Subrate T1 Change Charge from A140.1.3.A.3.

**A140.5.3 Rates and Charges**

**A. Rates and Charges for the Fast Packet Option**

**1. Broadband Line-FPO**

(a) 128 Kbps (2B1Q)

| Nonrecurring Charge | Month To  | A               | B               | USOC  |
|---------------------|-----------|-----------------|-----------------|-------|
|                     | Month     | 12 to 36 Months | 37 to 60 Months |       |
| \$ 540.00           | \$ 105.00 | \$ 92.00        | \$ 77.00        | FP112 |

**A140.6 Reserved For Future Use**

**A140.7 Reserved For Future Use**

---

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service

(Obsolated 9/19/2011, Type B - Not available for new installations, additions or on transfers of service to new location.)

#### A140.8.1 General

- A. Asynchronous Transfer Mode (ATM) Service (herein referred to as ATM Service) is a data transport service based on ATM cell-based switching technology.
- B. ATM Service provides flexible connectivity using virtual connections implemented over digital facilities operating at transmission speeds of 1.536 Mbps, 44.210 Mbps, 149.760 Mbps or 599.040 Mbps. This service provides for the switching of symmetrical duplex transmissions of fixed-length ATM cells, utilizing virtual circuits. To transfer information between at least two sites a virtual circuit must be set up across the ATM network. ATM service supports the establishment of both permanent virtual circuits (PVCs) and switched virtual circuits (SVCs).  
Information transmitted by ATM Service is segmented into fixed length cells, transported to and re-assembled at the specified destination. An ATM cell has a fixed length of 53 bytes. An ATM cell is broken into two main sections, the header and the payload. The payload is the portion which carries the actual information. The header is used for network functions such as addressing and error correction.
- C. Network interface specifications for ATM Service are contained in the following documents:
  - ATM Forum document, "ATM User-Network Interface Specification" (Versions 3.0 and 3.1 and UNI Version 4.0). This document may be obtained from:
    - ATM Forum
    - 2570 West El Camino Real
    - Suite 304
    - Mountain View, CA 94040
  - BellSouth Technical Reference 73585, "Asynchronous Transfer Mode (ATM) Network Interface and Performance Specifications". This document may be obtained from:
    - AT&T** Telecommunications, Inc. (T)
    - Regional Documentation Coordinator
    - 20th floor
    - 600 North 19th Street
    - Birmingham, AL 35203
- D. ATM Service, as provided for in this section, is offered for intraLATA use only.
- E. The **Terms, Conditions** and rates specified herein are in addition to the applicable **Terms, Conditions** and rates specified in other sections of this and other **service publications** of the Company. (T)
- F. The rates and charges set forth for ATM Service provide for the furnishing of service where suitable facilities are available.
- G. ATM Service is only available when provided in conjunction with Broadband Line Service. Specifications for Broadband Line Service are contained in A40.5.
- H. ATM Service PVCs may be interconnected with Frame Relay Service subject to the provisions set forth in A140.1.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions

(T)

##### A. Explanation of Terms

##### 1. Customer Connection to ATM Service

The Customer Connection provides the customer with the standard interface to the ATM Service network. This interface receives the data cells from the customer's network or device and verifies that the addressing and traffic parameters are valid before relaying the cell to the specified destination. Included in the Customer Connection rate element are the customer's termination on the ATM Service switching equipment and the transport from the Serving Area Point to the switching equipment (unless specified otherwise herein). These interfaces connect the ATM Service network with digital facilities operating at transmission speeds of 1.536 Mbps, 44.210 Mbps, 149.760 Mbps or 599.040 Mbps. Unless specifically stated otherwise herein, a customer may have both PVCs and SVCs on the same Customer Connection. Unique ATM Customer Connections operating at transmission speeds of 44.210 Mbps and 149.760 Mbps are available to provide Back-Up Capability as described in A40.8.2.A.22.

A Circuit Emulation Customer Connection is available for customer requirements to interwork existing DS1 level services utilizing time division multiplexing (TDM) across public ATM networks.

Customers with ATM Service requirements between 1.536 Mbps and 44.210 Mbps at a single premises may utilize either ATM Customer Connections using Inverse Multiplexing for ATM (IMA) or ATM Subrate T3 Customer Connections to economically serve that location. IMA Customer Connections provide the customer ATM Customer Connections at speeds of 3.072 Mbps, 4.608 Mbps, 6.144 Mbps, 7.680 Mbps, 9.216 Mbps, 10.752 Mbps, and 12.288 Mbps. ATM Subrate T3 Service provides ATM Customer Connections at speeds of 18 Mbps, 24 Mbps, 30 Mbps, and 36 Mbps.

##### 2. ATM Service Network Serving Area

Certain Company Central Offices are designated by the Company as Serving Area Points for the ATM Service Network Serving Area.

A customer accessing the ATM Service network, whose Serving Wire Center is designated a Serving Area Point, requires a Broadband Line-Fast Packet Option (FPO) as described in A40.5. An ATM Service customer, whose Serving Wire Center is not designated a Serving Area Point, will use a Broadband Line-FPO to the Serving Wire Center, as well as, the Broadband Line Extension - FPO (also described in A40.5) to gain access to the closest designated Serving Area Point.

##### 3. Permanent Virtual Circuit (PVC)

A PVC is a software defined data path transporting data within the ATM Service network between two ATM Customer Connections. This data path, once defined in the network software, does not have to be established again. PVCs are end-to-end, bi-directional channels that are established via the service provisioning process.

##### 4. PVC Service Categories

PVC service categories are established to support the service requirements of various categories of customer applications for ATM PVCs. Four PVC service categories are available. The customer must specify the desired service category for each PVC that is ordered. ATM Service supports the following types of PVC service categories:

- a. Constant Bit Rate (CBR): CBR allows for applications where a PVC requires special network timing requirements (i.e., strict PVC cell loss, cell delay and cell delay variation performance). For example, a CBR PVC would be utilized for applications requiring circuit emulation (i.e., a continuously operating logical channel) over ATM Service at transmission speeds comparable to DS1 and DS3. Such applications would include private line like service or voice type service where delays in transmission cannot be tolerated. The customer specifies the bandwidth required for each CBR PVC when it is ordered.
- b. Variable Bit Rate - Real Time (VBR-RT) : VBR-RT allows for applications where a PVC requires low cell delay variation. For example, VBR-RT would be utilized for applications such as variable bit rate video compression and packet voice and video which are somewhat tolerant of delay. The customer specifies the bandwidth required for each VBR-RT PVC when it is ordered.
- c. Variable Bit Rate - Non-Real Time (VBR-NRT): VBR-NRT allows for a PVC that can tolerate larger cell delay variations than VBR-RT. For example, VBR-NRT would be utilized for applications such as data file transfers. The customer specifies the bandwidth required for each VBR-NRT PVC when it is ordered.
- d. Unspecified Bit Rate (UBR): UBR allows for a PVC where the user does not require one of the PVC service categories described in a. through c. For example, UBR would be utilized where the customer seeks a low cost method of transporting bursty data for non-critical applications that can tolerate delay variations. The Company will attempt to deliver all ATM cells received via UBR PVCs; however, network congestion may result in loss of ATM cells.

(T)

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

(T)

##### A. Explanation of Terms (Cont'd)

##### 5. PVC Traffic Parameters

In accordance with the specifications for ATM Service set forth in the technical publications referenced in A140.8.1.C, each non-UBR type PVC has a set of traffic parameters to describe the characteristics of the information being transmitted. Fixed values for these traffic parameters are derived from the PVC bandwidth specified by the customer for each PVC. These parameters are:

- a. **Peak Cell Rate (PCR)** - The PCR, in cells per second, is an upper bound on the source traffic that can be submitted on an ATM Customer Connection. PCR is a traffic parameter considered for both CBR and VBR service categories. PCR is the only traffic parameter considered for a CBR PVC; the equivalent bandwidth per CBR PVC equals the PCR, in cells per second, times 0.000424.  
PCR is one of three traffic parameters considered for a VBR PVC. For a VBR-RT PVC, PCR is 200 percent of the SCR described following. For a VBR-NRT PVC, unless specified otherwise by the customer, PCR is 400 percent of the SCR described following.
- b. **Sustainable Cell Rate (SCR)** - The SCR, in cells per second, is an upper bound on the conforming average cell rate of an ATM Customer Connection over time.  
SCR is a traffic parameter considered only for a VBR PVC. The equivalent bandwidth per VBR-RT PVC is equal to the SCR, in cells per second, times 0.000512. The bandwidth per VBR-NRT PVC is equal to the SCR, in cells per second, times 0.000804.
- c. **Maximum Burst Size (MBS)** - MBS is the maximum number of consecutive cells that may be transmitted at the peak cell rate.  
MBS is a traffic parameter considered only for a VBR PVC. For a VBR-RT PVC, the MBS is fixed at 32 cells. For a VBR-NRT PVC, the MBS is fixed at 100 cells.

##### 6. PVC Segment

For ATM Service, the PVC segment defines the logical path between a customer's premises and the ATM Customer Connection on the ATM switch. An ATM PVC segment must be provisioned by the Company via service order activity and remain in place until requested to be removed by the customer. For ATM Service, two PVC segments are mapped together through the ATM switch to create a PVC representing a virtual channel through the ATM network. To allow one customer premises to communicate with another customer premises, two ATM Customer Connections and two PVC segments are required.

##### 7. PVC Segment Bandwidth

A PVC Segment Bandwidth Charge is applicable for each CBR or VBR PVC segment. Such non-UBR PVC equivalent bandwidth represents the ATM Service network resources based on the PVC's traffic parameters. The PVC Segment Bandwidth Charge is derived by multiplying the PVC segment's equivalent bandwidth (calculation following) by the appropriate PVC Segment Bandwidth Charge (expressed in megabits or increments of 64 Kbps as described following). The following calculations are applicable for determining non-UBR PVC segment bandwidth based upon the PVC service category.

- (a) CBR equivalent bandwidth is equal to the PCR (cells per second) times 0.000424. PCR is equal to increments of 64 Kbps of equivalent bandwidth times 150.943, or megabits of equivalent bandwidth times 2358.491.
- (b) VBR-RT equivalent bandwidth is equal to the SCR (cells per second) times 0.000512. For VBR-RT service, the PCR is fixed at 200 percent of the SCR and the MBS is fixed at 32 cells per second. SCR is equal to increments of 64 Kbps of equivalent bandwidth times 125.000, or megabits of equivalent bandwidth times 1953.125.
- (c) VBR-NRT equivalent bandwidth is equal to the SCR (cells per second) times 0.000804. For VBR-NRT service, the PCR is fixed at 400 percent of the SCR (unless specified otherwise by the customer)<sup>1</sup> and the MBS is fixed at 100 cells. SCR is equal to increments of 64 Kbps of equivalent bandwidth times 79.602, or megabits of equivalent bandwidth times 1243.781.

Where the result from the PVC segment equivalent bandwidth calculation is greater than 1.536 Mbps, the value is expressed in units of megabits and (if a fraction of a megabit) is rounded up to the next whole megabit. This bandwidth is multiplied by the Per Megabit Bandwidth Charge.

**Note 1:** VBR-NRT equivalent bandwidth, where the PCR to SCR ratio is specified by the customer, is determined using the formula in Section 1.3.4 of BellSouth Technical Reference 73585.



**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**  
**A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)**

**A140.8.2 Terms and Conditions (Cont'd)**

(T)

A. Explanation of Terms (Cont'd)

7. PVC Segment Bandwidth (Cont'd)

Where the result from the PVC segment equivalent bandwidth calculation is less than or equal to 1.536 Mbps, that number should be divided by .064 Mbps to arrive at a quantity of 64 Kbps increments. If the resulting number is not a whole number, it is rounded up to the next whole number and represents the number of 64 Kbps increments that should be utilized in the derivation of the PVC Segment Bandwidth Charge. This bandwidth is multiplied by the Per Increment of 64 Kbps Bandwidth Charge.

The following table illustrates the PVC segment equivalent bandwidth calculation for each non-UBR type PVC with one (1) megabit of bandwidth.

| ATM PVC Service Category | Equivalent Bandwidth | Traffic Parameters          |                                    |                                 |
|--------------------------|----------------------|-----------------------------|------------------------------------|---------------------------------|
|                          |                      | Peak Cell Rate <sup>1</sup> | Sustainable Cell Rate <sup>1</sup> | Maximum Burst Size <sup>2</sup> |
| CBR                      | 1 Megabit            | 2,358                       | N/A                                | N/A                             |
| VBR-RT                   | 1 Megabit            | 3,906                       | 1,953                              | 32                              |
| VBR-NRT                  | 1 Megabit            | 4,975                       | 1,244                              | 100                             |

8. Switched Virtual Circuit (SVC)

An SVC is a software defined data path within the ATM Service Network between two ATM Customer Connections that is not permanent, but established on demand by the customer when information transfer is needed and then taken down after the transmission is finished by the customer.

9. SVC Service Categories

SVC service categories are established to support the service requirements of various categories of customer applications for ATM SVCs. The same four service categories are available for SVCs as PVCs (i.e. CBR, VBR-RT, VBR-NRT and UBR). These service categories are described in A140.8.2.A.4.

10. SVC Traffic Parameters

In accordance with the specifications for ATM Service set forth in the technical publications referenced in A140.8.1.C, each non-UBR SVC has a set of traffic parameters to describe the characteristics of the information being transmitted. The traffic parameters are the same for SVCs as for PVCs; these parameters are described in A140.8.2.A.5.

11. SVC Bandwidth

SVC Bandwidth is selected by the customer to accommodate the total cumulative SVC bandwidth requirements for the maximum number of simultaneous SVC calls allowed on that Customer Connection. Per SVC bandwidth requirements are determined using the same parameters specified for PVC bandwidth requirements described in A140.8.2.A.7.

12. SVC Address

The Company assigns SVC addresses for each Customer Connection requested to transmit and/or receive SVCs. The customer provisions these addresses in his customer premises equipment (CPE). The data path for an SVC is then established on demand via the customer's CPE issuing a call setup request to the ATM switch. The setup request contains the addresses of the two ATM Customer Connections to be connected and SVC traffic contract information. This information allows the ATM switch to establish the end-to-end, bi-directional virtual circuit between the specified addresses with the appropriate bandwidth and service quality information necessary to support the customer's application. The SVC is disconnected when the customer's CPE signals a release to the ATM switch.

**Note 1:** Cells per second.

**Note 2:** Cells.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

(T)

##### A. Explanation of Terms (Cont'd)

##### 13. SVC Traffic Contract Information

Traffic contract information provided by the customer's CPE within each SVC setup consists of four major components: the SVC Service Category, the SVC Connection Traffic Descriptor, the SVC Conformance Definition and SVC Compliant Connection Definition.

##### - SVC Service Category:

Service categories for SVCs are the same as described for PVC's in A140.8.2.A.4 (CBR, VBR-RT, VBR-NRT and UBR).

##### - SVC Connection Traffic Descriptor:

This data identifies the rates of cell traffic to be expected with that SVC, i.e., the SVC traffic parameters are sustainable cell rate, peak cell rate and maximum burst size. The determination of SVC traffic parameters is identical to the determination of PVC traffic parameters as described in A140.8.2.A.5.

##### - SVC Conformance Definition:

This data identifies how the ATM network manages the user traffic to ensure that this SVCs traffic parameters are not exceeded.

##### - SVC Compliant Connection Definition:

This data determines the degree of tolerance that is afforded to a given SVC's non-conformity before it is considered non-compliant.

##### 14. SVC Bundles

ATM SVCs are offered in bundles of 5 SVCs as a rate element. For each bundle of 5 SVCs, a customer may have 5 simultaneous SVC calls. The customer determines the total maximum number of simultaneous SVC calls that will be required over his Customer Connection and selects the number of bundles which will meet this need.

##### 15. SVC Point-to-Point and Point-to-Multipoint Capability

SVCs can be either point-to-point or point-to-multipoint connections.

##### - A point-to-point SVC connects two ATM SVC addresses and is bi-directional.

- A point-to-multipoint SVC connects a single originating SVC address to multiple destination SVC addresses and is unidirectional (permitting only the originating SVC address to transmit and the destination SVC addresses to receive). The originating SVC address specifies the destination addresses for each specific SVC connection. All cell replication is done within the ATM Service network. The customer's CPE must be capable of initiating point-to-multipoint connections.

##### 16. SVC Closed User Group (CUG)

A SVC Closed User Group (CUG) may be established by an ATM customer in association with Customer Connections capable of transmitting SVCs. A CUG will restrict the requested SVC addresses to communicate with only the other ATM SVC addresses identified within its CUG; this precludes any SVC address to transmit or receive SVCs to/from any other SVC address not identified as a part of the CUG. An individual Customer Connection equipped for SVCs may be a part of more than one CUG.

##### 17. ATM Circuit Emulation Service

ATM Circuit Emulation Service allows the interworking of ATM Service with time division multiplexing (TDM) services at a DS1 level. ATM Circuit Emulation allows the encapsulation of DS1 level TDM Service into ATM cells by using AAL1 adaptation. Adaptation defines how higher layer information such as voice, data and video are placed in the payload of the 53-byte ATM cells. ATM Circuit Emulation Service is provided to emulate a structured or unstructured DS1 service; when provided to emulate a structured DS1, service may be requested with or without Channel Associated Signaling (CAS).

##### 18. ATM Customer Connection Using Inverse Multiplexing for ATM Service (IMA)

A customer requiring more ATM bandwidth than 1.536 Mbps but less than 44.210 Mbps, can economically utilize IMA to achieve ATM speeds in multiples of 1.536 Mbps and thereby avoid subscribing to a 44.210 Mbps Customer Connection. IMA is a physical layer technology in which a high-speed cell stream is broken down and transported across multiple 1.536 Mbps links, then reconstructed back into the original stream at the ATM switch or other associated ATM equipment. IMA Customer Connections are available at speeds in multiples of 1.536 Mbps (in multiples from 2 through 8) which results in ATM Customer Connections of 3.072 Mbps, 4.608 Mbps, 6.144 Mbps, 7.680 Mbps, 9.216 Mbps, 10.752 Mbps, and 12.288 Mbps.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**  
**A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)**

**A140.8.2 Terms and Conditions (Cont'd)**

**A. Explanation of Terms (Cont'd)**

**19. Feature Change Charge**

A Feature Change Charge is a nonrecurring charge which applies whenever a change is made (at the customer's request) to add or change ATM service as specified in A140.8.2.C.1.e.

**20. Serving Area Point (SAP)**

A Serving Area Point (SAP) is a Company Central Office that is designated as a member of the ATM Service Network Serving Area (see the explanation of ATM Service Network Serving Area, preceding).

**21. Oversubscription**

A customer may establish multiple virtual circuits (VCs, which are PVCs and/or SVCs) on an ATM Service Customer Connection.<sup>1</sup> VCs with a VBR service category are eligible to subscribe to more than the available equivalent bandwidth on the Customer Connection after bandwidth for CBR is assigned. This is called oversubscription. This allows the customer to take advantage of the fact that not all of these VCs will be active simultaneously. However, the network's apparent performance will be degraded if the customer attempts to make use of this overbooked commitment (or oversubscription) beyond the capacity of the ATM Service Customer Connection. In the worst case, attempts to fully utilize such overbooked commitment may appear to the customer as network unavailability.

The amount of oversubscription (expressed as a percentage) for a Customer Connection will be determined by:

$$\frac{\text{Sum of VBR equivalent bandwidths}}{\text{Customer Connection speed} - \text{sum of CBR equivalent bandwidths}} \text{ times } 100$$

In order to qualify for Network Service Level Agreements (SLAs) (as specified in B.6.), an ATM service Customer Connection may only oversubscribe PVC VBR bandwidth up to 200% according to the specific formula below, which also seeks to exclude SVC bandwidth from the total available bandwidth. In the event the customer exceeds this oversubscription limit, Network SLA credits will not be issued. The customer then must either upgrade their ATM Service Customer Connection speed or subscribe to an additional Customer Connection(s) to remain less than or equal to the 200% oversubscription limit to qualify for future Network SLA crediting.

$$\frac{\text{Sum of PVC VBR equivalent bandwidths}}{\text{Customer Connection speed} - \text{SVC bandwidth} - \text{sum of CBR equivalent bandwidths}} \text{ times } 100$$

**Note 1:** The maximum VBR oversubscription allowed on a Subrate T3 Customer Connection (any speed) is 200%.

(T)

(M)

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

##### A. Explanation of Terms (Cont'd)

##### 22. Back-Up Capability

Back-Up Capability is available on an optional basis (via unique Back-Up Customer Connections with transmission speeds of either 44.210 Mbps or 149.760 Mbps) and provides the customer with the ability to have a back-up logical port configured to his PVC service needs in the event that the customer's primary connection at 44.210 Mbps or 149.760 Mbps is disabled. A Back-Up Customer Connection utilizes a Broadband Line (with Broadband Line Extension Service, as appropriate). Both the Back-Up Customer Connection and its associated Broadband Line Service are specifically dedicated to providing back-up service and remain idle except when being utilized for back-up purposes.

The customer must prearrange with the Company which primary Customer Connection(s) may be directed to a specific Back-Up Customer Connection so that the necessary work is done by the Company which is required prior to back-up capability being possible. An ATM Customer Connection so identified which may be redirected in the event of a failure is referred to as a back-up enabled primary Customer Connection, or referred to herein as simply the primary Customer Connection. An ATM primary Customer Connection may only utilize an ATM Back-Up Customer Connection. A primary Customer Connection must be in the same ATM Network Serving Area as its Back-Up Customer Connection. A primary Customer Connection may have only one Back-Up Customer Connection identified. A Back-Up Customer Connection may serve as the back-up for more than one primary Customer Connection; however, a Back-Up Customer Connection may only be actively in use with one primary Customer Connection at any given time. The Back-Up Customer Connection must be the same size as the customer's largest primary Customer Connection.

The Back-Up Customer Connection is manually activated by the Company when the customer requests service from a primary Customer Connection to be redirected to its pre-identified Back-Up Customer Connection. All PVCs associated with the primary Customer Connection are rerouted to the Back-Up Customer Connection<sup>1</sup>. As a technical limitation, Back-Up Capability does not function in association with SVCs; if a primary Customer Connection with both PVCs and SVCs is redirected to its Back-Up Customer Connection, only the PVCs will be redirected and operational.

A Back-Up Customer Connection is not eligible for Network Service Level Agreements (SLAs) specified in B.6.

##### B. Basis of Offering

1. Detailed monthly billing is not provided.
2. Suspension of service is not allowed.
3. Obligations of Customer and Company
  - a. The Company is not responsible for the installation, operation, or maintenance of any equipment provided by the customer.
  - b. The customer is responsible for the provision and maintenance of all Customer Provided Equipment (CPE) and to ensure that the operating characteristics of this equipment are compatible with and do not interfere with the service offered by the Company.
  - c. The maximum number of virtual channels (PVC segments plus simultaneous SVCs) allowed per Customer Connection are specified in BellSouth Technical Reference 73585.
4. In order to maintain the quality of ATM Service, the Company reserves the right to perform preventive maintenance and software updates to the network. This could result in ATM Service being unavailable during the time period between 2:00 A.M. and 4:00 A.M. Eastern Time on any given Monday or Sunday morning. However, the Company expects only to utilize this maintenance window for any given switch on the average of once a quarter. In addition, the Company will make every reasonable effort to provide advance notice to those customers likely to be severely affected by such maintenance work. This maintenance window may be adjusted by the Company upon written notice to the customer.
5. The minimum service period is 12 months.

**Note 1:** To appropriately provision new PVCs ordered subsequent to a primary Customer Connection being enabled for Back-Up Capability, subsequent orders for PVCs should specify that the PVCs are being requested in association with a primary Customer Connection.

(T)

(T)

(M)

## **A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

### **A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)**

#### **A140.8.2 Terms and Conditions (Cont'd)**

##### **B. Basis of Offering (Cont'd)**

##### **6. Service Level Agreement**

ATM Service includes Service Level Agreements (SLAs) which specify the Company's provisioning, repair and performance commitments for ATM Service in specific areas. Provisioning and repair commitments are measured on a per occurrence basis. Network service level commitments are monthly performance measurements. The following service measurements will outline the service levels that the Company will deliver to its ATM customers.

Provisioning and Repair:

- ATM Installation Interval
- ATM Time-To-Repair

Network Service Levels:

- ATM Network Availability
- ATM Cell Loss Ratio
- ATM Cell Delivery Rate

Service Level Commitments will define ATM Service measurements that the Company agrees to provide every customer. If the Company fails to meet a Service Level Commitment, the customer is eligible for a SLA credit. Credits for missed Network Service Level Commitments will only be available to customers subscribing to the Gold Package in Customer Network Management from A140.12. Billing credits which may apply if the Company does not meet the objectives associated with these stated SLAs (specifically covering rates for ATM Service and associated Broadband Line Service from Section A40) are provided as set forth in c. Credits only apply for portions of service supplied by the Company.

##### **a. SLA Service Level Commitments**

The Company's Service Level Commitments for ATM Service are as follows:

- ATM Installation Interval - Standard Interval
- ATM Time-To-Repair on customer sites within the ATM Network Serving Area - 4 hours
- ATM Network Availability on a customer's network within the ATM Network Serving Area – 99.9%
- ATM Cell Loss Ratio – 1%
- ATM Cell Delivery Rate with CBR Class of Service – 99.99%
- ATM Cell Delivery Rate with VBR real-time Class of Service – 99.9%
- ATM Cell Delivery Rate with VBR non real-time Class of Service – 99.5%

##### **b. SLA Restrictions**

The Company will implement SLA provisioning restrictions that will define customer network design requirements and limitations to the Company's commitment to meet Service Levels for ATM Service. Customer network design requirements are intended to limit or negate the Company's obligation to provide SLA credits when the customer has under-engineered their ATM network. The customer network design requirements are as follows:

- The customer's network must have a minimum of 10 customer connections for the Company to provide SLA credits.
- The total VBR equivalent bandwidth on all PVCs (after the CBR bandwidth is subtracted) carried by any of the customer's ATM Customer Connections may not be greater than 200% of the Customer Connection speed (oversubscription).
- A customer must be subscribing to the Gold Package in Customer Network Management (CNM) from A140.12 to receive credits for missed Network Service Level Commitments. Customer Connections at both ends of a PVC must have the CNM Gold Package or equivalent. In the event only one end of a PVC is ordered from this Guidebook, credits will only be issued for the rate elements ordered from this Guidebook.

(T)

(T)

---

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 *Terms and Conditions* (Cont'd)

**B.** Basis of Offering (Cont'd)

6. Service Level Agreement (Cont'd)

b. SLA Restrictions (Cont'd)

SLA credits do not apply when any stated objective is not met because the Company does not have control over the circumstances causing the objective to be missed. Situations over which the Company does not have control can be defined as, but not limited to, the following:

- any act, any omission or negligence on the part of the customer, any other customer or any third party, or of any other entity providing a portion of the service,
- labor difficulties, governmental orders, civil commotions, declared National Emergencies, criminal actions against the Company, acts of God, war, or other circumstances beyond the Company's control,
- the customer's premises equipment,
- unavailability of the customer's facilities and/or equipment, and
- customer oversubscription of ATM Service Customer Connections.

SLA commitments only apply for service wholly within Company territory. SLA commitments will not apply for circuits which are part of a jointly provided service. SLA commitments do not apply for service provided by other telephone companies concurring in the rates, *Terms and Conditions* of the Company.

The customer must request a credit within one calendar month of the Company missing an ATM Service Level Commitment. The Company will investigate customer requests for any SLA credits to determine the cause of any performance failures reported by the customer. The Company will investigate the customer's request over a period of up to 45 calendar days. The 45-day period will begin when the customer makes the request for credit with their Sales Representative. SLA credits will be provided to the customer if the Company determines that they had control over the circumstances causing the failure. If the Company determines that these failures are the result of oversubscription of ATM Service Customer Connections, the Company will provide the customer with the reports documenting the oversubscription and Network SLA credits will not be issued. The customer will be required to upgrade their ATM Service Customer Connections or no future SLA credits will be allowed on that ATM Service Customer Connection(s).

When a customer requests a SLA credit for ATM Network Availability, all requests for a calendar month must be submitted at the same time. For example, the customer receives a SLA report on May 1, providing a report on April performance. Any requests for Network Availability SLA credits on Customer Connections for the month of April must all be submitted together.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd) (T)

##### B. Basis of Offering (Cont'd)

##### 6. Service Level Agreement (Cont'd)

##### c. SLA Credits for ATM Service Level Commitments (T)

The following credits will apply when the Company misses a Service Level Commitment (each credit is described in (1) thru (5)): (T)(M)

- ATM Installation Interval – Credit non-recurring installation charge paid by the customer (M)
- ATM Time-To-Repair – Credit one day of Monthly Recurring Charge (MRC) (M)
- ATM Network Availability – Credit one day of MRC (M)
- ATM Cell Loss Ratio – Credit MRC (M)
- ATM Cell Delivery Rate – Credit MRC (M)

The SLA credit amount will be determined by applying the credits outlined above to the rate elements or total billed revenues specified following.

- (1) ATM Installation Interval Credit - this credit will only apply to the installation or upgrade of an ATM Customer Connection. The credit will be equal to the nonrecurring installation charge for the Customer Connection, Broadband Line and Broadband Line Extension. The credit will not apply to expedited installations or to installations where no facility and/or switch exist. If on the due date the customer is not ready or in a case where another of the customer's service providers (including the customer's provider of customer premises equipment, interexchange service, or other local service provider) is not ready, the Company is not liable for missing the due date and SLA credits do not apply.
- (2) ATM Time-To-Repair Credit - this credit will require that the customer report the problem to the *Company's* Repair Center. The repair interval will start with the time entered on the trouble ticket. The Service Level Commitment measurement will be based on each individual trouble ticket for a Customer Connection. Multiple trouble tickets on the same day for the same Customer Connection will only be eligible for one time-to-repair credit. The credit will be one day of the MRC for the Customer Connection and Broadband Line. Credits on any individual Customer Connection for a calendar month cannot exceed the MRC for the Customer Connection and Broadband Line. (T)
- (3) ATM Network Availability – this credit will apply in the event that the measurement for the customer's network is missed. The credit will then be for each ATM Customer Connection which does not meet the 99.9% availability commitment. The credit will be one day of the MRC of the ATM Customer Connection and the Broadband Line. The unavailability of a Customer Connection will be calculated from the trouble tickets submitted for the Customer Connection. The unavailability of a customer's network will be calculated from the trouble tickets submitted for each Customer Connection within the customer's network. The Service Level Commitment will be calculated by first subtracting the unavailable time from the total available time for a particular calendar month and then dividing it by the total available time. Included in available time are scheduled maintenance windows and time the network was unavailable due to circumstances outside the Company's control.
- (4) ATM Cell Loss Ratio - measurement will be on each ATM PVC. The credit will be equal to the MRC for the PVC Segment Charge of the VPI/VCI pair making up the PVC.
- (5) ATM Cell Delivery Rate - measurement will be on each ATM PVC. The credit will be equal to the MRC for the PVC Segment Charge of the VPI/VCI pair making up the PVC.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

(T)

##### C. Provision of Service

##### 1. Rates and charges contained in this Section consist of the following elements:

##### a. Customer Connection to ATM Service

- (1) The ATM Customer Connection rate element includes the termination on the ATM switching equipment and the transport from ATM Serving Area Points to that switch (unless specified otherwise herein). A minimum of one Customer Connection is required per customer to subscribe to ATM Service.

Rates for the following ATM Customer Connections at speeds of 1.536 Mbps, IMA, Subrate T3 and 44.210 Mbps are flat rated based upon the average airline distance of ATM Serving Area Points from the ATM switch within a Network Serving Area: 1.536 Mbps (including Circuit Emulation<sup>1</sup>), 3.072 Mbps, 4.608 Mbps, 6.144 Mbps, 7.680 Mbps, 9.216 Mbps, 10.752 Mbps, 12.288 Mbps, 18 Mbps, 24 Mbps, 30 Mbps, 36 Mbps and 44.210 Mbps.

Rates for an ATM Customer Connection at speeds of 149.760 Mbps and 599.040 Mbps may include two components. A fixed charge applies per 149.760 Mbps or 599.040 Mbps ATM Customer Connection. In addition, a Per Mile Charge applies if the ATM switch is not located in the customer's Serving Wire Center. Airline distance will be calculated from the customer's Serving Area Point to the Company Central Office where the ATM switch is located within that Network Serving Area. Fractions of miles will be rounded up to the nearest whole mile.

- (2) The unique Back-Up Customer Connection rate elements provided at 44.210 Mbps and 149.760 Mbps are structured the same as standard ATM Customer Connections for those same transmission speeds as described in paragraph (1).

##### b. PVC Feature Charges

PVC Feature Charges are required to establish PVC connections across the ATM network.

- (1) PVC Segment Charge - A PVC Segment Charge applies for each PVC segment established over a Customer Connection. A PVC Segment Charge is applicable under all ATM PVC service categories.
- (2) PVC Segment Bandwidth Charge - A PVC Segment Bandwidth Charge is required per PVC segment established under the CBR or VBR PVC service category (but is not applicable to UBR PVCs). PVC bandwidth represents ATM Service network resources required for the non-UBR PVC and is based on the non-UBR PVC's traffic parameters (i.e., PCR, SCR, and MBS). The total charge for this rate element per segment is determined by multiplying the non-UBR PVC segment bandwidth by the PVC Segment Bandwidth Charge, either Per Megabit or Per Increment of 64 Kbps (as appropriate per A140.8.2.A.7.).
- (3) UBR Service Activation Charge - A UBR Service Activation Charge is applicable for each Customer Connection over which UBR PVCs will traverse. One charge is applicable per Customer Connection regardless of how many UBR PVCs will traverse that Customer Connection.

##### c. Inter-Network Serving Area Link PVC Feature Charges (Refer to A140.8.2.C.4.b.)

**Note 1:** The Unstructured Circuit Emulation – PRI over ATM Customer Connection is flat rated; however, specific charges apply as set forth in A140.8.2.C.7.a. (1) for mileage between the ATM switch providing circuit emulation capability and the Primary Rate ISDN switch.



## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

(T)

##### C. Provision of Service (Cont'd)

##### 1. Rates and Charges contained in this Section consist of the following elements: (Cont'd)

##### d. SVC Feature Charges

SVC Feature Charges are required to enable Customer Connections to establish SVC connections across the ATM network.

- (1) SVC Service Activation Charge - The SVC Service Activation Charge applies per Customer Connection, which is requested to be enabled to transmit and/or receive SVCs.
- (2) SVC Bundles - For each Customer Connection activated for SVCs, the customer must determine the maximum number of simultaneous SVC calls that Customer Connection should be sized to accommodate. The rate element for an SVC Bundle provides the capability for up to 5 simultaneous SVC calls. The customer determines how many bundles, or increments of 5 simultaneous SVC calls, are required for each Customer Connection. Where less than 5 simultaneous SVC calls are required, the customer is required to purchase a minimum of one bundle.

- (3) SVC Bandwidth - For each Customer Connection activated for SVCs, the customer must determine the bandwidth required to accommodate the total volume of simultaneous SVC calls, or total number of SVC bundles, selected for each Customer Connection. Bandwidth represents the ATM Service network resources that will be utilized for that Customer Connection based upon its total SVCs' traffic parameters.

Where the bandwidth required per Customer Connection activated for SVCs is greater than 1.536 Mbps, the SVC bandwidth value is expressed in units of megabits and (if a fraction of a megabit) is rounded up to the next whole megabit. This bandwidth is multiplied by the SVC Per Megabit Bandwidth Charge.

Where the bandwidth required per Customer Connection activated for SVCs is less than or equal to 1.536 Mbps, that number should be divided by .064 Mbps to arrive at a quantity of 64 Kbps increments. If the resulting number is not a whole number, it is rounded up to the next whole number and represents the number of 64 Kbps increments that should be utilized in the derivation of the SVC Bandwidth Charge. This bandwidth is multiplied by the SVC Per Increment of 64 Kbps Bandwidth Charge.

(M)

- (4) SVC Closed User Group (CUG)

Nonrecurring charges apply for each customer requested CUG.

(M)

A Per Group nonrecurring charge applies per CUG at the time of initial establishment of that CUG. A Feature Change Charge is applicable for each subsequent request to change the parameters of an existing CUG; the Per Group nonrecurring charge is not applicable for such requests.

(M)

A Per Entry nonrecurring charge applies per SVC Address (on an ATM SVC Customer Connection enabled for SVC capability) which is requested by the customer to be included in a CUG. The Per Entry nonrecurring charge applies for each SVC Address requested to be included in a CUG at the time the CUG is established. The Per Entry nonrecurring charge also applies for each SVC Address requested to be included in an already established CUG.<sup>1</sup>

(M)

Customer requests to change an SVC Address from being included in one CUG to another CUG shall be treated as a disconnect from the CUG the SVC Address is deleted from (at no charge) and as a new entry to the other CUG (where a Per Entry nonrecurring charge shall be applicable.<sup>1</sup>)

(M)

**Note 1:** The application of a Feature Change Charge is not required for such requests.

(M)

## A140. FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

##### C. Provision of Service (Cont'd)

1. Rates and Charges contained in this Section consist of the following elements: (Cont'd)

- e. Feature Change Charge

A Feature Change Charge applies for a customer request to change an existing ATM Service PVC feature from A140.8.3.B and C for which there is no nonrecurring charge. One Feature Change Charge applies per service order to perform the work requested by the customer. (Examples: A Feature Change Charge applies when a customer requests a change in the PVC segment bandwidth required on an existing non-UBR PVC. A Feature Change Charge applies when a customer requests that UBR Service Activation be added to an existing ATM Customer Connection which currently is not activated to carry UBR PVCs if the request does not also include an order for a UBR PVC Segment which carries a nonrecurring charge. A customer request to change the service category of an existing CBR PVC to a VBR-RT PVC would not involve a Feature Change Charge but would be treated as a disconnect of the CBR PVC and a new request for a VBR-RT PVC for which there is a nonrecurring charge.)

Only one Feature Change Charge applies per customer request that involves changes to multiple existing PVCs of the same PVC service category that are provisioned out of the same ATM switch. (For example, one Feature Change Charge would apply per customer request to change the PVC segment bandwidth associated with two existing CBR PVCs provisioned out of the same ATM switch.)

A Feature Change Charge applies for a customer request to increase or decrease the quantity of SVC Bundles<sup>1</sup> and/or SVC Bandwidth associated with an existing ATM Customer Connection equipped with SVCs. One Feature Change Charge applies per service order required to perform the work requested by the customer.

A Feature Change Charge applies for a customer request to change the parameters on an existing SVC CUG.

2. Certain Company Central Offices are designated by the Company as Serving Area Points (SAPs) for the ATM Service Network Serving Area. A customer accessing the ATM Service network, whose Serving Wire Center is designated a SAP, will only require a Broadband Line-FPO as described in A40.5. An ATM Service customer, whose Serving Wire Center is not designated a SAP, will require a Broadband Line-FPO to the Serving Wire Center as well as a Broadband Line Extension - FPO (also described in A40.5) to gain access to the closest designated SAP.
  3. Charges for installing ATM Service are included in the respective nonrecurring charges specified herein. Service Charges from A4 are not applicable for installing such services. Charges applicable for customer requested change of service installation due date and cancellation of service installation are as specified in A40.9.

**Note 1:** The nonrecurring charge per SVC Bundle applies for each additional SVC Bundle requested.

---

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

##### C. Provision of Service (Cont'd)

4. Should a customer, having locations in more than one Company ATM Network Serving Area within a LATA, desire to send PVC data traffic between these locations, the customer can interconnect these locations through the following two options:
  - a. **Dedicated Connection:**  
The customer subscribes to additional Customer Connections (in each Network Serving Area) which are enabled to support inter-serving area connectivity and Broadband Line Extension - FPOs to connect them. These additional rate elements will be used solely to transport this customer's data traffic between affected ATM Network Serving Areas. PVC and SVC Feature Charges apply for VCs through each connection except when these connections have been specifically requested by the customer to be provisioned as customer specific trunks.
  - b. **Shared Connection:**  
The Company may establish facilities between ATM Service switching equipment in different Network Serving Areas in the same LATA and may allow customers to share bandwidth on these facilities; where these shared facilities are available to customers, a shared connection is an option. The customer must establish one or more Inter-Network Serving Area Links (INSAL) that extend between ATM switches.
    - (1) Where the customer wishes to extend PVC Service, one PVC exists between both customer premises through each link. Charges for the PVC Inter-Network Serving Area Link are applied as follows:
      - the PVC Inter-Network Serving Area Link Establishment is charged at each end of the link per PVC,
      - for CBR or VBR PVCs, the appropriate PVC Inter-Network Serving Area Link PVC Bandwidth Charge is applicable for each end of the link per PVC; for UBR PVCs, an Inter-Network Serving Area UBR PVC Service Activation Charge applies per PVC for each end of the link, and
      - no additional PVC Segment Charges apply.
5. In some cases, the Company and another Incumbent Local Exchange Company that offers ATM technology will jointly connect ATM switching equipment within a LATA to provide customers the ability to interconnect their locations served by the different companies. In order to utilize the Company's portion of this jointly provided shared connection for PVC traffic, the customer must subscribe to one end of a PVC Inter-Network Serving Area Link with either an Inter-Network Serving Area Link PVC Bandwidth Charge (per CBR or VBR PVC) or a PVC Inter-Network Serving Area Link UBR Service Activation Charge (per UBR PVC).
6. For customer locations within Company LATAs served by an Incumbent Local Exchange Carrier other than the Company, the appropriate ATM Customer Connection charge for mileage associated with transmission speeds of 149.760 Mbps and 599.040 Mbps will be determined by using the airline distance from the switch location to the Company central office within the ATM Network Serving Area which is the closest designated SAP.

**Note 1:** The mileage utilized to determine the Broadband Line Extension associated with a Dedicated Connection at speeds equal to or less than 44.210 Mbps is measured from Serving Area Point to Serving Area Point between the two involved Network Serving Areas. The mileage utilized to determine the Broadband Line Extension associated with a Dedicated Connection at speeds of 149.760 Mbps or 599.040 Mbps is measured between the serving wire centers in each Network Serving Area where the ATM switches are located.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

##### C. Provision of Service (Cont'd)

7. Circuit Emulation Service provides for the emulation of a time division multiplexed (TDM) DS1 circuit through the ATM network so that the customer may interwork TDM services with their ATM Service. The customer is responsible for the appropriate charges for such TDM services from other service publications in addition to the charges specified herein for ATM Service. (M1)

An Unstructured versus Structured Circuit Emulation Customer Connection is selected based upon the customer's specific DS1 needs to respectively interwork an unstructured versus structured DS1 TDM service with ATM Service. (M1)

- a. An Unstructured Circuit Emulation Customer Connection accepts the termination of a full DS1 TDM bit stream.

- (1) A unique Unstructured Circuit Emulation Customer Connection is provided to accept the termination of a full DS1 TDM bit stream from a Primary Rate ISDN Service. One Unstructured Circuit Emulation Customer Connection - PRI over ATM rate element is required per Primary Rate ISDN Interface. One ATM CBR PVC Segment with 2 Megabits of CBR PVC Segment Bandwidth shall apply in association with the service originating from each Primary Rate ISDN Interface to the ATM Switch. (Additionally, the standard charges apply for the corresponding 2 Megabit ATM CBR PVC Segment to which this is mapped within the ATM switch, which is requested on the ATM Customer Connection associated with the customer's premises.) (T)

Appropriate rate elements for the Primary Rate ISDN Service when so terminated in ATM Service are as set forth in A42.3. Only Primary Rate ISDN Service provided from a central office which is a Serving Area Point within the same ATM Service Network Serving Area as the customer premises to which the service is to be transported may utilize this option. If the ATM switch used to provide the circuit emulation capability for the Primary Rate ISDN Service is not in the same central office as the Primary Rate ISDN switch, interoffice mileage charges from the Primary Rate ISDN Service *guidebook* shall apply between these two switch central offices. (T)

The ATM Customer Connection (associated with the customer premises) to which the PVC segment associated with the Unstructured Circuit Emulation Customer Connection - PRI over ATM may be mapped must be a transmission speed of Subrate T3 or higher in order to accept the 2 Megabit CBR PVC associated with this service.

The PVC Segment associated with the Unstructured Circuit Emulation Customer Connection - PRI over ATM may only be mapped to a PVC Segment associated with a local ATM Service Customer Connection whose service terminates to a premises within the same LATA as the Primary Rate ISDN Service switch. The provision of the Primary Rate ISDN Service (via the Unstructured Circuit Emulation Customer Connection - PRI over ATM) to the premises associated with the local ATM Service Customer Connection must be in accordance with all *Terms and Conditions* governing the provisioning of local exchange service via Primary Rate ISDN Service. (T)

- (2) An Unstructured Circuit Emulation Customer Connection is provided to accept the termination of a full DS1 TDM bit stream from the customer's premises through a 1.536 Mbps Broadband Line Service. One Unstructured Circuit Emulation Customer Connection - Other TDM over ATM is required per such DS1 TDM service. One ATM CBR PVC Segment with 2 Megabits of CBR PVC Segment Bandwidth shall apply in association with the service originating from the TDM premises to the ATM Switch. Additionally, the standard charges apply for the corresponding 2 Megabit ATM CBR PVC Segment to which this is mapped within the ATM switch; the associated ATM Customer Connection must be a transmission speed or type which can accept the 2 Megabit CBR PVC.

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)

#### A140.8.2 Terms and Conditions (Cont'd)

(T)

##### C. Provision of Service (Cont'd)

##### 7. (Cont'd)

- b. A Structured Circuit Emulation Customer Connection accepts up to 24 DS0 terminations from a channelized DS1 bit stream(s) from the customer (e.g., MegaLink Service with MegaLink Channel Service). Where MegaLink Service is used, the customer is responsible for paying the appropriate charges for MegaLink Service and MegaLink Channel Service. MegaLink Channel Service Broadband Line Service Feature Activation Charges apply for each DS0 termination to be directed to the Structured Circuit Emulation Customer Connection. The customer specifies the desired grouping of such DS0 terminations into ATM PVCs. An ATM CBR PVC Segment and Bandwidth Charges<sup>1</sup> apply for each PVC requested in association with the service originating from the TDM premises to the ATM Switch. Additionally, the standard charges apply for the corresponding ATM CBR PVC Segments to which these are mapped within the ATM switch.

A Structured Circuit Emulation Customer Connection is available with or without Channel Associated Signaling (CAS)<sup>2</sup> and is specified by the customer when service is ordered. CAS is necessary to support channelized DS1 TDM applications requiring DS1 Robbed Bit Signaling support.

8. A customer requiring connectivity to ATM Service greater than 1.536 Mbps but less than 44.210 Mbps may select ATM Service Customer Connections Using IMA. An IMA Customer Connection allows the customer to select an ATM Customer Connection at a speed that is a multiple (in multiples from 2 through 8) of 1.536 Mbps service. IMA Customer Connections are available at speeds of 3.072 Mbps, 4.608 Mbps, 6.144 Mbps, 7.680 Mbps, 9.216 Mbps, 10.752 Mbps, and 12.288 Mbps.

To access an IMA Customer Connection, the customer subscribes to the appropriate quantity of 1.536 Mbps Broadband Lines and Broadband Line Extensions to equal the bandwidth of the IMA Customer Connection. A reference chart is provided in A40.5.3.A.3.

9. The appropriate nonrecurring charges for an existing IMA Customer Connection to be changed to another speed of IMA Customer Connection shall be the appropriate nonrecurring charges from Section A40.5 for any additional Broadband Line Service plus the full nonrecurring charges from Section A140.8 for the new speed IMA Customer Connection requested and any associated PVC Features.

10. A customer requiring connectivity to ATM Service greater than 1.536 Mbps but less than 44.210 Mbps may select an ATM Subrate T3 Customer Connection. ATM Subrate T3 Customer Connections are available at speeds of 18 Mbps, 24 Mbps, 30 Mbps and 36 Mbps.

Several technical limitations exist in association with the provisioning of ATM Subrate T3 Service. An ATM Subrate T3 Customer Connection is provisioned utilizing 44.210 Mbps of transport bandwidth (e.g., a 44.210 Mbps Broadband Line Service); no other service(s) may utilize the remaining bandwidth. While an ATM Subrate T3 Customer Connection can simultaneously support both PVCs and SVCs, bandwidth reserved for SVCs is not available for use by PVCs (and vice versa). UBR PVCs and UBR SVCs are not allowed on an ATM Subrate T3 Customer Connection.

**Note 1:** PVC Segment Bandwidth charges shall be based upon the equivalent bandwidth required for each PVC requested. The transport of TDM service as ATM Circuit Emulation Service requires additional overhead. Consequently, the bandwidth required for a given PVC will be greater than the sum of the DS0 TDM bandwidth. For example, the PVC resulting from a single DS0 TDM bit stream of 64 Kbps will be greater than 64 Kbps as a result of the equivalent bandwidth required for overhead and will require two Increments of 64 Kbps Bandwidth per CBR PVC Segment.

**Note 2:** However, Channel Associated Signaling (CAS) may not be available at all ATM switch locations.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)****A140.8.2 Terms and Conditions (Cont'd)**

(T)

**C. Provision of Service (Cont'd)**

11. To have ATM Back-Up Capability as an option for a 44.210 Mbps or 149.760 Mbps Customer Connection, the customer is required to have an ATM Service Back-Up Customer Connection and a separate Broadband Line (with Broadband Line Extension Service, as appropriate) which are designated specifically for back-up purposes. Monthly rates and nonrecurring charges applicable for a Back-Up Customer Connection are provided in A140.8.3.A. Monthly rates and nonrecurring charges for Broadband Line Service are found in A40.5.

The activation of a Back-Up Customer Connection via the rerouting of traffic from a primary Customer Connection to the Back-Up Customer Connection is a manual operation performed by the Company at the direction of the customer. At the direction of the customer, the Company will subsequently then redirect traffic from the Back-Up Customer Connection to the primary Customer Connection.

A Primary Customer Connection Back-Up Enablement/Change Charge provided in A140.8.3.A is applicable per existing primary Customer Connection which is requested by the customer to be back-up enabled and is billed to each primary Customer Connection account. A Primary Customer Connection Back-Up Enablement/Change Charge is also applicable for each existing back-up enabled primary Customer Connection when the customer requests a reassignment of that primary Customer Connection to a different Back-Up Customer Connection.

**D. Contract Plans**

1. Contract plans as specified in the Fast Packet Services Payment Plan (SPP) in A40.10, with contract periods are described as follows:
  - a. Term Payment Plan A - payment periods may be selected from 12 to 36 months.
  - b. Term Payment Plan B - payment periods may be selected from 37 to 60 months.
2. (DELETED)
3. To be included under a Fast Packet Services Payment Plan, PVC Features and SVC Features must be associated with Customer Connections also under a Fast Packet Services Payment Plan. The length of the Fast Packet Services Payment Plan for the PVC Features and SVC Features cannot be for a longer period than the associated Customer Connection. A Termination Liability Charge will not be applicable for the disconnection of PVC Features and SVC Features set forth in A140.8.3.B, C and D, that are selected under the Fast Packet Services Payment Plan.
4. A Termination Liability Charge will not apply to ATM Service terminated on or after the date ATM Service became an obsolete service offering.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

**A140.8 Asynchronous Transfer Mode (ATM) Service (Cont'd)**

**A140.8.3 Rates and Charges (Cont'd)**

|   | Nonrecurring Charge | Month To Month | A 12 To 36 Months | B 37 To 60 Months | USOC  |
|---|---------------------|----------------|-------------------|-------------------|-------|
| <b>D. SVC Feature Charges</b>                               |                     |                |                   |                   |       |
| 1. SVC Service Activation Charge                            |                     |                |                   |                   |       |
| (a) Per Customer Connection (any speed)                     | \$35.00             | -              | -                 | -                 | ATASA |
| 2. SVC Bundles (Increment of 5 SVCs)                        |                     |                |                   |                   |       |
| (a) Per Bundle, Per Customer Connection                     | 30.00               | \$ 5.00        | \$ 5.00           | \$ 5.00           | ATASS |
| 3. SVC Bandwidth Per Customer Connection Activated for SVCs |                     |                |                   |                   |       |
| (a) Per Megabit <sup>1</sup> Bandwidth Charge, or           | -                   | 40.00          | 40.00             | 40.00             | ATASM |
| (b) Per Increment of 64 Kbps <sup>2</sup> Bandwidth Charge  | -                   | 2.60           | 2.60              | 2.60              | ATASK |
| 4. SVC Closed User Group (CUG)                              |                     |                |                   |                   |       |
| (a) Per Group   | 20.00               | -              | -                 | -                 | ATASG |
| (b) Per Entry   | 20.00               | -              | -                 | -                 | ATASE |
| <b>E. Feature Change Charge</b>                             |                     |                |                   |                   |       |
| 1. Per Occurrence   | 75.00               | -              | -                 | -                 | ATAFC |

**Note 1:** The Per Megabit Bandwidth Charge is applicable per Customer Connection activated for SVCs with a total bandwidth requirement greater than 1.536 Mbps.

**Note 2:** The Per Increment of 64 Kbps Bandwidth Charge is applicable per Customer Connection activated for SVCs with a total bandwidth requirement less than or equal to 1.536 Mbps.

Page 7.23 is hereby deleted in its entirety and removed from this Guidebook.

(N)

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.9 Reserved For Future Use (M)

### A140.10 Reserved For Future Use (M)

### A140.11 BellSouth Video Conferencing Service (T)

(Obsoleted 12/19/2003, Type B – Not available for new installations, additions or on transfers of service to new location). (M)

#### A140.11.1 General (T)

- A. BellSouth Video Conferencing service is a video service that provides switching and distribution processes required for interactive multipoint video conferencing based on International Telecommunications Union - Telecommunications (ITU-T) (H.320) standard codec equipment which must be provided by the customer at the endpoint locations. (M)  
This service includes a reservations center which provides established network connections, tracks individual conference room capabilities and availability, and provides initial trouble isolations. (M)  
Access from the customer premises to BellSouth Video Conferencing service must be purchased from other services provided by the Company. (M)
- B. BellSouth Video Conferencing service is provided as follows; (1) Automatic, Voice Activated Mode, (2) Chairman Control Mode, and (3) Broadcast/Presentation Mode. (T)
- C. This service utilizes a network based Multipoint Control Unit (MCU) to manage and switch compressed digital video signals produced by customer owned video codec equipment at video bit rate capabilities of 1.536 Mbps, 672/768 Kbps, 336/384 Kbps, and 112/128 Kbps. (M)
- D. *Company* services that will interface with BellSouth Video Conferencing service are Broadband Line Service, Switched 56 Kbps services, and ISDN switched services. (T)
- E. BellSouth Video Conferencing service includes a full-time, centralized, scheduling center (twenty-four hours per day, 365 days per year) accessible to the customer either by telephone dial-in or facsimile. (T)  
Scheduling can be established from two hours to eighteen (18) months in advance based on MCU/facility availability.
- F. In order to maintain the quality of BellSouth Video Conferencing service, the Company reserves the right to perform preventive maintenance or software upgrades to the network. This could result in the possibility of BellSouth Video Conferencing service being unavailable during the time period between 1:00 AM and 4:00 AM Eastern Time on any given Saturday or Sunday morning and 2:00 AM to 4:00 AM on any given Wednesday morning. However, the Company only expects to utilize this maintenance window for any given location on the average of once a quarter. In addition, the Company will make every reasonable effort to provide advance notice to those customers likely to be affected by such maintenance work. This maintenance window may be adjusted by the Company upon written notice to the customer. (T)
- G. The *Terms, Conditions* and rates specified herein are applicable to BellSouth Video Conferencing service. *Terms, Conditions* and rates specified in other sections of this and other *service publications* of the Company may also apply. (T)
- H. The rates and charges set forth for BellSouth Video Conferencing service provides for furnishing service where suitable facilities are available. Service inquires will be necessary to determine availability. (T)
- I. The technical specifications and standard network interfaces for BellSouth Video Conferencing service are contained in BellSouth Technical Reference 73566. This publication is available from: (T)  
*AT&T* Telecommunications, Inc. (T)  
Documentation Organization  
20th Floor  
600 North 19th Street  
Birmingham, Alabama 35203

#### A140.11.2 Terms and Conditions (T)

- A. Explanation of Terms
- Minute of Use (MOU)  
The term "minute of use" denotes the usage of BellSouth Video Conferencing service facilities for the purpose of calculating chargeable usage. Partial minutes count as full minutes. (T)  
No credit will be given for scheduled time not actually utilized unless canceled at least forty-eight hours prior to the scheduled conference time.
  - Video Conferencing Serving Area  
Company Central Offices that have been designated as Serving Area Points for BellSouth Video Conferencing service. (T)  
A customer may access the Video Conferencing Serving Area via Broadband Line Service, ISDN switched services, or Switched 56 Kbps services.
  - Serving Area Point (SAP)  
A Company Central Office that is designated as a member of the Video Conferencing Serving Area.
  - Network Compatibility Test  
Company/Customer end-to-end testing of end user equipment, codecs, multiplexers, transmission facilities, and Digital Crossconnect Systems at MCU H.320 standard compatibility.



## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.11 BellSouth Video Conferencing Service (Cont'd)

#### A140.11.2 Terms and Conditions (Cont'd)

##### A. Explanation of Terms (Cont'd)

##### 5. MOU Package

A usage sensitive offering of BellSouth Video Conferencing service for customers with fluctuating conference needs. The customer has the option of operating this service at or below the level of service quality purchased. Usage will be billed at a per-minute of use rate of the actual speed utilized. The fixed rate will be established based on the highest level of service required. Normal calling scopes as defined in Section A3 and A18 will apply to dial-in users.

##### 6. 50 Hour Package

A usage sensitive offering of BellSouth Video Conferencing service for customers wishing to purchase a minimum of 50 hours conference time per site, per month. Additional time is permitted and will be billed per minute of use greater than 50 hours. The customer has the option of operating this service at or below the level of service quality purchased. The recurring monthly rate will be based on the highest level of service required. Normal calling scopes as defined in Sections A3 and A18 will also apply to dial-in users.

##### 7. 100 Hour Package

A usage sensitive offering of BellSouth Video Conferencing service for customers wishing to purchase a minimum of 100 hours conference time per site, per month. Additional time is permitted and will be billed per minute of use greater than 100 hours. The customer has the option of operating this service at or below the level of service quality purchased. The recurring monthly rate will be based on the highest level of service required. Normal calling scopes as defined in Sections A3 and A18 will apply to dial-in users.

##### 8. Occasional Use Package

A usage sensitive offering for BellSouth Video Conferencing service customers that will provide dial-in video capability for occasional participants to a specific video conference. A per minute of use charge is applicable for each occasional use video site activated.

##### 9. Multispeed Capability

BellSouth Video Conferencing service provides the capability for customers to operate at various speeds at or below the level of service quality purchased.

##### B. Basis of Offering

1. Detailed billing is not part of this service. It may be provided under special arrangements.

2. Suspension of service is not allowed.

3. Service Charges as defined in Section A4 are not applicable.

4. The minimum service period for monthly subscribers is one month. The minimum service period for occasional users is thirty minutes.

5. BellSouth Video Conferencing service is available to customers under occasional use, month-to-month and variable rate period options. Variable rate periods have rates based on lengths of twelve to thirty-six months or thirty-seven to sixty months under conditions specified in the Fast Packet Services Payment Plan, in A40.10, except as modified in paragraph D.

6. BellSouth Video Conferencing service is not eligible for discount in accordance with provisions for concession service specified elsewhere in this *Guidebook*.

7. BellSouth Video Conferencing service is not available for use with Broadcast Quality Video Service.

8. BellSouth Video Conferencing service is provided on a per site basis.

9. A Network Compatibility Test is required and must be completed for each BellSouth Video Conferencing service site prior to scheduling the first conference. Initial testing is provided at no charge to the customer. Retesting may be necessary for changes such as CPE upgrades/moves, bit rate changes, or conference failure. Customers will be charged as provided in A40.11.3.E, for any retesting.

10. When Multispeed Capability is provided with an initial installation of BellSouth Video Conferencing service, nonrecurring charges do not apply. When Multispeed Capability is provided subsequent to the initial installation of service, nonrecurring charges will apply as provided in A40.11.3.E.

11. Rates applicable to the occasional use and month-to-month payment options are subject to company initiated changes.

(T)

(T)

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.11 BellSouth Video Conferencing Service (Cont'd)**

(T)

**A140.11.2 Terms and Conditions (Cont'd)**

(T)

**B. Basis of Offering (Cont'd)**

12. The customer owned codec equipment used to provide this service must be at ITU-T, H.320 standard and is a requirement of this service.
13. BellSouth Video Conferencing service must be provisioned with Extended Superframe Format (ESF) and Bipolar with 8 Zero substitution (Clear Channel Capability/B8ZS). (T)
14. All dedicated DSO facilities utilized for video must be reserved entirely for video and will be under full control of the BellSouth Video Conferencing service Master Scheduler. (T)
15. Cascading of MCU's is not available with this service offering.
16. Intermixing of various speeds within a single conference is not available with this service offering.
17. The minimum conference time for all video bit rates is thirty minutes.
18. Conference sites canceled less than forty-eight hours prior to the scheduled conference time will be billed as scheduled.
19. BellSouth Video Conferencing service usage will not be applied for any conference site that fails due to any cause other than the negligence or willful act of the subscriber or the failure of customer provided equipment. (T)
20. Trouble Determination is provided as specified for Complex (other Residence and Business Service) in Section A4. (T)
21. Access to BellSouth Video Conferencing service for customers outside of *Company* territory may be provided and billed for by other local exchange companies under the existing meet point guidelines. (T)
22. Obligations of Customer and Company.
  - a. The Company is not responsible for the installation, operation, or maintenance of any equipment provided by the customer.
  - b. The customer is responsible for the provision and maintenance of all CPE and to ensure that the operating characteristics of this equipment is compatible with and does not interfere with the service offered by the Company.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.11 BellSouth Video Conferencing Service (Cont'd)**

(T)

**A140.11.2 Terms and Conditions (Cont'd)**

(T)

**C. Provisions of Service**

1. Rates and charges contained in this Section consist of the following elements:

(T)

- a. MOU Package
- b. 50 Hour Package
- c. 100 Hour Package
- d. Occasional Use Package

2. Customers accessing BellSouth Video Conferencing service via Broadband Line Service must utilize Broadband Exchange Line Extensions when their serving wire center is not a SAP.

(T)

3. Customers accessing BellSouth Video Conferencing service via ISDN switched services or Switched 56 Kbps service must utilize interoffice channels when their serving wire center is not a SAP.

(T)

**D. Contract Plans**

1. Contract Plans are available under conditions specified in the Fast Packet Services Payment Plan in A40.10 with contract periods as follows:

(T)

- a. Term Payment Plan A - payment periods may be selected from 12 to 36 months.
- b. Term Payment Plan B - payment periods may be selected from 37 to 60 months.

2. The Termination Liability Charge is applicable as stated in A40.10, and is determined by multiplying the number of months remaining in the contract payment period by the contracted monthly rate by sixty percent.

3. Video bit rate changes are permitted with no Termination Liability Charge when:

- a. the completed service period is twelve months, or twenty-five percent (25%) of the length of the originally selected contract service period, whichever is greater, and

(T)

- b. the service period of the new Fast Packet SPP arrangement for the new video bit rate is equal to or longer than the remaining service period of the disconnected video bit rate, and

- c. the service orders to install the new video bit rate and disconnect the old video bit rate are related together and received by the Company at the same time, and there is no lapse in service between installation of the new video bit rate and the disconnection of the old video bit rate.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

**A140.11 BellSouth Video Conferencing Service (Cont'd)**

(T)

**A140.11.3 Rates and Charges**

|   | Nonrecurring Charge | Month To Month | A 12 to 36 Months | B 37 to 60 Months | USOC  |
|---|---------------------|----------------|-------------------|-------------------|-------|
| <b>A. MOU Package<sup>1</sup></b>             |                     |                |                   |                   |       |
| 1. 672/768 Kbps, per site, per month          |                     |                |                   |                   |       |
| (a) Fixed                                     | \$NA                | \$63.00        | \$50.00           | \$45.00           | MVCM7 |
| (b) Per MOU 672/768 Kbps                      | NA                  | .42            | .42               | .42               | NA    |
| (c) Per MOU 336/384 Kbps                      | NA                  | .28            | .28               | .28               | NA    |
| (d) Per MOU 112/128 Kbps                      | NA                  | .22            | .22               | .22               | NA    |
| 2. 336/384 Kbps, per site, per month          |                     |                |                   |                   |       |
| (a) Fixed                                     | NA                  | 38.00          | 30.00             | 27.00             | MVCM3 |
| (b) Per MOU 336/384 Kbps                      | NA                  | .28            | .28               | .28               | NA    |
| (c) Per MOU 112/128 Kbps                      | NA                  | .22            | .22               | .22               | NA    |
| 3. 112/128 Kbps, per site, per month          |                     |                |                   |                   |       |
| (a) Fixed                                     | NA                  | 25.00          | 20.00             | 18.00             | MVCM2 |
| (b) Per MOU 112/128 Kbps                      | NA                  | .22            | .22               | .22               | NA    |
| <b>B. 50 Hour Package<sup>1</sup></b>         |                     |                |                   |                   |       |
| 1. 1.536 Mbps, per site, per month            |                     |                |                   |                   |       |
| (a) Fixed (includes 50 hours of usage)        | NA                  | 885.00         | 708.00            | 602.00            | MVCF1 |
| (b) Each additional MOU greater than 50 hours | NA                  | .22            | .22               | .22               | NA    |
| 2. 672/768 Kbps, per site, per month          |                     |                |                   |                   |       |
| (a) Fixed (includes 50 hours of usage)        | NA                  | 672.00         | 538.00            | 457.00            | MVCF7 |
| (b) Each additional MOU greater than 50 hours | NA                  | .22            | .22               | .22               | NA    |
| 3. 336/384 Kbps, per site, per month          |                     |                |                   |                   |       |
| (a) Fixed (includes 50 hours of usage)        | NA                  | 490.00         | 392.00            | 333.00            | MVCF3 |
| (b) Each additional MOU greater than 50 hours | NA                  | .22            | .22               | .22               | NA    |
| 4. 112/128 Kbps, per site, per month          |                     |                |                   |                   |       |
| (a) Fixed (includes 50 hours of usage)        | NA                  | 409.00         | 327.00            | 278.00            | MVCF2 |
| (b) Each additional MOU greater than 50 hours | NA                  | .22            | .22               | .22               | NA    |

**Note 1:** Customer must subscribe to highest bit rate needed when utilizing multi-speed capability.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

**A140.11 BellSouth Video Conferencing Service (Cont'd)**

(T)

**A140.11.3 Rates and Charges (Cont'd)**

**C. 100 Hour Package<sup>1</sup>**

|  | Nonrecurring Charge | Month To Month | A 12 to 36 Months | B 37 to 60 Months | USOC  |
|--|---------------------|----------------|-------------------|-------------------|-------|
| 1. 1.536 Mbps, per site, per month             |                     |                |                   |                   |       |
| (a) Fixed (includes 100 hours of usage)        | NA                  | 1,283.00       | 1,026.00          | 872.00            | MVCH1 |
| (b) Each additional MOU greater than 100 hours | NA                  | .22            | .22               | .22               | NA    |
| 2. 672/768 Kbps, per site, per month           |                     |                |                   |                   |       |
| (a) Fixed (includes 100 hours of usage)        | NA                  | 1,044.00       | 835.00            | 710.00            | MVCH7 |
| (b) Each additional MOU greater than 100 hours | NA                  | .22            | .22               | .22               | NA    |
| 3. 336/384 Kbps, per site, per month           |                     |                |                   |                   |       |
| (a) Fixed (includes 100 hours of usage)        | NA                  | 838.00         | 670.00            | 570.00            | MVCH3 |
| (b) Each additional MOU greater than 100 hours | NA                  | .22            | .22               | .22               | NA    |
| 4. 112/128 Kbps, per site, per month           |                     |                |                   |                   |       |
| (a) Fixed (includes 100 hours of usage)        | NA                  | 748.00         | 598.00            | 508.00            | MVCH2 |
| (b) Each additional MOU greater than 100 hours | NA                  | .22            | .22               | .22               | NA    |

**D. Occasional Use Package (dial-in customers only)**

|                           |                     |    |         |        |       |
|---------------------------|---------------------|----|---------|--------|-------|
| 1. Video (112 - 384 Kbps) |                     |    |         |        |       |
| (a) Per site              | Nonrecurring Charge | NA | Per MOU | \$ .65 | USOC  |
|                           |                     |    |         |        | MVCOD |

**E. Network Compatibility Test and/or Multispeed Certification**

|               |  |  |                     |          |       |
|---------------|--|--|---------------------|----------|-------|
| 1. Subsequent |  |  |                     |          |       |
| (a) Per test  |  |  | Nonrecurring Charge | \$244.00 | USOC  |
|               |  |  |                     |          | MVCNS |

**Note 1:** Customer must subscribe to highest bit rate needed when utilizing multi-speed capability.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.12 Customer Network Management**

(Obsoleted 9/19/2011, Type B - Not available for new installations, additions or on transfers of service to new location.)

**A140.12.1 General**

- A. Customer Network Management (CNM) is available on an optional basis as a feature of Frame Relay Service and Asynchronous Transfer Mode (ATM) Service.
- B. The CNM option provides customers a view into their Fast Packet network for monitoring and trouble shooting purposes. (T)
- C. The CNM platform supports hierarchical customer names. For example, a customer defines an overall network name (usually the customer name) and then may choose to establish multiple sub-network names. A maximum of five hierarchical tiers are available (the overall network plus four sub-network tiers).
- D. Access to CNM is via a Web interface. A dial or dedicated method available in Section A32., Integration Plus Management Services, may also be used to access CNM. Switched service and private line service used as a means of accessing FlexServ service has been obsoleted (see A132). For security reasons, customers are required to identify themselves via a username and password. The username and password are assigned at the time the account is established. Following is a description and requirements for each type of access:
  - 1. Web Interface - This interface allows customers to access CNM via the Web using a standard Web browser. This type of access requires a Security Card.
    - a. (Obsoleted, See A132).
  - 2. (Obsoleted, See A132)
  - 3. (Obsoleted, See A132)

(M)

## A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES

### A140.12 Customer Network Management (Cont'd)

#### A140.12.1 General (Cont'd)

- E. CNM is offered in packages which provide the following CNM options: Fault Management, On Demand Statistics and Performance Reporting. (M)
1. Fault Management (M)
 

The Fault Management option provides the ability to monitor fault and alarm information as network events occur. If a network event results in automatic rerouting of customer owned PVCs on a Customer Connection within the Fast Packet network, such that those PVCs are not service impacted, then the Company will not send PVC events to the customer. The following Fault Management features are available on a customer and sub-network basis: (T)(M)

    - The Company will provide to the customer, in near real time, all events, faults, and network alarms on any Customer Connection or PVC. (M)
    - The customer can determine the severity level of alarms displayed and suppress the alarms they do not wish to view. (M)
  2. On Demand Statistics
 

CNM provides customers statistics for each Customer Connection and PVC on a customer and sub-network basis.
  3. Performance Reporting (PR) (T)
 

CNM-PR provides Frame Relay and/or ATM Service customers network performance reports on their Fast Packet network. Customers have the capability of requesting performance reports for interfaces. Interfaces are defined as customer connections and PVCs. CNM-PR provides a measure of the level of network performance of a customer's network and individual interfaces that is called the Network Performance Level. The Network Performance Level components include Incoming Utilization, Outgoing Utilization, Discarded Frames/Cells and Congestion. The Network Performance Level is used in several reports to provide a weighted performance measure taking into account all the performance parameters mentioned above. Historical Performance reports will baseline historic network performance, trend future performance and highlight network performance problems. The following selection of reports is available:

    - a. Network Summary Report - Provides an overview of the customer's network performance in terms of Total Frames/Cells Transmitted and Received, Percent Total Utilization, Total Frames/Cells Discarded, and Percent Frames/Cells Discarded of Total Frames/Cells Transmitted and Received.
    - b. Forecast Report - Provides the network interfaces that are projected to exceed customer specific thresholds of Utilization and Congestion.
    - c. Network Interface Performance Report - Provides the Network Performance Level on a customer selectable interface (customer connection or PVC).
    - d. Capacity Planning Report - Provides the top ten over-utilized and top ten under-utilized interfaces.
    - e. Threshold Exceptions Report - Provides a daily report on the top ten interfaces that exceed a customer selectable threshold parameter. These parameters are Input Utilization, Output Utilization, Incoming Congestion, Outgoing Congestion, In Discards, and Out Discards.
    - f. Top Ten Report - Provides a daily report of the top ten interfaces with the highest volumes and the worst Network Performance Level. It also specifies the top ten interfaces with the greatest change in both volume and Network Performance Level.
- F. The *Terms, Conditions* and rates specified herein are in addition to the applicable *Terms, Conditions* and rates specified in other sections of this and other service publications of the Company. (T)
- G. The rates and charges set forth for CNM provide for the furnishing of service where suitable facilities are available.
- H. CNM is only available for use with Frame Relay Service described in A140.1 and ATM service described in A140.8.

---

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES****A140.12 Customer Network Management (Cont'd)****A140.12.2 Terms and Conditions****A. Basis of Offering**

1. Suspension of service is not allowed.
2. CNM is not available on Back-Up Customer Connections non Intelligent PVCs.
3. A customer may subscribe to CNM on a monthly basis. An account is established which will include the Customer Connections designated by the customer to have CNM capability. Customers may choose to subscribe to CNM for all Customer Connections in their Fast Packet network or choose CNM for only a portion. (T)
4. Obligations of Customer and Company
  - a. The Company is not responsible for the installation, operation, or maintenance of any equipment provided by the customer.
  - b. The customer is responsible for the provision and maintenance of all Customer Provided (CPE) and to ensure that the operating characteristics of this equipment are compatible with and do not interfere with the service offered by the Company.
  - c. Application testing described in A2.5.11 is not available for CNM.
5. In order to maintain the quality of CNM, the Company reserves the right to perform preventive maintenance and software updates. This could result in CNM being unavailable during the time period between midnight and 3:00 A.M. Eastern Time on any given Sunday morning. In addition, preventive maintenance may be performed on the Frame Relay or ATM network being monitored by CNM on any given Monday or Sunday between 2:00 A.M. and 4:00 A.M. Eastern Time. CNM will be unable to view these circuits while preventive maintenance is being performed. However, the Company only expects to utilize this maintenance window for any given switch on the average of once a quarter. In addition, the Company will make every reasonable effort to provide advance notice to those customers likely to be severely affected by such maintenance work.
6. The minimum service period is one month. (M)



## **A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**

### **A140.12 Customer Network Management (Cont'd)**

#### **A140.12.2 Terms and Conditions (Cont'd)**

##### **B. Provision of Service**

1. CNM is available in three packages – Gold, Silver or Bronze. All Customer Connections within a customer's account must be under the same package. If a customer desires to have multiple packages, a separate account must be established for each package type. Following is a description of what is available in each package:

- The Gold Package includes all CNM options; Fault Management, On Demand Statistics and Performance Reporting. (M)
- The Silver Package includes Fault Management and On Demand Statistics. (M)
- The Bronze Package includes only Fault Management. (M)

2. Customers who subscribe to CNM may choose to monitor their entire Fast Packet network or selected Customer Connections. The following rates and charges are applicable for customers who subscribe to CNM: (T)

##### a. Service Establishment Charge

The Service Establishment Charge is a nonrecurring charge which applies per Frame Relay or ATM customer account. If a customer is both a Frame Relay and ATM customer, only one Service Establishment Charge will apply. This charge covers the initial establishment and set-up of the CNM account for the customer. A username(s) and password(s) will be assigned for use by the customer in accessing their account. At the time the account is established, a customer may also choose to establish sub accounts.

##### b. Reporting Packages – Gold, Silver, Bronze

A monthly charge applies for each Customer Connection the customer has chosen to monitor. A nonrecurring charge is applicable per Customer Connection at the time of installation.

##### c. Subsequent Modification Charge

The Subsequent Modification Charge is a nonrecurring charge which applies per Customer Connection when a CNM customer requests that existing CNM Customer Connections, or PVC's on the Customer Connection, be modified. Examples of this charge include change of customer name and movement between packages. This charge is not applicable:

- when a new PVC is added to an existing CNM Customer Connection and CNM is requested for the new PVC, or
- for a request to change a password.

##### d. Management Access Interface

All customers must have a Management Access Interface. This connection allows the customer to monitor their network. A monthly charge applies for each Web Interface. A nonrecurring charge is applicable per web access at the time of installation. A Security Card described below is required for each web access. See A32.1.2 for a dial or dedicated access option.

- Security Card – The Security Card charge specified in A140.12.3.B will apply for the initial card or for the issuance of additional cards for additional users or to replace a lost, damaged or expired card.

##### **C. Contract Plans**

1. Contract plans are available under conditions specified in the Fast Packet Services Payment Plan in A40.10 with contract periods described as follows:

- a. Term Payment Plan A - payment periods may be selected from 12 to 36 months.
- b. Term Payment Plan B - payment periods may be selected from 37 to 60 months.

**A140. OBSOLETE SERVICE OFFERING - FAST PACKET TRANSPORT SERVICES**  
**A140.12 Customer Network Management (Cont'd)**

**A140.12.3 Rates and Charges**

**A. CNM - Performance Reporting**

|    |   | <b>Nonrecurring Charge</b> |                       |                            | <b>USOC</b>              |
|----|---|----------------------------|-----------------------|----------------------------|--------------------------|
| 1. | CNM Service Establishment Charge                |                            |                       |                            |                          |
|    | (a) Per Customer                                |                            |                       | <b>\$250.00</b>            | <b>CNMSE</b>             |
|    |   | <b>Nonrecurring Charge</b> | <b>Month To Month</b> | <b>A 12 to 36 Months</b>   | <b>B 37 to 60 Months</b> |
| 2. | Gold Reporting <sup>1</sup>                     |                            |                       |                            | <b>USOC</b>              |
|    | (a) Per Frame Relay Service Customer Connection | <b>\$95.00</b>             | <b>\$0.00</b>         | <b>\$0.00</b>              | <b>\$0.00</b>            |
|    | (b) Per ATM Service Customer Connection         | <b>95.00</b>               | <b>0.00</b>           | <b>0.00</b>                | <b>0.00</b>              |
| 3. | Silver Reporting <sup>2</sup>                   |                            |                       |                            |                          |
|    | (a) Per Frame Relay Service Customer Connection | <b>90.00</b>               | <b>0.00</b>           | <b>0.00</b>                | <b>0.00</b>              |
|    | (b) Per ATM Service Customer Connection         | <b>90.00</b>               | <b>0.00</b>           | <b>0.00</b>                | <b>0.00</b>              |
| 4. | Bronze Reporting <sup>3</sup>                   |                            |                       |                            |                          |
|    | (a) Per Frame Relay Service Customer Connection | <b>85.00</b>               | <b>0.00</b>           | <b>0.00</b>                | <b>0.00</b>              |
|    | (b) Per ATM Service Customer Connection         | <b>85.00</b>               | <b>0.00</b>           | <b>0.00</b>                | <b>0.00</b>              |
|    |   |                            |                       | <b>Nonrecurring Charge</b> | <b>USOC</b>              |
| 5. | Subsequent Modification Charge                  |                            |                       |                            |                          |
|    | (a) Per Customer Connection                     |                            |                       | <b>\$75.00</b>             | <b>CNMSM</b>             |

**B. Management Access Interface<sup>4</sup>**

|    |               | <b>Nonrecurring Charge</b> |                |                | <b>USOC</b>    |
|----|---------------|----------------------------|----------------|----------------|----------------|
| 1. | Web Interface |                            |                |                |                |
|    | (a) Each      | <b>\$125.00</b>            | <b>\$25.00</b> | <b>\$18.75</b> | <b>\$15.00</b> |
|    |               | <b>Nonrecurring Charge</b> |                |                | <b>USOC</b>    |
| 2. | Security Card |                            |                |                |                |
|    | (a) Each      | <b>\$100.00</b>            |                |                | <b>CNMSC</b>   |

**A140.13 (DELETED)**

- Note 1:** Includes Fault Management, On Demand Statistics and Performance Reports.
- Note 2:** Includes Fault Management and On Demand Statistics.
- Note 3:** Includes only Fault Management.
- Note 4:** See A32.1.2 for a dial or dedicated access option.

Page 15 is hereby deleted in its entirety and removed from this Guidebook.

(M)

(N)

---

## A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)

### CONTENTS

|               |                                       |            |     |
|---------------|---------------------------------------|------------|-----|
| <b>A142.1</b> | <b>ISDN - Business Service (IBS)</b>  | 1          |     |
| A142.1.1      | General                               | 1          |     |
| A142.1.2      | Rates and Charges                     | 1          |     |
| <b>A142.2</b> | <b>ISDN - Residence Service (IBS)</b> | 4          |     |
| A142.2.1      | General                               | 4          |     |
| A142.2.2      | <i>Terms and Conditions</i>           | 4          | (T) |
| A142.2.3      | Definitions                           | 4.1        |     |
| A142.2.4      | Rates and Charges                     | 4.1        |     |
| A142.2.5      | Optional Features                     | <b>6.1</b> | (T) |
| <b>A142.3</b> | <b>Primary Rate ISDN</b>              | 7          |     |
| A142.3.1      | Reserved for Future Use               | 7          |     |
| A142.3.2      | <i>Terms and Conditions</i>           | 7          | (T) |

**A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

**A142.1 ISDN - Business Service (IBS)**

(Obsoleted 10-30-96 Type 4) Service rates in this section are available for existing lines at existing locations only. Not available for new service, additions to existing service or moves of existing service to new location.

Obsolescence Rules

1. Inward activity for ISDN - Business Service in this Section will not be allowed except that features may be added or deleted on existing lines at their current location. (T)
2. Existing ISDN - Business Service subscribers will be allowed to maintain their ISDN - Business Service at their current location until the expiration date of their Term Payment Plan. Upon expiration of their Term Payment Plan subscribers must either; 1) convert to the month to month rate for ISDN - Business Service, or 2) subscribe to an alternate service.
3. ISDN - Business Service subscribers upon moving to a new location must either; 1) convert to the Flat Rate Threshold Pricing Plan for ISDN - Business Service; or 2) subscribe to an alternate service.
4. Nonrecurring charges will not apply for conversion of ISDN - Business Service subscribers to the Flat Rate Threshold Pricing Plan.
5. Existing ISDN - Business Service subscribers will reference Section A42.1 for Interoffice Circuits and Optional Features. (T)

**A142.1.1 General**

- A. The definitions, *Terms and Conditions* in A42.1 will apply to these offerings except as stated following: (T)
- B. Service will be allowed as Flat Rate or Measured Rate as indicated in this Section. Usage rates as appropriate are specified in Section A3. (T)

**A142.1.2 Rates and Charges**

- A. Interface
  1. Basic Rate DSL Access Arrangement

|     |                        | Installation<br>Charge | Month<br>to<br>Month | Rate Stability<br>Monthly Rate |                     | USOC  |
|-----|------------------------|------------------------|----------------------|--------------------------------|---------------------|-------|
|     |                        |                        |                      | 24-59<br>Mos. Plan             | 60-120<br>Mos. Plan |       |
| (a) | ISDN Access (5ESS/DMS) | \$130.00               | \$55.00              | \$55.00                        | \$55.00             | LTBLB |
| (b) | (DELETED)              |                        |                      |                                |                     |       |
| (c) | ISDN Access (EWSD)     | 130.00                 | 55.00                | 55.00                          | 55.00               | LTBEB |

(M)

**A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK - ISDN**

**A142.1 ISDN - Business Service (IBS) (Cont'd)**

**A.142.1.2 Rates and Charges (Cont'd)**

**A. Interface (Cont'd)**

|   | Installation Charge | Month to Month | Rate Stability Monthly Rate |                  | USOC  |         |
|---|---------------------|----------------|-----------------------------|------------------|-------|---------|
|   |                     |                | 24-59 Mos. Plan             | 60-120 Mos. Plan |       |         |
| 2. Channels Activated   |                     |                |                             |                  |       |         |
| a. B Channel (Maximum of 2)   |                     |                |                             |                  |       | (T)     |
| (1) Circuit Switched Voice/Data, Each                                     |                     |                |                             |                  |       | (M1)    |
| (a) Flat Rate   | -                   | \$16.25        | \$13.25                     | \$11.25          | LPRFX | (M1)    |
| (b) Measured  | -                   | 6.50           | 5.30                        | 4.10             | LPSMX | (M1)    |
| (2) Circuit Switched Voice/Data for use with MultiServ PLUS service, each |                     |                |                             |                  |       |         |
| (a) Flat  | -                   | 12.25          | 9.35                        | 7.25             | MNCCF |         |
| (b) Measured  | -                   | 2.50           | 1.30                        | 0.10             | MNCCR |         |
| <b>B. Interface Users</b>   |                     |                |                             |                  |       |         |
| 1. Per User/Terminal Profile  |                     |                |                             |                  |       |         |
| a. Terminal Service Profile (EWSD)  |                     |                |                             |                  |       |         |
| (1) Per Terminal Service Profile  |                     |                |                             |                  |       |         |
| (a) Each  | -                   | -              | -                           | -                | EWSTP |         |
| b. Access to B Channel CSV/CSD  |                     |                |                             |                  |       |         |
| (1) Flat Rate (5ESS/DMS)  |                     |                |                             |                  |       |         |
| (a) Each  | \$10.00             | -              | -                           | -                | LTQ8Y |         |
| (2) Flat Rate (EWSD)  |                     |                |                             |                  |       |         |
| (a) Voice   | 10.00               | -              | -                           | -                | LTQVB |         |
| (b) Data  | -                   | -              | -                           | -                | LTQDB |         |
| (3) Measured Rate - Area Calling Service (5ESS/DMS)                       |                     |                |                             |                  |       |         |
| (a) with Local Usage Detail (LUD)   | 10.00               | 3.00           | 3.00                        | 3.00             | LTQ83 |         |
| (b) without Local Usage Detail (LUD)                                      | 10.00               | -              | -                           | -                | LTQ84 |         |
| (c) Premium Calling <sup>1</sup>  | 10.00               | -              | -                           | -                | LTQ85 |         |
| (4) Measured Rate - Area Calling Service - (EWSD) <sup>2</sup> Voice      |                     |                |                             |                  |       | (T)(M2) |
| (a) with Local Usage Detail (LUD)   | 10.00               | 3.00           | 3.00                        | 3.00             | LTQV3 | (M2)    |
| (b) without Local Usage Detail (LUD)                                      | 10.00               | -              | -                           | -                | LTQV4 | (M2)    |
| (c) Premium Calling <sup>1</sup>  | 10.00               | -              | -                           | -                | LTQV5 | (T)(M2) |
| (5) Measured Rate - Area Calling service - (EWSD) <sup>2</sup> Data       |                     |                |                             |                  |       | (T)(M2) |
| (a) with Local Usage Detail (LUD)   | -                   | -              | -                           | -                | LTQD3 | (M2)    |
| (b) without Local Usage Detail (LUD)                                      | -                   | -              | -                           | -                | LTQD4 | (M2)    |
| (c) Premium Calling <sup>1</sup>  | -                   | -              | -                           | -                | LTQD5 | (T)(M2) |
| <b>Note 1:</b> Requires Premium Calling Usage Package in A3.2.8.F.        |                     |                |                             |                  |       | (T)     |
| <b>Note 2:</b> Both Voice and Data required per B channel access on EWSD. |                     |                |                             |                  |       | (T)(M2) |

M1 - Material appearing on this page previously appeared on page(s) 1 of this section.  
M2 - Material appearing on this page previously appeared on page(s) 3 of this section.

---

## A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)

### A142.1 ISDN - Business Service (IBS) (Cont'd)

#### A142.1.2 Rates and Charges (Cont'd)

C. Usage (M)

1. Circuit Switched Voice and Data (Measured Only)

- a. Per minute rates for usage on all circuit switched service (voice and/or data), and *Terms and Conditions* for Area Calling Service defined in A3.2. (T)

## **A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

### **A142.2 ISDN - Residence Service (IRS)**

Effective December 15, 2015, ISDN – Residence Service (IRS) is obsolete. IRS will not be available for new service, additions or changes to existing service, or moves of existing service to a new location. Customers may retain the service for existing IRS lines at existing locations.

#### **A142.2.1 General**

- A. Effective October 30, 1996 ISDN - Residence Service (IRS) will be offered only under a Flat Rate Threshold Pricing Plan. This plan allows up to 200 hours of use each month per DSL at the flat rate. Minutes of use rates will apply for all usage above the 200 hours per DSL threshold. A minimum service period of three months will be required on the Flat Rate Threshold Pricing Plan. Termination Charges as defined in this Guidebook will apply if the subscriber terminates or disconnects the service prior to fulfilling the three months period.
- B. ISDN - Residence Service (IRS) is a new intraLATA group of offerings supported by the Integrated Services Digital Network (ISDN) architecture. IRS supports simultaneous transmission of voice, data, and packet services on the same exchange access line. Calling/Called Number Delivery and Calling Name Delivery and Call Hold are included with this service where facilities permit. Numbers will not be delivered from lines equipped with Optional Calling Numbers Blocking in A13.19.
- C. IRS provides a new method of access to the telephone network called Basic Rate Access. Basic Rate Access will consist of the ability to access up to two 64 Kbps (B) channels and one 16 Kbps (D) channel at the service delivery point.
- D. IRS is provided through Basic Rate Access. Features are available to increase the capability of the Bearer Alternative Service and may be subscribed to on an as-needed basis.
- E. B channel circuit switched services offer up to 64 Kbps intra-office transmission of voice or data. This option permits the customer to utilize either circuit voice or data transmission paths on a per call selection basis. Transmission on the B channel will be circuit switched at 64 Kbps within the switch and/or equipped facilities between ISDN compatible central offices. ISDN interconnection to non-ISDN equipped central offices will be potentially subjected to analog transmission or sub-rated to 56 Kbps. This option includes one directory number (DN).
- F. IRS will consist of the following components:
  - Basic Rate Digital Subscriber Line (DSL) Access
  - Two B channels CSV/CSD and one D channel Low Speed Packet Switched Data. Optional B channel packet services may be purchased in place of the B channel CSV/CSD. A maximum of two simultaneous B channels can be in use per Basic Rate Access.
  - Minimum of one and maximum of eight User Profiles per Basic Rate Digital Subscriber Line (DSL) Access Arrangement.
- G. IRS lines under the Flat Rate Threshold Pricing Plan will be an exception to Section A2, and can be mixed with either flat rate, message or measured lines at the same location.

#### **A142.2.2 Terms and Conditions**

- A. Customer Premises Equipment (CPE) that is compatible with the ISDN Interface is the responsibility of the user for provisioning.
- B. The Company will be responsible for publishing and maintaining ISDN Interface Specifications.
- C. The Company shall not be responsible if changes in any of the equipment, operations, or procedures of the Company utilized in the provision of Basic Rate Access render any facilities provided by the customer obsolete or require modification or alteration of such equipment or system, or otherwise affect its use or performance.
- D. Suspension of service is not allowed.
- E. Service Charges in Section A4 are applicable per Basic Rate DSL access in addition to rates and charges following.
- F. Installation charges in A42.1 will be waived for ISDN Residence Service customers transferring existing service to ISDN Business Service. Appropriate installation charges will be charged for any additions to the service completed at the time of transfer.
- G. Usage rates will apply for all minutes of use over the 200 hours allowed under the Flat Rate Threshold Pricing Plan. Usage rates, as appropriate, are specified in this section.
- H. IRS will be available where central office and outside plant facilities permit.
- I. When a customer's normal serving central office is not equipped to provide IRS, that customer may be served from an equipped central office without incurring interoffice charges. IRS customers to be served under this arrangement must sign an agreement the service will be moved back to the normal serving central office and to a probable number change when/if that office is equipped with ISDN. If the customer's normal serving central office is equipped to provide IRS, and service is provided from another central office at the customer's request, interoffice charges as provided in this Section will apply. When requested by the customer, IRS served from a central office other than the central office the subscriber would normally be served from will require interoffice facilities as provided in this Section, per DSL. Any non-ISDN interoffice facilities connecting to this service will follow the *Terms and Conditions* in Section A9.
- J. Each ISDN Basic Rate DSL Access Arrangement will be counted as one line in determining the application of the Service Charges specified in Section A4 and the End User Charges as specified in the End User Common Access Service section of BellSouth Telecommunications, Inc., FCC No.1, Section 4.

(T)

(T)

(M)

**A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

**A142.2 ISDN - Residence Service (IRS) (Cont'd)**

(M)

**A142.2.3 Definitions**

B CHANNEL

A bidirectional synchronous channel capable of supporting 64 Kbps of digital transmission.

D CHANNEL

A 16 Kbps digital signaling channel also capable of supporting 9.6 Kbps of packet information for the Basic Rate Interface.

64 KBPS CLEAR CHANNEL CAPACITY (CCC)

A B channel connection that provides end-to-end digital connection in which all 64 Kbps of bandwidth are available for customer use.

**A142.2.4 Rates and Charges**

**A. Interoffice Circuits**

**1. Per DSL**

|                              | <b>Installation Charge</b> | <b>Monthly Rate</b> | <b>USOC</b>  |
|------------------------------|----------------------------|---------------------|--------------|
| (a) Each, Including 1st Mile | <b>\$240.00</b>            | <b>\$115.00</b>     | <b>MIGNC</b> |
| (b) Each additional mile     | -                          | <b>.45</b>          | <b>MIGNM</b> |

**B. Interface**

|   | <b>Installation Charge</b> | <b>Month to Month</b> | <b>Rate Stability<sup>1</sup> Monthly Rate 24-59 Mos. Plan</b> | <b>USOC</b>        |
|---|----------------------------|-----------------------|--|--------------------|
| 1. Basic Rate DSL Access Arrangement              |                            |                       |  |                    |
| (a) ISDN Access (5ESS/DMS)                        | <b>\$ 130.00</b>           | -                     | -  | <b>LTBLR/LQTTR</b> |
| (b) ISDN Access (EWSD®)                           | <b>130.00</b>              | -                     | -  | <b>LQTER/LQTER</b> |
| 2. Channels Activated                             |                            |                       |  |                    |
| a. Up to 2 B channels Circuit Switched Voice/Data |                            |                       |  |                    |
| (1) Per DSL                                       |                            |                       |  |                    |
| (a) Flat Rate <sup>2</sup>                        | -                          | <b>\$ 48.00</b>       | <b>\$36.00</b>   | <b>LPRFX/LQFX</b>  |
| (2) Permanent High Speed Packet Additive          |                            |                       |  |                    |
| (a) Each  | -                          | <b>110.00</b>         |  | <b>LPWHX</b>       |

**Note 1:** As of August 31, 2011, Rate Stability Plans are no longer available for new or renewing subscribers.

**Note 2:** The appropriate flat rate schedule in Section A3 will also apply.

Material previously appearing on this page now appears on page(s) 4 of this section.

®Registered Trademark of Siemens Aktiengesellschaft



**A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

**A142.2 ISDN - Residence Service (IRS) (Cont'd)**

**A142.2.4. Rates and Charges (Cont'd)**

|   | Installation Charge                         | Monthly Rate                  | USOC        |     |
|---|---|-------------------------------|-------------|-----|
| <b>C. Interface Users</b>   |   |                               |             |     |
| 1. Per User/Terminal Profile  |   |                               |             |     |
| a. Terminal Service Profile (EWSD®)   |   |                               |             |     |
| (1) Per Terminal Service Profile  |   |                               |             |     |
| (a) Each - - EWSTP/EWSTQ  |   |                               |             |     |
| b. Access to B Channel CSV/CSD  |   |                               |             |     |
| (1) Flat Rate (5ESS/DMS)  |   |                               |             |     |
| (a) Each \$10.00 - LTQ8Y/LQAFX  |   |                               |             |     |
| (2) Flat Rate (EWSD) <sup>1</sup>   |   |                               |             |     |
| (a) Voice 10.00 - LTQVR/LQAVX   |   |                               |             |     |
| (b) Data - - LTQDR/LQADX  |   |                               |             |     |
| (3) Measured Rate - Area Calling Service - (5ESS/DMS)   |   |                               |             |     |
| (a) with Local Usage Detail (LUD) 10.00 \$1.00 LTQ8C  |   |                               |             |     |
| (b) without Local Usage Detail (LUD) 10.00 - LTQ8D  |   |                               |             |     |
| (c) Premium Calling <sup>2</sup> 10.00 - LTQ8E  |   |                               |             |     |
| (4) Measured Rate - Area Calling - (EWSD®) <sup>2</sup> - Voice   |   |                               |             |     |
| (a) with Local Usage Detail (LUD) 10.00 1.00 LTQVC  |   |                               |             |     |
| (b) without Local Usage Detail (LUD) 10.00 - LTQVD  |   |                               |             |     |
| (c) Premium Calling <sup>2</sup> 10.00 - LTQVE  |   |                               |             |     |
| (5) Measured Rate - Area Calling Service - (EWSD®) <sup>1</sup> - Data  |   |                               |             |     |
| (a) with Local Usage Detail (LUD) - - LTQDC   |   |                               |             |     |
| (b) without Local Usage Detail (LUD) - - LTQDD  |   |                               |             |     |
| (c) Premium Calling <sup>2</sup> - - LTQDE  |   |                               |             |     |
| <b>D. Usage</b>   |   |                               |             |     |
| 1. Circuit Switched Voice and Data (Measured Only)  |   |                               |             |     |
| a. Per minute rates for usage on all circuit switched services (voice and/or data), and <i>Terms and Conditions</i> for Area Calling Service are defined in A3.2. (T) |   |                               |             |     |
| 2. Usage above 200 hours per DSL allowed in the Flat Rate Threshold Pricing Plan will be billed at the per minute of use rate.  |   |                               |             |     |
|   |   | <b>Rate Per Minute of Use</b> | <b>USOC</b> |     |
| (a)   | Per Minute of Use above Threshold Allowance | <b>\$0.01</b>                 | <b>N/A</b>  | (M) |

**Note 1:** Both Voice and Data re required per B channel access on EWSD®.

**Note 2:** Requires Premium Calling Usage Package in A3.2.8.F.

**A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

**A142.2 ISDN - Residence Service (IRS) (Cont'd)**

**A142.2.4. Rates and Charges (Cont'd)**

**E. Packages**

1. Packages EZ1, EZ1A, EZ2 and EZ2A are available for use with IRS on National ISDN lines. The packages will not be available on Custom ISDN lines. A credit will be applied to the monthly billing for customers purchasing IRS via one of these packages. Packages must be ordered exactly as stated in the descriptions of the packages. If any feature listed in the package is deleted or provisioning options are changed, the package credit will no longer apply. Additional optional features compatible with the package configurations are allowed with the packages. Additional features may be added only on the User Profile already provisioned with features. (T)  
(M1)
2. Description of Packages - (M1)
  - a. Package EZ1 - Low Speed DSL, 2 B-channel CSV/CSD - Channel Activation, 2 B-channel CSV/CSD - User Profile, 2 Additional Call Appearances, 1 Conference Drop Hold & Transfer, 1 Call Forwarding Variable - Button.
  - b. Package EZ1A - Low Speed DSL, 2 B-channel CSV/CSD - Channel Activation, 2 B-channel CSV/CSD - User Profile, 2 Additional Call Appearances, 1 Conference Drop Hold & Transfer, 1 Call Forwarding Variable - Button, Visual Message Waiting, Call Forwarding Busy Line, Call Forwarding Don't Answer. Voice mail service will be allowed with this package.
  - c. Package EZ2 - Low Speed DSL, 2 B-channel CSV/CSD - Channel Activation, 2 B-channel CSV/CSD - User Profile, 2 Additional Call Appearances, 1 Conference Drop Hold & Transfer, 1 Call Forwarding Variable - Button, 2 Secondary DN's.
  - d. Package EZ2A - Low Speed DSL, 2 B-channel CSV/CSD - Channel Activation, 2 B-channel CSV/CSD - User Profile, 2 Additional Call Appearances, 1 Conference Drop Hold & Transfer, 1 Call Forwarding Variable - Button, 2 Secondary DN's, Visual Message Waiting, Call Forwarding Busy Line, Call Forwarding Don't Answer. Voice Mail service will be allowed with this package.
3. Package Rates and Charges
  - a. Per DSL
    - (1) Packages - Credit Per DSL

|                          | <b>Installation<br/>Charge</b> | <b>Monthly<br/>Credit</b> | <b>USOC</b>  |
|--------------------------|--------------------------------|---------------------------|--------------|
| (a) Package EZ1 Credit   | -                              | <b>\$5.50</b>             | <b>LPE01</b> |
| (b) Package EZ1-A Credit | -                              | <b>6.00</b>               | <b>LPE1A</b> |
| (c) Package EZ2 Credit   | -                              | <b>6.50</b>               | <b>LPE02</b> |
| (d) Package EZ2-A Credit | -                              | <b>7.00</b>               | <b>LPE2A</b> |

**F. Termination Charges**

IRS lines placed in service under a Rate Stability Plan will incur a Termination Charge at the date of termination if the customer terminates or disconnects the service prior to fulfilling the minimum service period. Termination Charges will not apply for IRS lines upgrading to another service offered by the Company with a contract period equal to or longer than the existing ISDN contract.

1. Rate Stability Plan of 24 months -  
Termination Charge if service disconnected within:

|                              | <b>Termination<br/>Charge</b> | <b>USOC</b>  |
|------------------------------|-------------------------------|--------------|
| (a) 1-12 months <sup>1</sup> | <b>\$200.00</b>               | <b>LPER1</b> |
| (b) 13-23 months             | <b>100.00</b>                 | <b>LPER2</b> |

**Note 1:** This Termination Charge also applies at the date of termination if a customer terminates or disconnects prior to fulfilling the three months minimum service period. (M2)

M1 - Material appearing on this page previously appeared on page(s) 5 of this section.

M2 - Material previously appearing on this page now appears on page(s) 6.1 of this section.

## A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)

### A142.2 ISDN - Residence Service (IRS) (Cont'd)

#### A142.2.5 Optional Features

##### A. Optional Features

Customers are required to subscribe to ISDN - Residence Service (IRS) before ordering these features. Calling/Called Number Delivery, Calling Name Delivery and Call Hold are provided with this service. Features are available to increase the capability of IRS and may be subscribed to on an as needed basis. Availability of features are limited to where facilities permit and may be limited by central office type and switch load.

Where facilities permit, Call Forwarding features will provide for one calling path. Up to nine (9) additional call forwarding paths may be added with a monthly charge per calling path.

Availability of features as described in paragraphs 1 and 2 is dependent upon whether the central office is equipped with custom ISDN or National ISDN.

##### 1. Features for use with Electronic Key Telephone Service (EKTS):

This option provides a group of features that increase the user's voice terminal flexibility and offers the functionality of a key system to groups of users with EKTS equipment.

- a. Shared Primary DN - This is a primary DN that appears on one or more terminals.
- b. Secondary-Only DN - This is a secondary DN that appears on one or more terminals, but is not the primary DN on any of those terminals.
- c. Shared Secondary-Only DN - First Appearance - the first appearance of a secondary DN that appears on more than one terminal but is not the primary DN on any of those terminals.
- d. Key Short Hunt - This feature enhances call coverage by delivering key-set DN Short Hunt capability to standard-feature ISDN Voice terminals.
- e. Shared Non-ISDN DN - This feature allows call coverage for an analog set.
- f. Privacy Release - This is a privacy feature that allows a customer to specify, on an EKTS group basis, that no other user can bridge on to calls. On a call by call basis, this feature can be disabled to allow bridging to occur.
- g. Manual Exclusion - This is the opposite of Privacy Release. On a call by call basis the user can restrict bridging.
- h. EKTS Intercom Calling - Dial - This feature allows an EKTS user to call other terminals in the EKTS group with one or two-digit dialing.
- i. EKTS Intercom Calling - Automatic - This feature allows an EKTS user to call another terminal in the EKTS group by activating a button on the EKTS set.
- j. EKTS Intercom Calling-Call Appearance - This feature allows EKTS Intercom Calling to be provisioned on a Call appearance.
- k. Conference, Drop, Hold, Transfer - EKTS
  - Conference - This feature allows the user to add a third party to an existing conversation. This feature is for use with voice calls only.
  - Drop - This central office based feature allows the user to disconnect the last party added to a conference call.
  - Hold - Suspends an established call while another action is taking place.
  - Transfer - This feature allows the user to transfer a call to another DN. This feature is for use with voice calls only. This feature may require an additional call appearance or an additional DN. This feature is available for use with EKTS sets with service provisioned in the EWSD switch. EWSD subscribers with Non-EKTS sets and 5ESS/DMS subscribers should use the Conference, Drop, Hold and Transfer feature in the following section.

##### 2. The following features are available with either Custom ISDN or National ISDN. National ISDN customers may purchase these features for use with either EKTS sets or non-EKTS sets.

- a. Call Forwarding Variable - This feature allows the ISDN user to have the ability to forward all incoming calls to a user specified directory number.
- b. Call Forwarding Variable - Feature Button - This feature is the same as Call Forwarding Variable except that it is activated by a feature button.
- c. Call Forwarding - Busy Line - This feature automatically routes the calls to a preselected number when the called line is busy. This feature may be either fixed (changeable by service order) or programmable (customer changeable) by station user via feature activation code.
- d. Call Forwarding - Don't Answer - This feature automatically routes calls to a preselected number when the called line does not answer in a preset ringing cycle. This feature may be either fixed (changeable by service order) or programmable (customer changeable) by station user via feature activation code.
- e. Call Pickup - Allows a user to answer calls directed to another line in the same preset Call Pickup Group.

M1 - Material appearing on this page previously appeared on page(s) 6 of this section.

M2 - Material previously appearing on this page now appears on page(s) 6.2 of this section.

## **A142. OBSOLETE SERVICE OFFERINGS INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

### **A142.2 ISDN - Residence Service (IRS) (Cont'd)**

#### **A142.2.5 Optional Features (Cont'd)**

##### **A. Optional Features (Cont'd)**

##### **2. (Cont'd)**

- f. Conference, Drop, Hold, Transfer - (M1)
  - Conference - allows the user to add a third party to an existing conversation. This feature is for use with voice calls only. (M1)
  - Drop - This central office based feature allows the user to disconnect the last party added to a conference call. (M1)
  - Hold - allows the user to place a call on hold by pressing the function button. Any set with the call appearance for the call on hold can pick up the call by pressing the call appearance button. (M1)
  - Transfer - This feature allows the user to transfer a call to another DN. This feature is for use with voice calls only. (M1)
    - This feature may require an additional call appearance or an additional DN.
- g. Six-Way Conference, Drop, Hold, Transfer - This feature has the same functionality as Conference, Drop, Hold, Transfer feature except that six-way conference is allowed. (M1)
- h. Speed Calling - This feature allows each user to assign up to thirty telephone numbers to a two-digit code for the purpose of enabling abbreviated dialing.
- i. Calling/Called Number Delivery/Calling Name Delivery-National ISDN - This feature provides the user who is receiving/originating a call with information about the calling/called party and the facility or destination and is provided with IRS. Some "privacy" options may be in effect in certain areas and will be located in Section A13.
- j. Visual Message Waiting Indicator - Provides the user of a message service with a visual indication that a message is waiting.
- k. Audible Message Waiting Indicator - Provides the user of a message service with an audible indicator that a message is waiting.
- l. Additional Call Appearance - PDN or DN - This feature allows the terminal to have more than one DN button assigned to the same DN or Primary Directory Number (PDN).
- m. Call Tracing - This feature enables the customer to initiate an automatic trace of the last call received. Upon activation by the customer, the network automatically sends a message to the Company's Security Department indicating the calling number, the time the call was received, and the time the trace was activated. The customer using this feature would be required to contact the local business office for further action.
- n. Call Return - This feature enables a customer to place a call to the telephone number associated with the most recent call received, whether or not the call was answered or the number is known. The customer can dial a code or press a feature button to request that the network place the call.
  - If the called line is not busy, the call is placed. If the called line is busy, a confirmation announcement is heard. Once the customer hangs up, the network will monitor the busy/idle status of both lines every forty-five seconds for up to thirty minutes. If during the queuing process both lines become idle, the customer is alerted that the network is ready to place the call. When the customer picks up the telephone, the call will automatically be placed. If unanswered by the customer the alerting will repeat every five minutes until answered, or for the remainder of the thirty minute monitoring interval. Multiple numbers may be placed in queue. The first idle number will be connected first. Both the customer and the called party may originate and receive calls without affecting the call return feature status.
- o. Selective Call Forwarding - Allows the customer to transfer selected calls to another telephone number. A screening list of up to six numbers is created by the customer and placed in the network memory via an interactive dialing sequence. Subsequently, calls are forwarded to the Call Forwarding telephone number only if the calling number can be obtained and is found to match a number on the screening list.
  - If the customer also subscribes to Call Block and the same telephone number is entered on both screening lists, the Call Block feature must be deactivated to allow the call to be forwarded.
  - This feature will not work if the incoming call is from a telephone number in a hunt group unless the telephone number is the main number of the hunt group, or is Telephone Number identified. (M2)

## A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)

### A142.2 ISDN - Residence Service (IRS) (Cont'd)

#### A142.2.5 Optional Features (Cont'd)

##### A. Optional Features (Cont'd)

##### 2. (Cont'd)

- (M)
- p. Call Block - This feature provides the customer the ability to prevent incoming calls from up to six different telephone numbers.  
 A screening list is created by the customer either by adding the last number associated with the line (incoming or outgoing), or by preselecting the telephone numbers to be blocked. When a call is placed to the customer's number from a number on the screening list, the caller receives an announcement indicating that the party he is attempting to call does not wish to receive calls at this time.  
 If the customer also subscribes to Selective Call Forwarding and/or Personalized Ring 6 and the same telephone numbers appear on those screening lists, Call Block will take precedence.  
 This feature will not work if the incoming call is from a telephone number in a hunt group unless the telephone number is the main number of the hunt group, or is Telephone Number identified.
- q. Personalized Ring 6 - This feature provides an alerting to the subscribing customer for up to six specific telephone numbers.  
 The customer creates a screening list of up to six telephone numbers through an interactive dialing sequence. When a call is received from one of the predetermined telephone numbers, the customer is alerted. Calls from the telephone numbers not included on the screening list will produce a normal ring.  
 When a telephone number on the Personalized Ring 6 screening list also appears on the Selective Call Forwarding list, the Preferred Call Forwarding will take precedence. Likewise, when the same number is shown on the Call Block list, the call will be blocked.  
 The customer's line will not produce an alert if the incoming call is from a telephone number in a hunt group unless the telephone number is the main number of the hunt group, or is Telephone Number identified.
- r. Repeat Dialing - Repeat Dialing, when activated, automatically redials the last number the customer attempted to call. If the called line is not busy, the call will be placed.  
 If the called line is busy, a confirmation announcement is heard, the customer hangs up and a queuing process begins. For the next thirty minutes both the calling and called lines are checked periodically for availability to complete the call. If during this queuing process the called line becomes idle, the customer is alerted that the network is ready to place the call. When the customer picks up the telephone, the call will automatically be placed.
- s. Call Forwarding Multiple Simultaneous - This feature allows a station line to forward more than one call at a time.
- t. Automatic Line/Direct Connect  
 Station specially programmed to dial specific internal station number or "0" or the attendant when the station user goes off-hook.
- u. Selective Call Acceptance  
 Allows customers to accept incoming voice calls only from certain telephone numbers selected by the customer.
- v. Station Restriction  
 Allows a station line to be assigned various type of restriction.
- Denied Termination allows the station line to be used for outgoing calls only. It cannot receive incoming calls. All incoming calls are routed to common intercept announcement.
  - Denied Origination from Outgoing Calls allows the station line to be used for incoming calls only. No outgoing calls can be originated from it.
- w. Redirected Number Feature – Redirected number delivery may be provided as a termination feature. If the received call has been previously forwarded, the first and last forwarding DN's will be delivered to the called party who subscribes to redirected number delivery.

---

## **A142. OBSOLETE SERVICE OFFERINGS - INTEGRATED SERVICES DIGITAL NETWORK (ISDN)**

### **A142.3 Primary Rate ISDN**

#### **A142.3.1 Reserved for Future Use**

#### **A142.3.2 Terms and Conditions**

(Obsoluted 02-29-2008, Type D. Beginning February 29, 2008, Calling Number Delivery Blocking - Permanent is not available as part of Primary Rate ISDN service for new customers, new service arrangements, rearrangements, moves or transfers. Customer arrangements with calling number delivery blocking may keep the capability for arrangements existing prior to February 29, 2008. For new customers/new service arrangements purchased on or after February 29, 2008, calling number delivery blocking is the responsibility of the customer, i.e., to be performed through their PBX or other customer premises equipment, as appropriate.)

(T)