TARIFF DISTRIBUTION

FILE PACKAGE NO.: NC-17-0012

DATE:	January 4, 2017
STATE:	NORTH CAROLINA
EFFECTIVE DATE:	01/04/2017
TYPE OF DISTRIBUTION:	Approved
TYPE OF DISTRIBUTION:	Approved

PURPOSE: Increase business Analog Private Line (APL) monthly charges

PAGE NUMBER	PAGE REVISION
10.1.2	0007
10.1.7	0006
10.1.8	0006
10.1.9	0006
10.2	0006
	10.1.2 10.1.7 10.1.8 10.1.9

NC-17-0012

EFFECTIVE: January 4, 2017

B3. CHANNELS AND EQUIPMENT

B3.4 Rates and Charges

B3.4.1 Local Channels

A. Voice Grade Per point of termination

				Nonrecurring				
				Monthly	0	Charge		
				Rate	First	Additional	USOC	
1.	Voice							
		(a)	Type 2230	83.00	\$145.60	\$145.60	P2JUX	(I)
		(b)	Туре 2231	104.00	162.25	162.25	P2JHX	(I)
		(c)	Туре 2432	151.00	203.65	203.65	P2JQX	(I)
		(d)	Туре 2434	20.00	166.50	166.50	P2JGX	(I)
		(e)	Туре 2435	164.00	365.00	365.00	P2JWX	(I)
		(f)	Type 2261 ¹	85.00	150.00	150.00	P2JLX	(I)
		(g)	Type 2462 ¹	198.00	191.45	191.45	P2JRX	(I)
2.	Data							
		(a)	Type 2260	101.00	148.88	148.88	P2JKX	(I)
		(b)	Type 2463	181.00	203.66	203.66	P2JMX	(I)
		(c)	Type 2464	181.00	203.66	203.66	P2JNX	(I)
2 1 2 N	on Wine	Conto	on Connected Chennels					

B3.4.2 Non-Wire Center Connected Channels

- A. Served Direct
 - 1. Not routed via the central office, limited to one airline mile or less

		Monthly		recurring Charge		
(a)	Series 2000	Rate \$38.00	First \$156.00	Additional \$156.00	USOC SDD2X	(I)

Note 1: Effective April 1, 2013, Dataphone Select-A-Station Service was withdrawn.

Sixth Revised Page 10.1.7

EFFECTIVE: January 4, 2017

NC-17-0012

B3. CHANNELS AND EQUIPMENT

B3.4 Rates and Charges (Cont'd

B3.4.4 Interoffice Channels¹

- A. Fixed and Mileage Charges applicable
 - 1. Voice Grade

(a)	Series 2000	Fixed Monthly Charge \$122.00	Monthly Charge Per Mile \$2.05	Nonrecuring Charge Per Channel \$48.83	USOC 3LBBS	(I)
-----	-------------	--	---	---	---------------	-----

Note 1: For method of determining mileage, see B3.1.3.A.5 concerning these channels.

NC-17-0012

EFFECTIVE: January 4, 2017

B3. CHANNELS AND EQUIPMENT

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions

A. Bridging

Bridging charges are applicable where more than two Local Channels, or one or more Local Channels and more than one Interoffice Channel, or more than one Local Channel and one Interoffice Channel are bridged or hubbed at the same wire center. No additional bridging charges are applicable for Series 1000, Types 1204 and 1205.

1. Voice Grade Bridges (Series 2000)

			Monthly Rate	Nonrecurring	USOC	
	Voice Drid		Kate	Charge	USUC	
a.	Voice Bridg					
	(1) Per Po		\$ 20.00	¢ 54 50	DOA	~
	. ,	Two-Wire (Type 2230)	\$ 20.00	\$ 54.79	BQ9	(I)
		Four-Wire (Type 2435)	20.00	62.00	BQ9	(I)
b.	Data Bridgi	e				
	(1) Per Po	ort				
	(a)	Four-Wire (Types 2463 and 2464)	20.00	63.00	BQ9	(I)
c.	Telemetry a	and Alarm Bridging-Split Band, Active Bridging				
	(1) Comn	non Equipment, per central office				
	(a)	First bridging shelf, capacity of 48 two-wire	413.00	430.00	XW1	(I)
		connections				
	(b)	Additional bridging shelf, capacity of 56 two-wire	370.00	390.00	XW2	(I)
		connections installed subsequent to the first bridging				
		shelf				
	(c)	Additional bridging shelf, capacity of 56 two-wire	164.00	240.00	XW8	(I)
		connections installed at the same time as the first				
		bridging shelf				
		hel connections, per channel connected				
	. ,	Remote station channel connection	12.00	22.30	XW3	(I)
	()	Mid-link channel connection, first channel	38.00	65.00	XW4	(I) (I)
		,	20.00	47.64	XW5	
	(c)	Mid-link channel connection, subsequent channels	20.00	47.04	AWS	(I)

EFFECTIVE: January 4, 2017

NC-17-0012

B3 CHANNELS AND EQUIPMENT

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions

B. Signaling Arrangements

Signaling arrangements are provided at the customer's option to arrange channels for suitable signaling. Signaling is required on all off-premises extension channels and tie line channels associated with PBX (or similar) systems.

			Nonrecurring Charge			
			Monthly Rate	Initial	Subseque	nt USOC
1.	Per local chan	inel				
	(a)	Ringdown-Manual	\$ 1.00	\$10.50	\$12.51	SL3
	(b)	Ringdown-Automatic	1.00	28.25	33.65	SL5
	(c)	E & M Type	12.00	35.50	42.28	SLM
	(d)	Type A (0-199 ohms)	20.00	28.00	33.65	SAL
	(e)	Type B (200-899 ohms)	12.00	18.00	21.44	SAU
	(f)	Type C (900 or more ohms)	1.00	3.00	3.57	SAY
2.	Per Channel r	not routed via the Central Office or betwe	en			
	buildings on t	he same continuous property				
	(a)	Type A Arrangement (0-199 ohms)	14.10	41.10	49.10	SALSD
	(b)	Type B Arrangement (200-899 ohms)	4.55	30.00	35.70	SAUSD
	(c)	Type C Arrangement (900 or more	-	-	-	SAYSD
		ohms)				
3.	Per Channel r	not routed via the Central Office or betwe	en			
	buildings on	the same continuous property or channel	els			
	within the san	ne building				
	(a)	E & M Type	5.75	33.00	39.25	SLMEM
		• •				

NC-17-0012

EFFECTIVE: January 4, 2017

Envelope Delay Distortion

B3. CHANNELS AND EQUIPMENT

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions (Cont'd)

C. Conditioning (Voice Grade Services)

1. Conditioning provides more specific transmission characteristics for data services. There are two types of C-conditioning and one type of D-conditioning, each with different technical specifications. C-Type conditioning controls attenuation distortion and envelope delay distortion. D-Type conditioning controls the signal to C-notched noise ratio and intermodulation distortion.

Conditioning is charged for on a per Local Channel basis for two-point and multi-point service. For two-point services the parameters apply to each service. For multi-point services the parameters apply to any path between any two service points.

2. The types and description of the available conditioning options are as follows: Type Conditioning Frequency Response Specification

Type Conditioning	Frequency Response Specification	Specification	Distortion
C1 (two-point or multipoint)	300-2700 Hz,	1000-2400 Hz, 1	ess
	-2dB to $+6dB$.	than 1000 micro	seconds
	1000-2400 Hz,		
	-1dB to $+3$ dB.		
	300-3000 Hz,		
	-3dB to +12dB.		
C2 (two-point or multipoint)	300-3000 Hz,	1000-2600 Hz, I	ess
	-2dB to $+6dB$.	than 500 micros	seconds
	500-2800 Hz,	600-2600 Hz, le	SS
	-1dB to $+3$ dB.	than 1500 micro	seconds
		500-2800 Hz, le	SS
		than 3000 micro	seconds
		Non-Linear	Distortion
	C-Notched Noise	2nd Order	3rd Order
		Distortion	Distortion
D1 (two-point)	Noise level 28dB	35dB below	40dB below
	below signal level	signal level	signal level
(Obsoleted, See B103.8.1)			

3. When a channel is equipped with Type D1 conditioning and is utilized for voice communications, the Company does not undertake to represent that the channel will be suitable for such voice transmission.

		Monthly Rate	Initial	Subsequent	USOC	
4.	C-Type Conditioning					
	a. C-Type Conditioning is available for Types 2463 and 2464.					
	(1) C-Types of Conditioning per local channel					
	(a) C1-Type	\$7.00	\$8.50	\$10.12	P2W	(I)
	(b) C2-Type	-	30.00	35.73	P3W	
5.	D-Type Conditioning					
	a. D-Type Conditioning					
	(1) Available for Types 2463 and 2464					
	(a) D1-Type	18.00	30.00	35.73	QHA	(I)
	(b) (Obsoleted, See B103.8.1)					