TARIFF DISTRIBUTION

FILE PACKAGE NO.: SC-19-0017

DATE: March 1, 2019

STATE: SOUTH CAROLINA

EFFECTIVE DATE: 03/01/2019

TYPE OF DISTRIBUTION: Approved

PURPOSE: Increase business Analog Private Line (Channels) monthly charges

<u>PAGE NUMBER</u>	PAGE REVISION
8	0020
9	0018
10	0018
11	0015
12	0014
	8 9 10 11

SC-19-0017 EFFECTIVE: March 1, 2019

B3. CHANNELS

B3.4 Rates and Charges

B3.4.1 Local Channels

A. Sub Voice Grade (Obsoleted, See B103.)

					Monthly	Nonrecu	rring Charge		
					Rate	First	Additional	USOC	
В.		ice Grade							
	Per	point of ter	mina	ation					
	1.	Voice							
			(a)	Type 2230	\$475.00	\$496.80	\$165.60	P2JUX	(I)
			(b)	Type 2231	475.00	496.80	165.60	P2JHX	(I)
			(c)	Type 2432	712.00	561.60	208.80	P2JQX	(I)
			(d)	Type 2434	148.00	237.60	119.52	P2JGX	(I)
			(e)	Type 2435	712.00	532.80	187.20	P2JWX	(I)
			(f)	Type 2261	552.00	835.20	352.80	P2JLX	(I)
			(g)	Type 2462	657.00	813.60	338.40	P2JRX	(I)
	2.	Data							
			(a)	Type 2260	552.00	597.60	230.40	P2JKX	(I)
			(b)	Type 2463	752.00	597.60	230.40	P2JMX	(I)
			(c)	Type 2464	752.00	590.40	223.20	P2JNX	(I)
C.	Wit	red Music							
	1.	Per point	of te	ermination					
			(a)	Type 6210	276.00	806.40	331.20	P6JJX	(I)
			(b)	Type 6211	287.00	806.40	331.20	P6JAX	(I)
			(c)	Type 6212	358.00	928.80	432.00	P6JBX	(I)
			(d)	Type 6213	402.00	950.40	453.60	P6JCX	(I)
			(e)	Type 6214	276.00	806.40	331.20	P6JKX	(I)
			(f)	Type 6215	280.00	806.40	331.20	P6JEX	(I)
			(g)	Type 6216	358.00	928.80	432.00	P6JNX	(I)
			(h)	Type 6217	402.00	950.40	453.60	P6JGX	(I)

B3.4.2 Non-Wire Center Connected Channels (Obsoleted, See Section B103)

Page 8.1 is hereby deleted in its entirety and removed from this Guidebook.

SC-19-0017 EFFECTIVE: March 1, 2019

B3. CHANNELS

B3.4 Rates and Charges (Cont'd) B3.4.3 Interoffice Channels¹

JJ.T.	JIII	cionne chai	ilicis					
				Fixed Monthly Rate	Monthly Rate Per Mile	Nonrecurring Charge	USOC	
A.	Fixe	ed and Mileage	Charges applicable, per channel					
	1.	Sub Voice Gr	ade - Series 1000 (Obsoleted, See B	103.)				
	2.	Voice Grade S	Service - Series 2000					
		(a)	1 thru 8 Miles	\$685.00	\$52.00	\$151.20	3LBBS	(I)
		(b)	9 thru 25 Miles	685.00	52.00	151.20	3LBBS	(I)
		(c)	Over 25 Miles	685.00	52.00	151.20	3LBBS	(I)
	3.	Wired Music	- Series 6000 3.0 kHz					
		Types 6210, 6	5211, 6214 and 6215					
		(a)	1 thru 8 Miles	396.00	15.00	119.52	3LBCS	(I)
		(b)	9 thru 25 Miles	396.00	15.00	119.52	3LBCS	(I)
		(c)	Over 25 Miles	396.00	15.00	119.52	3LBCS	(I)
	4.	Wired Music	- Series 6000 5 kHz					
		Types 6212 a:	nd 6216					
		(a)	1 thru 8 Miles	410.00	28.00	108.00	3LBDS	(I)
		(b)	9 thru 25 Miles	410.00	28.00	108.00	3LBDS	(I)
		(c)	Over 25 Miles	410.00	28.00	108.00	3LBDS	(I)
	5.	Wired Music	- Series 6000 8 kHz					(I)
		Types 6213 a	and 6217					
		(a)	1 thru 8 Miles	553.00	46.00	108.00	3LBES	(I)
		(b)	9 thru 25 Miles	553.00	46.00	108.00	3LBES	(I)
		(c)	Over 25 Miles	553.00	46.00	108.00	3LBES	(I)

Note 1: For method of determining mileage, see B3.3.3.A.

Page 9.1 is hereby deleted in its entirety and removed from this Guidebook.

SC-19-0017 EFFECTIVE: March 1, 2019

B3. CHANNELS

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions

A. Bridging

Bridging charges are applicable where more than two Local Channels, or one or more Local Channels and more than one Interoffice Channel, or more than one Local Channel and one Interoffice Channel are bridged or hubbed at the same wire center. No additional bridging charges are applicable for Series 1000, Types 1204 and 1205.

				Nonrecurring	Monthly		
				Charge	Rate	USOC	
1.			Bridges (Series 2000)				
		oice Bri	2 2				
	(1)						
		(a)	Two-Wire (Type 2230)	\$56.16	\$182.00	BQ9	(I)
		(b)	Four-Wire (Type 2435)	56.16	236.00	BQ9	(I)
		ta Brid					
	(1)) Per	Port				
		(a)	Four-Wire (Types 2463 and 2464)	61.92	341.00	BQ9	(I)
	c. (D	ELETE	ED)				
	d. (D	ELETE	ED)				
	e. Te	lemetry	y and Alarm Bridging - Split Band, Active Bri	dging			
	(1)) Con	nmon Equipment, per central office				
		(a)	First bridging shelf, capacity of 48	365.00	681.00	XW1	(I)
			two-wire connections				
		(b)	Additional bridging shelf, capacity of	330.00	681.00	XW2	(I)
			56 two-wire connections installed				
			subsequent to the first bridging shelf				
		(c)	Additional bridging shelf, capacity of	205.00	345.00	XW8	(I)
			56 two-wire connections installed at the				
			same time as the first bridging shelf				
	(2)) Cha	nnel connections, per channel connected				
		(a)	Remote station channel connection	40.00	28.00	XW3	(I)
		(b)	Mid-link channel connection, first	47.00	68.00	XW4	(I)
			channel				
		(c)	Mid-link channel connection,	47.00	68.00	XW5	(I)
			subsequent channels				
2.	Wired	Music	Bridges (Series 6000)				
			on Amplifiers				
	(1)) Per	Port				
		(a)	Each	50.40	2.88	6LE	

EFFECTIVE: March 1, 2019 SC-19-0017

B3. CHANNELS

B3.4 Rates and Charges (Cont'd) B3.4.4 Optional Features and Functions (Cont'd)

Nonrecurring	Monthly	
Charge	Rate	USOC

Signaling Arrangements

Signaling arrangements are provided at the customer's option to arrange channels for suitable signaling. Signaling is required on all off-premises extension channels and tie line channels associated with PBX (or similar) systems.

1. Per local channel

		Monthly	Nonrecu	irring Charge		
		Rate	Initial	Subsequent	USOC	
(a)	Ringdown - Manual	\$111.00	\$60.48	\$309.60	SL3	(I)
(b)	Ringdown - Automatic	102.00	21.60	106.56	SL5	(I)
(c)	E & M Type	102.00	61.92	273.60	SLM	(I)
(d)	Type A (0-199 ohms)	60.00	60.48	201.60	SAL	(I)
(e)	Type B (200-899 ohms)	60.00	59.04	201.60	SAU	(I)
(f)	Type C (900 or more ohms)	28.00	15.84	201.60	SAY	(I)

SC-19-0017 EFFECTIVE: March 1, 2019

B3. CHANNELS

B3.4 Rates and Charges (Cont'd)

B3.4.4 Optional Features and Functions (Cont'd)

- C. Conditioning (Voice Grade Services)
 - 1. Conditioning provides more specific transmission characteristics for data services. There are two types of C-conditioning and one type of D-conditioning, each with different technical specifications. C-Type conditioning controls attenuation distortion and envelope delay distortion. D-Type conditioning controls the signal to C-notched noise ratio and intermodulation distortion.

Conditioning is charged for on a per Local Channel basis for two-point and multi-point service. For two-point services the parameters apply to each service. For multipoint services the parameters apply to any path between any two service points.

2. The types and description of the available conditioning options are as follows:

Type Conditioning	Frequency Response Specification	Envelope Delay Distortion Specification
C1 (two-point or multipoint)	300-2700 Hz,	1000-2400 Hz, less
	-2dB to $+6dB$.	than 1000 microseconds
	1000-2400 Hz,	
	-1dB to $+3$ dB.	
	300-3000 Hz,	
	-3dB to $+12dB$.	
C2 (two-point or multipoint)	300-3000 Hz,	1000-2600 Hz, less
	-2dB to $+6dB$.	than 500 microseconds
	500-2800 Hz,	600-2600 Hz, less
	-1dB to $+3$ dB.	than 1500 microseconds
		500-2800 Hz, less
		than 3000 microseconds
		Non-Linear Distortion
	C-Notched Noise	2nd Order 3rd Order
		Distortion Distortion
D1 (two-point)	Noise level 28dB	35dB below 40dB below
-	below signal level	signal level signal level

- 3. When a channel is equipped with Type D1 conditioning and is utilized for voice communications, the Company does not undertake to represent that the channel will be suitable for such voice transmission.
- 4. C-Type Conditioning
 - a. C-Type Conditioning is available for Types 2463 and 2464.

		Monthly Rate		ring Charge Subsequent	USOC	
	(1) C-Types of Conditioning per local channel					
	(a) C1-Type	\$28.00	\$14.40	\$122.40	P2W	(I)
	(b) C2-Type	28.00	31.68	135.36	P3W	(I)
5.	D-Type Conditioning					
	a. D-Type Conditioning is available for Types 2463 a	nd 2464.				
	(1) D-Type Conditioning per local channel					
	(a) D1-Type	28.00	21.60	128.16	QHA	(I)