TARIFF DISTRIBUTION

FILE PACKAGE NO.: TN-15-0040

DATE: July 2, 2015

STATE: TENNESSEE

EFFECTIVE DATE: 07/02/2015

TYPE OF DISTRIBUTION: Approved

PURPOSE: Increase Private Line Channels (APL) monthly charges.

TARIFF SECTION	PAGE NUMBER	PAGE REVISION
H003	13.1	0013
H003	17	0010

TN-15-0040 EFFECTIVE: July 2, 2015

B3. CHANNELS

B3.4 Rates And Charges (Cont'd)

B3.4.2 Non-Wire Center Connected Channels (Obsoleted, See Section B103) B3.4.3 Interoffice Channels¹

A. Fixed and Mileage Charges

		Fixed Monthly Charge	Monthly Charge Per Mile	Nonrecurring Charge Per Channel	USOC	
1.	Sub Voice Grade - Series 1000 ²					
	(a) 1 thru 8 Miles	\$121.00	\$ 12.00	-	3LBAS	
	(b) 9 thru 25 Miles	121.00	12.00	-	3LBAS	
	(c) Over 25 Miles	121.00	12.00	-	3LBAS	
2.	Voice Grade Service - Series 2000					
	(a) 1 thru 8 Miles	378.00	30.00	\$122.75	3LBBS	(I)
	(b) 9 thru 25 Miles	378.00	30.00	122.75	3LBBS	(I)
	(c) Over 25 Miles	378.00	30.00	122.75	3LBBS	(I)

Note 1: For method of determining mileage, see B3.3.3.A.

Note 2: Metallic interoffice channels are no longer available for new installations, moves or transfers. Metallic interoffice facilities are in continually decreasing supply due to modernization programs that replace existing metallic interoffice with non-metallic facilities such as fiber optics.

TN-15-0040 EFFECTIVE: July 2, 2015

B3. CHANNELS

B3.4 Rates And Charges (Cont'd)

B3.4.4 Optional Features And Functions (Cont'd)

C. Conditioning (Voice Grade Services) (Cont'd)

2. The types and description of the available conditioning options are as follows:

Type Conditioning Frequency Response Specification Envelope Delay Distortion

Type Conditioning	Frequency Response Specification	Envelope Delay Dist Specification	ortion		
C1 (two-point or multipoint)	300-2700 Hz,	1000-2400 Hz, less			
	-2dB to $+6dB$.	than 1000 microsecon	nds		
	1000-2400 Hz,				
	-1dB to $+3$ dB.				
	300-3000 Hz,				
	-3dB to $+12dB$.				
C2 (two-point or multipoint)	300-3000 Hz,	1000-2600 Hz, less			
	-2dB to $+6dB$.	than 500 microsecone	ds		
	500-2800 Hz,	600-2600 Hz, less			
	-1dB to $+3$ dB.	than 1500 microsecor	roseconds		
		500-2800 Hz, less	Hz, less		
		than 3000 microseconds			
		Non-Linear Distortion			
	C-Notched Noise	2nd Order	3rd Order		
		Distortion	Distortion		
D1 (two-point)	Noise level 28dB	35dB below 40	0dB below		
	below signal level	signal level s	signal level		

When a channel is equipped with Type D1 conditioning and is utilized for voice communications, the Company does not undertake to represent that the channel will be suitable for such voice transmission.

		Nonrecurring				
		Monthly	Monthly Charge			
		Rate	Initial	Subsequent	USOC	
4.	C-Type Conditioning					
	a. C-Type Conditioning is available for Types 2463 and 2464.					
	(1) C-Types of Conditioning per local channel					
	(a) C1-Type	\$14.00	\$11.00	\$68.20	P2W	(I)
	(b) C2-Type	14.00	23.10	78.10	P3W	(I)
5.	D-Type Conditioning					
	a. D-Type Conditioning is available for Types 2463 and 2464.					
	(1) D-Type Conditioning per local channel					
	(a) D1-Type	14.00	17.60	72.60	QHA	(I)